

YORK ABRASIVES Flap Discs

High performance alternative to sanding discs. Have the advantage over depressed centre grinding discs on light gauge sheet metal where surface finish is important. Overlapped abrasive strips slowly wear away revealing fresh abrasive, ensuring the disc always cuts effectively, reducing clogging and providing constant finish throughout disc life. No backing pads needed. Safe to use at 80m/s on any grinder. Tested at 150m/s and approved by the German Grinding Wheel Authority (DSA). Available in two grades and with two types of backing.



Precision Layered



Aluminium Oxide Grade Glass Fibre-Backed (General-purpose, non-scratch).



Grit	Weight per 10	Order Code YRK-220	Price/1 THB
100mm Dia x 16mm Bore 15,300 MOS (rpm)			
P36	0.70kg	-9410K	49.00
P40	0.70kg	-9420K	49.00
P60	0.65kg	-9430K	49.00
P80	0.60kg	-9440K	49.00
P120	0.55kg	-9450K	49.00
115mm Dia x 22mm Bore 13,300 MOS (rpm)			
P36	0.95kg	-9510K	57.00
P40	0.90kg	-9520K	57.00
P60	0.85kg	-9530K	57.00
P80	0.75kg	-9540K	57.00
P120	0.75kg	-9550K	57.00
125mm Dia x 22mm Bore 12,000 MOS (rpm)			
P36	1.30kg	-9610K	65.00
P40	1.20kg	-9620K	65.00
P60	1.10kg	-9630K	65.00
P80	1.00kg	-9640K	65.00
P120	0.90kg	-9650K	65.00
180mm Dia x 22mm Bore 8,600 MOS (rpm)			
P36	2.40kg	-9710K	118.00
P40	2.30kg	-9720K	130.00

Zirconium Grade Glass Fibre-Backed (For stainless steel, non-scratch).



Grit	Weight per 10	Order Code YRK-220	Price/1 THB
100mm Dia x 16mm Bore 15,300 MOS (rpm)			
PP36	0.70kg	-8410K	65.00
P40	0.70kg	-8420K	NA
P60	0.70kg	-8430K	65.00
P80	0.60kg	-8440K	65.00
P120	0.55kg	-8450K	65.00
115mm Dia x 22mm Bore 13,300 MOS (rpm)			
P36	0.85kg	-8510K	74.00
P40	0.80kg	-8520K	74.00
P60	0.90kg	-8530K	74.00
P80	0.80kg	-8540K	74.00
P120	0.75kg	-8550K	74.00
125mm Dia x 22mm Bore 12,000 MOS (rpm)			
P36	1.20kg	-8610K	87.00
P40	1.15kg	-8620K	NA
P60	1.15kg	-8630K	87.00
P120	1.00kg	-8650K	87.00
180mm Dia x 22mm Bore 8,600 MOS (rpm)			
P36	2.60kg	-8710K	135.00
P40	2.30kg	-8720K	135.00

115mm Rust & Paint Removal Disc

Made of intertwined nylon fibres which are then immersed in synthetic resin and gently hardened. Ideal for removing old paint, rust and welding splatter without scratching the surface of the workpiece, cleaning and smoothing wood and plastic, polishing of stainless steel and removal of thermal bluing. DIN EN 13743.



Size x Bore (mm)	Maximum rpm	Order Code YRK-245	Price/1 THB
115 x 22	10,500	-3800K	620.00

Non Woven Polishing Flap Discs

High performance non-woven flap discs make an ideal choice for polishing and finishing stainless steel, carbon steel, non-ferrous metals etc. Available in two sizes and choice of coarse, medium and fine. Maximum rpm 13,280 and maximum speed 80m/s.



Size (mm)	Grade	Order Code YRK-220	Price/1 THB
115 x 22	Coarse	-9800K	410.00
115 x 22	Medium	-9810K	410.00
115 x 22	Fine	-9820K	410.00
125 x 22	Coarse	-9830K	462.00
125 x 22	Medium	-9840K	462.00
125 x 22	Fine	-9850K	462.00