# 259

PC

feature

## **Airline Fittings**

### 0 Ó ወ ≷ 0 2 ∆ir

Nominal Bore: 5mm. Flow rate @ 6 bar - 900 l/min.

Maximum working pressure: 17 bar/250psi. Adaptor series: Standard.

campressed air applications. Twist locking

Couplings

Schrader couplings and adpators,

generally suitable for most fixed

Interchangable: Cejn 317, Rectus 17.



**Standard Schrader** 

Male Thread		Female Thread		
Product Number	Thread Size	Order Code PCL-259	Price/1 THB	
Male Thread				
ACS102	R1⁄4	-2002C	2150.00	
ACS103	R <sup>3/8</sup>	-2002E	2150.00	
Female Thread				

-2002A

2080.00

#### **Standard Schrader Adaptors**

G1/4

When connected to the coupling, the adaptor can swivel, thereby elininating hose kinks.

ACS101

Nominal Bore: 5mm. Flow rate @ 6 bar - 900 l/min. Maximum working pressure: 17 bar/250psi. Coupling series: Standard.

Interchangable: Cejn 317, Rectus 17.




Product Number	Thread Size	Order Code PCL-259	Price/1 THB	
Male Thread				
ACAS104	$R^{\gamma_4}$	-1998G	420.00	
Female Thread				
ACAS105	Rp <sup>1</sup> ∕₄	-1998J	420.00	
Hose Tailpiece				
ACAS101	6mm	-1998A	420.00	
ACAS103	8mm	-1998E	420.00	
ACAS102	10mm	-1998C	420.00	



Designed for use with KOBE airline couplings. 'Third level' zinc plated for protection against corrosion.



**Genuine 'Schrader' Coupling Adaptors** Corrosive resistant finish. For use with Kobe airline couplings.



196

OS21 APAC TH 0196 indd 1

50 Years of Keeping Industry Working © 2022

#### **Heavy Duty Schrader** Couplings

Schrader heavy duty couplings and adpators, generally suitable for most fixed campressed air applications. Twist locking feature.

Nominal Bore: 8.5mm. Flow rate @ 6 bar - 500 l/min. Maximum working pressure: 17 bar/250psi. Adaptor series:Heavy Duty Adaptors. Interchangable: Cejn 499, Rectus 68.



	Product Number	Thread Size	Order Code PCL-259	Price/1 THB
Male Thread				
	ACS202	G <sup>1</sup> / <sub>4</sub>	-2003G	7030.00
	ASC203	G3/8	-2003K	5740.00
	ACS201	G <sup>1</sup> / <sub>2</sub>	-2003F	3850.00

#### **Heavy Duty Schrader** Adaptors

When connected to the coupling, the adaptor can swivel, thereby elininating hose kinks.

Nominal Bore: 8.5mm.

Flow rate @ 6 bar - 500 l/min. Maximum working pressure: 17 bar/250psi. Coupling series: Heavy Duty. Interchangable: Cejn 499, Rectus 68.



Product Number	Thread Size	Order Code PCL-259	Price/1 THB	
Male Thread				
ACAS204	R <sup>1</sup> / <sub>4</sub>	-1999X	1750.00	
ACAS205	R <sup>3/8</sup>	-1999Y	1160.00	
ACAS203	R <sup>1</sup> /2	-1999W	620.00	
Female Thread				
ACAS206	G <sup>1</sup> / <sub>4</sub>	-1999Z	1930.00	
ACAS207	G¾	-2000A	1200.00	
Hose Tailpiece				
ACAS201	10mm/3/8	-1999R	690.00	
ACAS202	12mm/1/2	-1999T	620.00	

#### **PF Adaptors**

Broomwade InstantAir was aquired by PCL in 2001 and still made in the UK. Bayonet style and are zinc plated steel. Nominal Bore: 5mm.

Flow rate @ 6 bar - 2,200 l/min. Maximum working pressure: 35 bar/508psi Couplings: PF Series.



Product Number	Thread Size	Order Code PCL-259	Price/1 THB
AA7702	R <sup>1</sup> / <sub>4</sub>	-1702B	239.00
AA7703	R <sup>3/8</sup>	-1703C	272.00
Female Thread			
AA7706	Rp <sup>1</sup> / <sub>4</sub>	-1706F	272.00
AA7707	Rp³∕8	-1707G	282.00
Hose Tailpiece			
AA7710	6mm	-1710K	293.00
AA7711	8mm	-1711L	293.00
AA7712	10mm	-1712M	304.00

#### **Euro Couplings**

Suitable for most general compressed air applications where this adaptor profile is required.

Nominal Bore: 5.5mm. Flow rate @ 6 bar - 650 l/min Maximum working pressure: 14 bar/200psi. Adaptor series: Euro. Interchangable: Aro 210, Cejn 300, JWL 522/532, Schrader Euro, Rectus 14/22.



Thread Size	Order Code PCL-259	Price/1 THB		
Male 1	Thread			
R <sup>1</sup> ⁄4	-1980A	730.00		
R³∕8	-1980B	730.00		
R <sup>1</sup> /2	-1980C	730.00		
Female Thread				
Rp¼	-1981D	730.00		
Rp <sup>3∕</sup> 8	-1981E	730.00		
Rp <sup>1</sup> ∕2	-1981F	730.00		
Hose Tailpiece				
7mm	-1979D	730.00		
8mm	-1979E	730.00		
10mm	-1979F	730.00		
	Size Male R <sup>V</sup> 4 R <sup>3</sup> 8 R <sup>V</sup> 2 Female Rp <sup>1</sup> 4 Rp <sup>3</sup> 8 Rp <sup>1</sup> 2 Hose To 7mm 8mm	$\begin{tabular}{ c c c c c } \hline Size & PCL-259 \\ \hline Male Thread \\ $\mathbb{R}^{V_4}$ & -1980A \\ $\mathbb{R}^{V_3}$ & -1980B \\ $\mathbb{R}^{V_2}$ & -1980C \\ \hline \hline Female Thread \\ $\mathbb{R}p^{V_4}$ & -1981D \\ $\mathbb{R}p^{\mathcal{F}_8}$ & -1981E \\ $\mathbb{R}p^{V_2}$ & -1981F \\ \hline $Hose Tailpiece \\ \hline $Tmm$ & -1979D \\ $\mathbb{8}mm$ & -1979E \\ \hline \end{tabular}$		

#### Euro Adaptors

Hose

Thread

Steel contruction with corrosive resistant finish. Nominal Bore: 5.5mm. Flow rate @ 6 bar - 650 l/min Maximum working pressure: 14

bar/200psi.

Coupling Series: Euro.

Interchangable:

Aro 210, Cejn 300, JWL 522/532,

Schrader Euro, Rectus 14/22.





Female Ma Thread		Thread	Hose Tailpiece	
Product Number	Thread Size	Order Code PCL-259	Price/1 THB	
	Male Thread			
ACA6912	6.35mm/1/4	-1989P	152.00	
Female Thread				
ACA6924	R <sup>1</sup> /2	-1989Q	152.00	
Hose Tailpiece				
ACA6912	6.35mm/1/ <sub>4</sub>	-1989M	152.00	
ACA6922	7.9mm/ <sup>5/</sup> 16	-1989N	152.00	
ACA6930	9.5mm/ <sup>3⁄</sup> 8	-1989R	184.00	