
KENNEDY Heavy Duty Tyre Inflator with Gauge

This heavy duty push-on inflator is of rugged construction and has a clear-view integral pressure gauge reading from 10 - 120psi. Heavy duty corrosion resistant body with brass fittings. 300psi rated fibre reinforced rubber hose.
Conforms to EC Directive 86/217/EEC.
Accuracy:
Reading scale: 2psi/50kPa (0.5bar).
Inflation range: 120psi/800kPa (8bar).





Product Number	Weight each	Order Code KEN-503	Price/1 THB
ALG120	635g	-8520K	3140.00

Heavy Duty Dial Type Tyre Inflator

This push-on type tyre inflator is robust and has a dial type pressure gauge reading up to a maximum of 170psi. The pressure gauge is protected from accidental damage by a rubber shock guard. Heavy duty corrosion-resistant body with steel operating lever, brass fittings and anti-shock rubber guard. 300psi rated fibre reinforced rubber hose.
Conforms to EC Directive 86/217/EEC.
Accuracy:
Reading scale: 2psi/10kPa (0.1bar).
Inflation range: 170psi/1200kPa (12bar).





Product Number	Weight each	Order Code KEN-503	Price/1 THB
TPG170	720g	-8480K	3833.00

PCL Tyre Inflation Equipment

Airforce Tyre Inflator
Clear dial display, modern, lightweight and shock resistant construction. Direct valve design increasing inflation and deflation rates. Built-in swivel and hanging device. Conforms to **BSEN 12645:1999**.
Calibration type: 0 - 170ibf/in² and 0 - 12bar.
Air inlet: ¼" BSP.



Product Number	Connector Type	Hose Length	Order Code PCL-259	Price/1 THB
AFG1HO3	Twin Hold-on	21"	-2004A	7780.00
AFG1HO6	Twin Clip-on	9'	-2004K	9330.00
AFG1HO8	Euro Connect on	6'	-2004T	5280.00

Accura 1 Tyre Inflator
Direct valve design increasing inflation and deflation rates with an over-pressure warning if pressure exceeds 12bar/174lbf/in²/1200kPa. Individually tested and certified, **Exceeds EC Directive 86/217/EEC**.

Reading accuracy:
0.01bar/0.2lbf/in²/1kPa.
Maximum inflation pressure:
15bar/218lbf/in²/1,500kPa.
Inflation range: 12bar/174lbf/in²/1,200kPa.
Operating temperature:
-20°C to 60°C.



Product Number	Connector Type	Hose Length	Order Code PCL-259	Price/1 THB
DAC1AO3	Twin Hold-on	21"	-3023A	10260.00
DAC1AO6	Twin Clip-on	9"	-3026D	10560.00

Tyre Valve Inflator Connector

Twin hold on connector for standard bore tyre valves. Access both inner and outer valves of twin wheel assemblies on commercial vehicles. Open connection for use with tyre inflation gauges. Black rubber handle. ¼" female air inlet thread.
Overall length: 250mm.



Product Number	Connector Type	Weight each	Order Code PCL-259	Price/1 THB
C01A03	Hold-on	100g	-3001A	1150.00

© 2022

OS21_APAC_TH_0200.indd 1 13/01/2022 09:14