HEAVY

DUTY

13mm сниск

HEAVY

DUTY

## Air Tools - Drills

# KOBE 13mm Reversible Pistol Drill

### FPD500

Suitable for high torque drilling applications as well as screwdriving, hole sawing and cylinder honing. Rubber handle provides grip and operator comfort. ½" chuck. Adjustable side handle. Short gear case design. Heavy duty gearing system with oil-less bushing. Spring loaded rotor vanes. Rear exhaust. Ball bearing construction for a long tool life.



#### 10mm Straight $K(\mathbf{0})$ Air Drill

9314.00

-2142K

#### BCSD10

500

Exhaust outlet adjusts 360° to direct air flow away from the operator. Keyless chuck and safety lever throttle. Ergonomic and comfortable hand grip.




6195.00

# 13mm Heavy Duty **Pistol Drill**

HEAVY

13mm Jacobs chuck, high reduction gearbox, high torque, with side handle,  $\frac{1}{2}$ hp motor.





Free Speed	Weight	Order Code	Price/1
(rpm)	each	<b>KBE-270</b>	THB
500	1.80kg	-1500E	7980.00

## 13mm Reversible **Heavy Duty Pistol Drill DPR813**

Jacobs chuck, thumb switch for reverse, auxiliaryhandle, suitable for screwdriving, heavy duty planetary gearing.

Air inlet thread:  $V_4$ " NPT. Minimum hose: 3/8" (10mm). Spindle thread: 3/8" - 24. Air pressure: 90psi/6.3bar.



\*Based on a 15 second cycle per minute average use.

Free Speed	Weight	Order Code	Price/1
(rpm)	each	<b>KBE-270</b>	THB
800	1.80kg	-1525F	8505.00

**KOBE** 

# 13mm Reversible Pistol Grip Drill

1.80kg

2,500

Use for drilling and screwdriving. Two speed trigger (slow speed when pushed halfway). Directional lever accessible from both sides for left/right handed use.

13mm ( $\frac{1}{2}$ ") chuck and detachable side handle included. Planetary gears for longer life and smoother running. Ergonomic comfortable grip.

-6050K

Recommended air pressure: 6.2bar (90psi). Air inlet thread:  $V_4$ " NPT. Air consumption: 4cfm\* (113ltr/min).

Minimum air hose size (ID): 3/8" (10mm). Vibration level #: 0.4m/s<sup>2</sup>

†Per EN ISO 15744:2002. #Per EN 28927-5.



**Ergonomic** comfortable grip.



Two speed trigger for slow or fast action.



Forward/ Reverse lever action.



Noise level<sup>†</sup>: 86dBA. Sound power level<sup>†</sup>: 93dBA.

Spindle thread: 3/8" - 24.

Overall length: 218mm.

Complete with industrial

\*Based on a 15 second cycle per minute average use.

Use

Free Speed	Weight	Order Code	Price/1
(rpm)	each	<b>KBE-270</b>	THB
800	1.30kg	-4330K	10490.00

205

13mm CHUCK

Use

50 Years of Keeping Industry Working