KOBE Automatic Shut-off Screwdriver

CSP005S
Heavy duty reverse action pistol grip screwdriver suitable for production and assembly applications. Push to start type with auto shut-off clutch for precision applications. Three interchangeable torque springs allow for easy conversion for new applications. ¼" hex drive. External torque adjustment does not require disassembly of the tool. Variable speed throttle. Ergonomically contoured grip for operator comfort. Handle exhaust directs air away from the workpiece and operator. Hanging ring included.

Chuck size: ¼" (6mm) hex. **Air inlet thread:** ¼" NPT.
Minimum air hose size (ID): ⅜" (10mm).
Green torque spring:* 0.6 - 2.1Nm (5 - 19in/lbs).
Black torque spring:
1.1 - 4.3Nm (10 - 38in/lbs).
Yellow torque spring:
1.7 - 5.1Nm (15 - 45in/lbs).



Air pressure: 6.3bar/90psi.
Air consumption: 4cfm* (144ltr/min).
Sound pressure level: 84dBA.
Sound power level: 93dBA.
Vibration level: <0.5m/s².
Overall length: 210mm.

CONTINUOUS USE
Designed & Rated For Continuous Use



Weight each	Order Code KBE-270	Price/1 THB
815g	-3760K	17010.00

*Based on a 15 second cycle per minute average use.

KOBE Speed Ratchets

⅜ ½

SR375 ⅜" square drive, 10mm bolt capacity.
SR500 ½" square drive, 13mm bolt capacity.

Ball type retainer, disc type reversing action, compact, lightweight design, ideal for automotive work, front exhaust.

Free speed: 150rpm. **Air inlet thread:** ¼" NPT.
Minimum air hose size (ID): 10mm (⅜").
Air pressure: 6.2bar/90psi.
Air consumption: 4cfm* (113ltr/m).
Torque: 50ft/lbs.
Overall length: 255mm.



	KBE-270 2375K	2500K
Sound pressure level:	89dBA	89dBA
Sound power level:	96dBA	89dBA
Vibration level:	4.0m/s²	4.0m/s²

*Based on a 15 second cycle per minute average use.

Model Number	Weight each	Order Code KBE-270	Price/1 THB
SR375	1.10kg	-2375K	2940.00
SR500	1.10kg	-2500K	3990.00

KOBE Speed Ratchet ¼" Square Drive

¼

R7722
Suitable for the removal and installation of threaded fasteners. Reversible hardened steel ¼" square drive. Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.

Drive size: ¼" (6mm). **Free speed:** 200rpm.
Recommended air pressure: 6.2bar/90psi. **Air consumption:** 4cfm* (113ltr/min). **Working torque range:** 7 ~ 27nm (5 ~ 20ft/lbs).
Air inlet thread: ¼" NPT. **Minimum air hose size (ID):** 10mm (⅜").
Sound pressure level: 80dBA. **Sound power level:** 88dBA.
Vibration level: 1.8m/s².
Overall length: 200mm.



Weight each	Order Code KBE-270	Price/1 THB
0.65kg	-4010K	5145.00

*Based on a 15 second cycle per minute average use.

KOBE Speed Ratchets

⅜ ½

FSR375 ⅜" square drive.
Working torque range: 5 - 20ft.lbs (7 - 27Nm).
Overall length: 205mm. **Free speed:** 200rpm.

FSR500 ½" square drive.
Working torque range: 10 - 50ft.lbs (14 - 68Nm).
Overall length: 265mm. **Free speed:** 150rpm.

Suitable for the removal and installation of threaded fasteners when doing automotive and light assembly work. Reversible hardened steel square drive. Rubber handle provides grip and operator comfort. Three planetary gears for longer life and smoother running.
Rubber cover protects the ratchet head and the workpiece.
Short body length allows access into hard to reach areas.
Low profile teasing throttle for precise speed control.
Rotating rear exhaust with baffle. Rotating air inlet to prevent the air hose tangling. Adjustable air regulator.

OPERATOR FRIENDLY
Operator Friendly Composite Handle Grip

Air inlet thread: ¼" NPT.
Minimum air hose size (ID): 10mm (⅜").
Air pressure: 6.2bar/90psi.
Air consumption: 4cfm* (113ltr/min).



	KBE-270 2360K	2300K
Sound pressure level:	84dBA	80dBA
Sound power level:	88dBA	87dBA
Vibration level:	1.8m/s²	2.6m/s²

Model Number	Weight each	Order Code KBE-270	Price/1 THB
FSR375	640g	-2360K	4725.00
FSR500	1.20kg	-2300K	5040.00

*Based on a 15 second cycle per minute average use.

© 2022

OS21_APAC_TH_0215.indd 1 07/12/2021 10:04