## Airline Fittings

# PF CL Couplings

Designed to offer a competitive alternative to the genuine Schrader range Nominal Bore: 5mm Flow rate @ 6 bar -

2,200 l/min Maximum working pressure: 35 bar/508psi Adaptors: PF Series



Male	Female	Hose
Thread	Thread	Tailpiece

Product Number	Thread Size	Order Code <b>PCL-259</b>	Price/1 THB	
Male Thread				
AC77CM	$R^{1\!/_{\!\!4}}$	-1982S	885.00	
AC77EM	R³⁄8	-1982R	885.00	
AC77JM	$R^{1/2}$	-1982V	885.00	
Female Thread				
AC77CF	Rp <sup>1</sup> ∕ <sub>4</sub>	-1982Q	885.00	
AC77EF	Rp³⁄8	-1982Y	885.00	
AC77JF	$Rp^{1/2}$	-1982W	885.00	
Hose Tailpiece				
AC7706	6mm	-1982B	885.00	
AC7708	8mm	-1982C	885.00	
AC7710	10mm	-1982H	885.00	
AC7713	13mm	-1982J	885.00	

### **KF Couplings**

Excellent flow characteristics for industrial applications. Nominal Bore: 7.6mm Flow rate @ 6 bar -2,100 l/min Maximum working pressure: 35 bar/508 psi **Adaptors: KF Series** 

Interchangable: Cein 314/315, Nitto Kohki 200, Rectus 13



Male Female Thread Thread

Product	Thread	Order Code	Price/1	
Number	Size	PCL-259	THB	
	Male T	hread		
AC78CM	$R^{\eta_4}$	-1520A	1540.00	
AC78EM	R <sup>3/</sup> 8	-1520B	1540.00	
AC78JM	$R^{\!$	-1520C	1540.00	
	Female	Thread		
AC78CF	Rp <sup>1</sup> ∕₄	-1520D	1540.00	
AC78EF	Rp³⁄8	-1520E	1540.00	
AC78JF	$Rp^{1/2}$	-1520F	1540.00	
Hose Tailpiece				
AC7806	6mm	-1520G	1540.00	
AC7808	8mm	-1520H	1540.00	
AC7810	10mm	-1520J	1540.00	
AC7813	13mm	-1520K	1540.00	

### **ISO B12 Adaptors**

For use with the ISO B12 Series coupling range. Nominal Bore: 5.5mm Flow rate @ 6 bar -117 cfm @ 100 psi Maximum working pressure: 35 bar/508psi Couplings: ISO B12 Series







Female Thread Male Hose Thread Tailpiece

Product Number	Thread Size	Order Code <b>PCL-259</b>	Price/1 THB
	Male T	hread	
AA7502	R <sup>1</sup> ⁄ <sub>4</sub>	-1502A	270.00
AA7503	R3/8	-1502B	303.00
AA7504	$R^{1\!/}_2$	-1502C	575.00
Female Thread			
AA7506	Rp <sup>1</sup> ⁄₄	-1502D	270.00
AA7507	Rp³⁄8	-1502E	303.00
Hose Tailpiece			
AA7510	6mm	-1502F	270.00
AA7511	8mm	-1502G	270.00
AA7512	10mm	-1502H	270.00
AA7513	13mm	-1502J	270.00

#### **ISO B12 Couplings**

Excellent flow characteristics for industrial applications. Nominal Bore: 5.5mm Flow rate @ 6 bar - 1,100 l/min Maximum working pressure: 35 bar/508psi Adaptors:

ISO B12 Series Interchangable: Cejn 310, Hanson 3000, Legris 24, Rectus 23/24







Male **Female** Hose **Thread Thread** Tailpiece

Product Number	Thread Size	Order Code PCL-259	Price/1 THB	
	Male 1	hread		
AC75CM	$R^{1/4}$	-1530A	1540.00	
AC75EM	R3/8	-1530B	1540.00	
AC75JM	$R^{1/2}$	-1530C	1540.00	
	Female	Thread		
AC75CF	Rp <sup>1</sup> ⁄₄	-1530D	1540.00	
AC75EF	Rp³⁄8	-1530E	1540.00	
AC75JF	$Rp^{1/2}$	-1530F	1540.00	
Hose Tailpiece				
AC7506	6mm	-1530G	270.00	
AC7508	8mm	-1530H	1540.00	
AC7510	10mm	-1530J	1540.00	
AC7513	13mm	-1530K	1540.00	

#### **KF Adaptors**

For use with the KF Series coupling range. Nominal Bore: 7.6mm Flow rate @ 6 bar -117 cfm @ 100psi Maximum working pressure:

35 bar/508psi **Couplings:** KF Series



Male	Female	Hose
Thread	Thread	Tailpiec

	Product	Thread	Order Code	Price/1
	Number	Size	PCL-259	THB
		Male 1	hread	
	AA7802	$R^{1/4}$	-1510A	270.00
	AA7803	R <sup>3/</sup> 8	-1510B	303.00
	AA7804	$R^{1/2}$	-1510C	575.00
Female Thread				
	AA7806	Rp <sup>1</sup> ∕₄	-1510D	270.00
	AA7807	Rp³⁄8	-1510E	303.00
	AA7808	$Rp^{1/2}$	-1510F	575.00
Hose Tailpiece				
	AA7810	6mm	-1510G	270.00
	AA7811	8mm	-1510H	270.00
	AA7812	10mm	-1510J	270.00
	Δ Δ7813	13mm	-1510K	270.00

#### Mini Speed Regulator

For use in conjunction with airline couplings. Case hardened with zinc finish. Male threaded tailpieces for connecting a hose to a female fitting.



Product	Thread	Order Code <b>PCL-259</b>	Price/1
Number	Size		THB
APA91	$R^{\mathcal{V}_4}$	-2028H	566.00



50 Years of Keeping Industry Working