Cold Chisels & Pry Bars



Contractor **Flat Cold Chisels**

Manufactured from high quality octagonal chrome vanadium steel with a ground cutting edge, in accordance with BS 3066. For use on brickwork, masonry and cold metals.

	SITESAF SSF-505-120 A MAN TH PADR		
		STTESAFE SS-505-1210K Andre service	
Width x Length	Octagon	Order Code	Price/1
(mm)	(mm)	SSF-505	THB
12 x 200	11	-1060K	132.00
12 x 200 c/w guard		-1070K	264.00
18 x 200	16	-1100K	206.00
18 x 200 c/w guard		-1110K	334.00
18 x 255	16	-1120K	214.00
18 x 255 c/w guard		-1130K	398.00
25 x 200	22	-1160K	347.00
25 x 200 c/w guard		-1170K	462.00
25 x 255	22	-1180K	398.00
25 x 255 c/w guard		-1190K	536.00
25 x 305	22	-1200K	462.00
25 x 305 c/w guard		-1210K	557.00

Contractor Cross Cut Chisel

Chrome vanadium - channelling brickwork.	used for		SITESAFE.) SSF-505-1260K
Width x Length (mm)	Octagon (mm)	Order Code SSF-505	Price/1 THB
6 x 150	12	-1260K	204.00

Contractor Brick Bolster Chisels

Chrome vanadium used for splitting bricks.

Width x Length

(mm)

75 x 230

75 x 230 c/w guard 100 x 230

100 x 230 c/w guard



-1330K

819.00

Contractor Electrician's Floor Chisels

22

Chrome vanadium - hardened and tempered cutting edge. For cutting the tongue in tongued and grooved floorboards.	ITTEATE Design	

Width x Length (mm)	Octagon	Order Code SSF-505	Price/1 THB
((((((((((((((((((((((((((((((((((((((((mm)	335-303	IHD
55 x 230	16	-1360K	536.00
55 x 230 c/w guard	10	-1370K	599.00

Electric **Engraver Kit**

Electric hand held engraver with positive on/off switch and 5 position stroke adjuster for varied engraving depths. For use on metals, plastics, glass, ceramics, wood and leather. Supplied with two Carbide steel engraving tips and an alphanumeric template.

- 5-Position adjustable
- engraving depthSoft grip
- Positive On/Off
- 1.8m cable
- Includes 2 tips and template for letters and numbers

	Product Number	Voltage	RPM	Weight	Order Code OSA-279	Price/1 THB	-
-	ENG003	2300	6000	each 375g	-9810K	724.00	
		50	Years	of Keeni	na Industr	w Worki	<u> </u>

50 Years of Keeping Industry Working © 2022

Wrecking & **Pry Bars**

Manufactured from heat treated carbon steel. Ideal for dismantling timber constructions, opening packing cases and removing nails (depending on the type of bar).

Chisel and V-Notch Wrecking Bar

For general dismantling and stripping applications, within a wide range of industries.

Length	Order Code KEN-505	Price/1 THB
450mm	-7180K	494.00
600mm	-7240K	620.00
750mm	-7300K	704.00

Chisel and Point Crowbar For heavy duty work.

the second se	A rest of the second	
Length	Order Code	Price/1
x Width	KEN-505	THB
900 x 38mm	-7360K	1218.00
1200 x 42mm	-7480K	1754.00
1500 x 42mm	-7600K	2562.00

Heel and Point Crowbar For heavy duty dismantling.

and the second se	the state of the s	and the second
Length x Width	Order Code KEN-505	Price/1 THB
900 x 38mm	-7690K	1218.00
1180 x 42mm	-7720K	1890.00
1500 x 45mm	-7750K	2772.00

Super Lever Pry Bars Can be used as a nail lifter, pry bar, adze or lever.

	2	0
Length x Width	Order Code KEN-505	Price/1 THB
325 x 33mm	-8200K	387.00
375 x 33mm	-8250K	431.00

Combination Sets Contains one wrecking bar and one pry bar.

2 PIECES		5	
Number of Pieces	Contents	Order Code KEN-505	Price/1 THB
2	450mm Wrecking Bar, 325mm Pry Bar	-8750K	798.00
2	600mm Wrecking Bar 375mm Pry Bar	-8760K	924.00

Scutch Holders - Carbon Steel

Used for chasing out and general masonry work.

		and man a share	
Width x Length	Octagon	Order Code	Price/1
(mm)	(mm)	KEN-505	THB
25 x 200	18	-6860K	1575.00
38 x 200	18	-6870K	1838.00
Detachable Bit For scutch chisels and	d hammers.		
Comb Type	Width	Order Code	Price/100
	(mm)	KEN-505	THB
Wide/Coarse	25	-9130K	2981.00
	38	-9140K	4442.00
Plain/Drove	25	-9230K	2981.00
	38	-9240K	4442.00

Protector Sleeves

Contoured high impact resistant plastic grips redirects the force of miss-hits safely away from your hands preventing injury. Suitable for use with octagonal cold chisels.

To Suit Octagon Size	Length (mm)	Order Code KEN-505	Price/1 THB	
13mm	120	-9040K	162.00	
16mm	120	-9050K	167.00	
19mm	120	-9060K	176.00	and the second sec
22mm	120	-9070K	176.00	and the state

335