SENATOR QUALITY TOOLING Soldering Irons

Supplied with a double flat nickel plated tip, 1.2m power lead and 3 amp three pin plug. Manufactured to **BS EN 60335-2-45**.



Wattage	Tip Style	Voltage	Order Code SEN-516	Price/1 THB
25W	Fine Point	230V	-2210K	644.00
40W	6mm Offset	230V	-2240K	806.00

KENNEDY QUALITY INDUSTRIAL TOOLING Multi Angle Vice

Aluminium vice with a two position lockable ball joint, cast steel clamp and swivel mechanism. Horizontal/vertical grooved jaw is designed to hold irregular shaped objects. Removable jaw rubber covers for protecting delicate components. Will clamp to surfaces of 5 to 50mm thickness.

Jaw width: 74mm.
Upright: rotates through 360° and the vice can swivel between 45° and 135°.
Right angles: vice can be rotated through 360°.



Jaw Capacity	Weight each	Order Code KEN-516	Price/1 THB
60mm	930g	-2000K	1796.00

Helping Hands

Ideal for precision soldering, wiring and model making applications. With 10 movable joints for universal adjustment. 50mm diameter x 2.5 magnification. Two spring loaded crocodile clips for holding objects up to 8mm thick. Solid cast iron base for stability.
All other metal parts are chrome plated and corrosion-resistant.



Mag.	Mirror Size	Order Code KEN-516	Price/1 THB
2.5x	50mm Dia.	-1800K	599.00

KENNEDY QUALITY INDUSTRIAL TOOLING Desoldering Tool

Anti-Static Val-U-Vac
With carbon impregnated tip and body to prevent solder adhesion and dispel static. Conforms with **CECC 15**. Removal of molten solder is achieved by the spring loaded piston creating a vacuum in the barriel of the tool. With safety shield and extraction springs located outside of the vacuum chamber and PTFE nozzle to prevent solder sticking.
Nozzle size: 3mm OD x 1.5mm, ID x 20mm.



Overall Size	Weight each	Order Code KEN-516	Price/1 THB
190 x 20mm	40g	-8480K	930.00

Professional Desoldering Tool

DSGPRM
Anodised aluminium body and steel plunger for professional use. With extraction spring located outside of the vacuum chamber and PTFE nozzle to prevent solder sticking. With safety shield.
Nozzle size: 3mm OD x 1.5mm, ID x 20mm long.



Size (mm)	Weight each	Order Code KEN-516	Price/1 THB
190 x 20	60g	-8500K	1764.00
Spare Nozzles (Pk 5)		-8505K	1481.00

SENATOR QUALITY TOOLING Desoldering Pump

Single handed use. Quickly removes molten solder from joints. Smooth action sprung loaded piston. Nozzle easily removed for cleaning. Temperature resistant, can be placed directly onto solder. Anti-static body ensures excellent component protection.



Size (W x H x D) mm	Weight each	Order Code SEN-516	Price/1 THB
60 x 240 x 25	50g	-2160K	NA

© 2022

OS21_APAC_TH_0352.indd 1 07/12/2021 13:10