Tape Measures

Steel Tape Measures

Non-reflective steel tape with nylon coated blade for maximum durability. The tape is housed in a high impact ABS plastic case with flush winding handle and belt clip. For ease of use, the tape is finished off with a handy plastic loop and metal end hook.



| Blade | Order Code | Price/1 |
|----------|----------------|---------|
| Length | KEN-536 | THB |
| 20m/66' | -3720K | NA |
| 30m/100' | -3740K | NA |

ENATOR Fibreglass Tape Measures

A high tensile strength fibreglass blade that is both water- and corrosion-proof. It has an easy to read dual scale (metric and imperial), reinforced blade tip and metal end claw. The tape is presented in an impact resistant ABS plastic case with flush fitting winding handle and convenient



| Blade Length | Blade Width | Order Code SEN-536 | Price/1 THB |
|-----------------|----------------|------------------------------|----------------|
| 10m/33' | 9.5mm | -2420K | NA |
| 20m/66' | 9.5mm | -2440K | NA |
| 30m/100' | 9.5mm | -2460K | NA |

Surveyor's Fibreglass Tape Measures

A high tensile strength fibreglass tape that will never kink or rust. It is white on one side and yellow on the other to help prevent twisting and the blade is double-coated to protect the markings which feature both metric and imperial measurements. Housed in a robust ABS open frame with folding end claw and large D type handle with rubber insert for a comfort grip. It also has a quick, 2x fast retraction function and marking spike.



Metric Measuring Wheel

Diameter

(Extended/Folded)

995/505mm

Robust, lightweight design with impact-resistant wheel and patented gear transmission structure with weather-resistant housing. Folding aluminium handle automatically 'clicks' into extended position. Five digit counter. 2 reset buttons. Spring loaded kickstand. 'Exact Point' indicator. Trigger operated brake. Supplied with carry case.



50 Years of Keeping Industry Working

417

THB

NA

-9010K

1.96kg