\$572

Screwdrivers

KENNEDY. PROFESSIONAL

Pro-Torq Screwdrivers

Chrome vanadium steel blades with magnetic tips. Fitted with aunique dual grip triangular handle which has been designed for improved user comfort, allowing more torque to be applied.



With convenient hanging hole in the handle for storage.

Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 screwdriver would be suitable for most applications. **DIN ISO**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
No.0	75mm	25q	-5110K	225.00
No.1	75mm	55g	-5120K	226.00
No.1	250mm	80g	-4490K	295.00
No.2	Stubby	40g	-5180K	212.00
No.2	100mm	85g	-5140K	235.00
No.2	250mm	120g	-4500K	295.00
No.3	150mm	145g	-5150K	376.00
No.4	200mm	210a	-5160K	433.00

Flared Tip, Round Blade

To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. **DIN ISO 2380.**



	-			
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
3.2mm	75mm	25g	-5425K	163.00
6.5mm	Stubby	40g	-5420K	212.00
6.5mm	100mm	85g	-5430K	281.00
6.5mm	150mm	100g	-5440K	297.00
8.0mm	200mm	170g	-5450K	412.00
10.0mm	250mm	240g	-5460K	536.00

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. **DIN ISO** 8764



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
No.2	Stubby	45g	-5280K	192.00
No.0	75mm	25g	-5290K	163.00
No.1	75mm	55g	-5300K	230.00
No.1	250mm	80g	-5360K	318.00
No.2	100mm	85g	-5310K	281.00
No.2	250mm	120g	-5370K	331.00
No.3	150mm	145g	-5320K	382.00
No.4	200mm	210g	-5340K	494.00

Flared Tip, Square Blade

Square bladed screwdrivers can be gripped in a spanner or locking wrench to allow greater torque to be applied from the side rather than from directly above the screwdriver.

DIN ISO 2380.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
6.5mm	100mm	90g	-5500K	228.00
6.5mm	150mm	105g	-5510K	239.00
8.0mm	200mm	185g	-5520K	315.00
10.0mm	250mm	275g	-5530K	433.00
10.0mm	300mm	305g	-5550K	474.00

For Pro-Torq Screwdriver Sets, See Next Page . . .

KENNEDY QUALITY INDUSTRIAL TOOLING

'Hi-Grip' Pound Thru' Screwdrivers

Through blade screwdriver with chrome vanadium steel blades and striking heads, suitable for striking with a hammer to free up seized screws. Fully hardened magnetic tips. Comfortable moulded grip. Hexagon blades. **DIN ISO 2380/8764.**



Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 screwdriver would be suitable for most applications. **DIN ISO 8764.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
No.1	75mm	100g	-3610K	186.00
No.2	100mm	150g	-3620K	251.00
No.3	150mm	220g	-3630K	306.00

Flared Tip

Slotted head screws are the most commonly used screw. To safely drive these screws,

the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. Hexagon blades. **DIN ISO 2380.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
6mm	100mm	150g	-3510K	260.00
6mm	150mm	160g	-3520K	278.00
8mm	200mm	240g	-3540K	345.00
9.5mm	250mm	315g	-3560K	460.00

Parallel Tip

To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. **DIN ISO 2380.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
3.2mm	100mm	25g	-5650K	145.00
3.2mm	150mm	30g	-5660K	216.00
4.0mm	300mm	50g	-5400K	186.00
5.5mm	75mm	55g	-5710K	230.00
5.5mm	100mm	60g	-5720K	237.00
5.5mm	150mm	65g	-5730K	248.00
5.5mm	200mm	75g	-5740K	290.00
5.5mm	250mm	80g	-5750K	338.00
5.5mm	260mm	81g	-5404K	380.00

ΤX

TX head screws are used predominantly for engineering and automotive applications.

The design of the screw allows high torque levels to be applied without the driver slipping potentially damaging the components.

Tip Size T6

<u> </u>				
Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
T6	75mm	30g	-5260K	157.00
T7	75mm	30g	-5262K	157.00
T8	75mm	30g	-5264K	157.00
T9	75mm	30g	-5266K	157.00
T10	100mm	60g	-5268K	196.00
T15	100mm	60g	-5270K	196.00
T20	100mm	25g	-5272K	196.00
T25	100mm	85g	-5274K	235.00
T30	100mm	85g	-5276K	235.00

Pound Thru' Set

Supplied in display box.





PIECES



Weight	Order Code KEN-572	Price/1 THB
1.54kg	-3700K	2320.00

50 Years of Keeping Industry Working

472