KENNEDY QUALITY INDUSTRIAL TOOLING Engineer's & Electrician's Screwdrivers

With a traditional 'fluted' design handle. High quality steel blades with satin finish. Magnetic tips, hardened and ground to prolong tool life. This range offers the widest choice of blade selection and blade length. The high impact plastic handles are acid and oil resistant. A comprehensive selection to meet the demands of modern industry.
DIN ISO 2380/8764.



Crosspoint

Crosspoint screws virtually eliminate the screwdriver slippage if the correct size is used. The No.2 driver is suitable for most applications. **DIN ISO 8764.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
No.0	75	25g	**-1000K**	**79.00**
No.1	75	55g	**-1010K**	**104.00**
No.2	100	80g	**-1020K**	**123.00**
No.3	150	135g	**-1030K**	**179.00**
No.4	200	225g	**-1040K**	**273.00**
No.1	Stubby	60g	**-1210K**	**104.00**
No.2	Stubby	60g	**-1220K**	**104.00**

PZ/Supadriv

PZ/Supadriv has extra 'cutaways' to help drive the screw. Favoured by the construction and joinery trade. **DIN ISO 8764.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
No.0	75	25g	**-2000K**	**79.00**
No.1	75	55g	**-2010K**	**104.00**
No.1	250	80g	**-2510K**	**123.00**
No.2	100	80g	**-2020K**	**123.00**
No.2	250	110g	**-2520K**	**160.00**
No.3	150	135g	**-2030K**	**179.00**
No.3	250	175g	**-2530K**	**224.00**
No.4	200	225g	**-2040K**	**273.00**
No.1	Stubby	60g	**-2210K**	**104.00**
No.2	Stubby	55g	**-2220K**	**104.00**

Flared Tip, Round Blade

Same as the parallel tip.
DIN ISO 2380.



Tip Size (mm)	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
6.5mm	Stubby	60g	**-3020K**	**105.00**
6.5mm	100	80g	**-3040K**	**125.00**
6.5mm	150	90g	**-3060K**	**134.00**
8.0mm	200	155g	**-3080K**	**204.00**
10.0mm	250	250g	**-3100K**	**301.00**
10.0mm	300	280g	**-3120K**	**322.00**

Parallel Tip

Slotted head screws are the most commonly used screw. To safely drive these screws, the tip of the screwdriver should be of the same width as the slot in the screw head and fill it as well, to minimise slipping and deforming the screw head. **DIN ISO 2380.**



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
3.2mm	50	25g	**-4520K**	**92.00**
3.2mm	75	25g	**-4530K**	**78.00**
3.2mm	100	25g	**-4540K**	**81.00**
3.2mm	150	30g	**-4560K**	**92.00**
5.5mm	75	55g	**-5030K**	**118.00**
5.5mm	100	55g	**-5040K**	**120.00**
5.5mm	150	65g	**-5060K**	**122.00**
5.5mm	200	70g	**-5080K**	**133.00**
5.5mm	250	80g	**-5100K**	**147.00**

Flared Tip, Square Blade

Square bladed screwdrivers can be gripped in a spanner or locking wrench to allow greater torque to be applied from the side rather than from directly above the screwdriver.
DIN ISO 2380.



Tip Size	Blade Length	Weight each	Order Code KEN-572	Price/1 THB
6.5mm	100	85g	**-4040K**	**162.00**
6.5mm	150	95g	**-4060K**	**113.00**
8.0mm	200	175g	**-4080K**	**182.00**
10.0mm	250	285g	**-4100K**	**214.00**

Set Contents (mm):

FLARED: 6.5 stubby, 6.5 x 100, 6.5 x 150, 10.0 x 250.
PARALLEL: 3.2 x 100, 5.5 x 150.
PZ: No.1 stubby, No.1 x 75, No.2 stubby, No.2 x 100, No.3 x 150.



11 PIECES

Weight each	Order Code KEN-572	Price/1 THB
1.0kg	**-9900K**	**2016.00**

Set Contents (mm):

FLARED: 6.5 stubby, 6.5 x 100, 8.0 x 200, 10.0 x 250.
PARALLEL: 3.2 x 75, 3.2 x 150, 5.5 x 75, 5.5 x 150.
CROSS POINT: No.0 x 75, No.1 stubby, No.1 x 75, No.2 stubby, No.2 x 100, No.3 x 150, No.4 x 200.

15 PIECES



Weight each	Order Code KEN-572	Price/1 THB
1.39kg	**-9920K**	**3066.00**

Set Contents (mm):

FLARED: 6.5 stubby, 6.5 x 100, 8.0 x 200.
PARALLEL: 3.2 x 75, 3.2 x 150.
CROSS POINT: No.0 x 75, No.1 stubby, No.1 x 75, No.2 stubby, No.2 x 100, No.3 x 150, No.4 x 200.



12 PIECES

Weight each	Order Code KEN-572	Price/1 THB
1.05kg	**-5940K**	**2091.00**

© 2022

OS21_APAC_TH_0474.indd 1 07/12/2021 10:14