


Impact Sockets - 3/4" Square Drive

583 Group

KENNEDY Chrome Molybdenum Impact Sockets

Manufactured from high quality chrome molybdenum steel. Black oxidised finish with permanent laser etched markings.

3/4" Drive Metric, Standard Length, 6-Point
Conform to: DIN 3129.



Socket (mm)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
16	A	44.0	27.0	11.0	50.0	367g	-3090K	756.00
17	AA	38.0	30.0	17.0	51.0	248g	-8560K	756.00
18	A	44.0	32.0	13.0	50.0	433g	-8561K	756.00
19	AA	38.0	32.0	17.0	51.0	255g	-8562K	756.00
20	A	44.0	34.0	14.0	50.0	433g	-8563K	767.00
21	A	44.0	35.0	15.0	50.0	400g	-8564K	777.00
22	A	44.0	37.0	15.0	50.0	400g	-8565K	777.00
23	B	40.0	40.0	18.0	51.0	321g	-8566K	777.00
24	B	40.0	40.0	18.0	51.0	313g	-8567K	777.00
25	A	44.0	40.0	16.0	50.0	433g	-3180K	777.00
26	A	44.0	41.0	16.0	50.0	433g	-8569K	777.00
27	A	44.0	43.0	19.0	54.0	433g	-8570K	777.00
28	B	44.0	44.0	19.0	54.0	433g	-8571K	777.00
29	C	44.0	45.0	21.0	54.0	450g	-8572K	819.00
30	C	44.0	46.0	17.0	54.0	402g	-8573K	819.00
32	C	44.0	49.0	22.0	56.0	500g	-8574K	819.00
33	C	44.0	50.0	20.0	57.0	482g	-8575K	819.00
34	C	44.0	52.0	22.0	56.0	550g	-3260K	903.00
35	C	44.0	53.0	22.0	56.0	550g	-8577K	903.00
36	C	44.0	54.0	20.0	57.0	529g	-8578K	903.00
38	C	44.0	56.0	19.0	57.0	542g	-8579K	903.00
41	C	44.0	60.0	24.0	58.0	598g	-8580K	903.00
42	C	44.0	62.0	27.0	58.0	700g	-8581K	903.00
46	C	44.0	66.0	26.0	63.0	724g	-8582K	929.00
47	C	44.0	68.0	30.0	68.0	900g	-8583K	1365.00
50	C	54.0	71.0	27.0	68.0	1051g	-8584K	1323.00

3/4" Drive Metric, Deep Length, 6-Point
Conform to: DIN 3129.



Socket (mm)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
17	AA	38.0	30.0	37.0	90.0	411g	-8813K	751.00
18	A	44.0	32.0	18.0	95.0	600g	-8814K	751.00
19	AA	38.0	32.0	37.0	90.0	407g	-8815K	751.00
21	A	44.0	35.0	21.0	95.0	650g	-8816K	751.00
22	A	44.0	37.0	22.0	95.0	700g	-8817K	751.00
24	A	40.0	40.0	37.0	90.0	558g	-8818K	751.00
25	A	44.0	40.0	25.0	95.0	700g	-8819K	751.00
26	A	44.0	41.0	26.0	95.0	700g	-8820K	751.00
27	A	40.0	40.0	36.0	90.0	503g	-8821K	751.00
28	B	44.0	44.0	28.0	95.0	750g	-8822K	751.00
30	C	44.0	46.0	37.0	90.0	629g	-8823K	887.00
32	C	44.0	48.0	37.0	90.0	705g	-8824K	887.00
33	C	44.0	50.0	37.0	90.0	766g	-8825K	971.00
34	C	44.0	52.0	38.0	90.0	810g	-8826K	1019.00
36	C	44.0	54.0	50.0	90.0	804g	-8827K	1019.00
38	C	44.0	56.0	50.0	90.0	845g	-8828K	1040.00
41	C	44.0	60.0	50.0	90.0	931g	-8829K	1244.00
42	C	44.0	62.0	48.0	90.0	994g	-8830K	1281.00
46	C	44.0	66.0	50.0	90.0	1076g	-8831K	1397.00
47	C	44.0	68.0	38.0	95.0	1300g	-8832K	1397.00

3/4" Drive Inch Size, Standard Length, 6-Point
Conform to: SAE, USA Federal Standard GGG-W-660A.



Socket (inch)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
5/8"	A	38.0	27.5	11.0	50	267g	-3360K	536.00
1 1/16"	A	38.0	29.0	12.0	50	267g	-3370K	536.00
3/4"	AA	38.0	30.0	18.0	51	240g	-8699K	462.00
13/16"	A	38.0	32.0	15.0	52	300g	-8700K	536.00
7/8"	A	38.0	34.0	15.0	52	300g	-8710K	578.00
15/16"	A	38.0	36.0	16.0	52	300g	-3410K	536.00
1"	C	38.0	40.0	16.0	52	333g	-8703K	536.00
1 1/16"	C	38.0	40.0	19.0	52	333g	-3430K	578.00
1 1/8"	B	42.0	42.0	21.0	52	333g	-8705K	578.00
1 3/16"	B	44.0	44.0	21.0	52	367g	-3450K	578.00
1 1/4"	B	44.0	46.0	18.0	54	398g	-8707K	496.00
1 5/16"	C	44.0	50.0	20.0	57	467g	-8708K	546.00
1 3/8"	C	44.0	50.0	22.0	56	450g	-8709K	578.00
1 7/16"	C	44.0	51.0	25.0	56	500g	-8710K	578.00
1 1/2"	C	44.0	56.0	20.0	57	542g	-8711K	614.00
1 5/8"	C	44.0	60.0	23.0	58	607g	-8712K	803.00
1 11/16"	C	44.0	63.0	25.0	63	688g	-8713K	908.00
1 3/4"	C	44.0	65.0	27.0	62	800g	-3540K	1019.00
1 13/16"	C	44.0	67.0	30.0	68	900g	-3550K	1019.00
1 7/8"	C	44.0	68.0	26.0	68	834g	-8716K	1097.00

3/4" Drive BSW Size, Standard Length, 6-Point
Conform to: SAE, USA Federal Standard GGG-W-660A.



Socket (BSW)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
9/16"	A	44.0	41.0	16.0	50	433g	-3620K	1523.00
1 1/16"	C	44.0	48.0	21.0	56	450g	-3640K	1523.00
3/4"	C	44.0	51.0	22.0	56	500g	-3650K	1523.00
7/8"	C	44.0	57.0	25.0	58	600g	-3670K	2972.00
1"	C	44.0	63.0	27.0	63	800g	-3690K	2972.00
1 1/8"	C	44.0	68.0	30.0	68	900g	-3710K	2972.00
1 1/4"	C	44.0	74.0	32.0	72	1100g	-3720K	2972.00

3/4" Drive Inch Size, Deep Length, 6-Point

Conform to: SAE, USA Federal Standard GGG-W-660A.



Socket (inch)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
3/4"	A	38.0	30.0	19.0	85.0	433g	-4160K	2615.00
7/8"	A	38.0	34.0	22.0	85.0	467g	-4180K	2615.00
15/16"	A	38.0	36.0	24.0	85.0	467g	-4190K	2615.00
1"	C	38.0	40.0	25.0	85.0	550g	-4200K	2615.00
1 1/16"	C	38.0	40.0	27.0	85.0	550g	-4210K	2615.00
1 1/8"	B	42.0	42.0	29.0	85.0	550g	-8922K	2877.00
1 3/16"	B	44.0	44.0	30.0	85.0	600g	-8923K	2615.00
1 1/4"	C	44.0	49.0	32.0	85.0	800g	-8924K	2615.00
1 5/16"	C	44.0	50.0	38.0	90.0	755g	-8925K	772.00
1 7/16"	C	44.0	51.0	37.0	85.0	800g	-4270K	2615.00
1 1/2"	C	44.0	57.0	38.0	95.0	1100g	-8927K	2615.00
1 5/8"	C	44.0	68.0	38.0	95.0	1100g	-8928K	1336.00

3/4" Drive BSW Size, Deep Length, 6-Point
Conform to: SAE, USA Federal Standard GGG-W-660A.

Socket (BSW)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
3/4"	C	44.0	51.0	33.0	95	1000g	-4450K	2646.00
13/16"	C	44.0	53.0	35.0	95	1000g	-4460K	2888.00
7/8"	C	44.0	57.0	38.0	95	1100g	-4470K	3024.00

Hand Tools