

Impact Sockets - 3/4" & 1" Square Drive

Hand Tools



Chrome Molybdenum Impact Sockets

Manufactured from high quality chrome molybdenum steel. Black oxidised finish with permanent laser etched markings.

3/4" Drive Reducers & Adaptors

Male Drive x Female Drive	Weight each	Order Code KEN-583	Price/1 THB
3/4" x 1/2"	156g	-9079K	350.00
1/2" x 3/4"	338g	-9080K	366.00
1" x 3/4"	437g	-9081K	719.00



Universal Ball Joint

Male Drive x Female Drive	Weight each	Order Code KEN-583	Price/1 THB
3/4" x 3/4"	600g	-9159K	1649.00



Retaining Rings


Supplied with pins



To Suit Outside Dia.	Square Drive	Weight each	Order Code KEN-583	Price/1 THB
38 - 44mm	3/4"	8g	-8200K	97.00
48 - 54mm	3/4"	16g	-8210K	129.00
46 - 58mm	1"	16g	-8300K	141.00
62mm	1"	18g	-8310K	193.00
78 - 86mm	1"	31g	-8320K	239.00

1" Drive Metric, Standard Length, 6-Point

Conform to: DIN 3129.



Socket (mm)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
21	A	54.0	38.0	15.0	60.0	700g	-5050K	1155.00
22	A	54.0	40.0	15.0	60.0	700g	-8590K	1155.00
24	A	54.0	42.0	18.0	60.0	800g	-8591K	1155.00
25	A	54.0	43.0	18.0	60.0	800g	-5090K	1155.00
26	A	54.0	44.5	18.0	60.0	800g	-5100K	1155.00
27	AA	50.0	46.0	17.0	58.0	525g	-8594K	767.00
28	A	54.0	47.0	19.0	62.0	800g	-5120K	1155.00
29	A	54.0	48.0	19.0	62.0	800g	-5130K	1155.00
30	B	52.0	52.0	18.0	62.0	653g	-8597K	840.00
32	B	52.0	52.0	19.0	62.0	622g	-8598K	840.00
33	A	54.0	53.0	22.0	62.0	800g	-8599K	1155.00
34	B	54.0	55.0	22.0	62.0	800g	-8600K	1155.00
35	B	54.0	55.0	22.0	62.0	800g	-5190K	1155.00
36	B	54.0	57.0	25.0	67.0	900g	-8602K	1155.00
37	B	54.0	59.0	25.0	67.0	900g	-5210K	1617.00
38	B	54.0	58.0	31.0	65.0	738g	-8604K	1155.00
41	B	54.0	63.0	27.0	70.0	1000g	-8605K	1260.00
42	B	54.0	65.0	27.0	74.0	1200g	-8606K	1617.00
46	B	54.0	70.0	30.0	76.0	1200g	-8607K	1617.00
47	B	54.0	71.5	32.0	76.0	1200g	-5300K	1617.00
48	B	54.0	72.5	32.0	76.0	1200g	-8609K	1617.00
50	B	54.0	75.0	35.0	80.0	1500g	-8610K	1617.00
52	B	54.0	77.0	35.0	84.0	1500g	-8611K	1617.00
55	B	54.0	80.0	43.0	83.0	1412g	-8612K	1701.00
56	B	54.0	82.0	40.0	84.0	1750g	-8613K	1775.00
60	B	54.0	86.0	45.0	87.0	1688g	-8614K	2111.00
65	B	54.0	92.0	49.0	90.0	1933g	-8615K	2751.00
70	B	54.0	100.0	42.0	96.0	3000g	-8616K	3644.00
75	B	86.0	106.0	45.0	98.0	4000g	-8617K	4914.00
80	B	86.0	112.0	48.0	100.0	4000g	-8618K	5198.00
85	B	86.0	115.0	60.0	100.0	3810g	-8619K	5198.00
90	B	86.0	124.0	65.0	105.0	4296g	-8620K	5418.00
95	B	86.0	131.0	52.0	115.0	6000g	-8621K	5649.00
100	B	95.0	137.0	58.0	115.0	7000g	-8622K	12747.00

7 Piece Set - Metric

Standard length: 19, 24, 27, 30, 32, 36 and 46mm.



7 PIECES

Weight each	Order Code KEN-583	Price/1 THB
4.20kg	-9204K	6195.00

3/4" Drive Extension Bars



Length (mm)	Weight each	Order Code KEN-583	Price/1 THB
100 (4")	470g	-9124K	1166.00
150 (6")	773g	-9125K	1166.00
230 (9")	900g	-7600K	1565.00
250 (10")	1350g	-9126K	1785.00
300 (12")	1336g	-9127K	1785.00
400 (15 3/4")	1701g	-9128K	2163.00

1" Drive Inch Size, Standard Length, 6-Point

Conform to: SAE, USA Federal Standard GGG-W-660A.

Socket (inch)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
7/8"	A	51.0	39.0	15.0	58.0	550g	-5610K	1407.00
15/16"	A	51.0	40.0	18.0	58.0	550g	-5620K	1407.00
1"	A	51.0	42.0	18.0	58.0	550g	-5630K	1407.00
1 1/16"	A	51.0	44.0	19.0	58.0	600g	-8724K	1407.00
1 1/8"	A	51.0	46.0	19.0	58.0	600g	-8725K	1407.00
1 3/16"	A	51.0	48.0	21.0	60.0	650g	-5660K	1407.00
1 1/4"	B	51.0	51.0	22.0	60.0	650g	-8727K	1407.00
1 5/16"	C	52.0	53.0	22.0	62.0	733g	-8728K	1407.00
1 7/16"	C	52.0	56.0	25.0	62.0	700g	-8729K	1407.00
1 1/2"	C	52.0	58.0	25.0	62.0	800g	-8730K	1407.00
1 9/16"	C	52.0	60.0	25.0	62.0	800g	-5720K	1869.00
1 5/8"	C	52.0	61.5	27.0	62.0	800g	-5730K	1880.00
1 11/16"	C	52.0	65.0	27.0	64.0	900g	-5740K	1880.00
1 3/4"	C	58.0	66.0	27.0	64.0	1000g	-5750K	1880.00
1 13/16"	C	58.0	68.0	30.0	64.0	1100g	-5760K	1880.00
1 7/8"	C	58.0	70.0	32.0	66.0	1100g	-8736K	1880.00
2"	C	58.0	74.0	35.0	70.0	1250g	-5790K	1880.00
2 1/16"	C	58.0	75.0	35.0	70.0	1250g	-8738K	2058.00
2 1/8"	C	58.0	78.0	35.0	70.0	1250g	-5810K	2058.00
2 3/16"	C	62.0	80.0	35.0	72.0	1500g	-5820K	1880.00
2 1/4"	C	54.0	82.0	44.0	83.0	1484g	-8741K	2058.00
2 3/8"	C	62.0	87.0	42.0	78.0	1500g	-5850K	2058.00
2 1/2"	C	62.0	91.0	42.0	80.0	2500g	-5870K	2268.00
2 9/16"	C	62.0	93.0	42.0	80.0	2500g	-8744K	2268.00
2 5/8"	C	62.0	95.0	42.0	82.0	2500g	-5890K	2268.00
2 3/4"	C	62.0	100.0	42.0	96.0	3000g	-5910K	2268.00
2 13/16"	C	62.0	102.0	45.0	96.0	4000g	-5920K	2268.00
3"	C	86.0	107.0	48.0	100.0	4000g	-8748K	9702.00
3 1/8"	C	86.0	111.0	48.0	100.0	5000g	-8749K	9702.00
3 1/2"	C	86.0	124.0	52.0	105.0	5000g	-6000K	9702.00

1" Drive BSW Size, Standard Length, 6-Point

Conform to: SAE, USA Federal Standard GGG-W-660A.



Socket (BSW)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
1 1/16"	A	54.0	51.0	21.0	62	800g	-6080K	9702.00
3/4"	B	54.0	53.0	22.0	62	800g	-6090K	1344.00
13/16"	B	54.0	56.0	22.0	65	800g	-6100K	1481.00
1"	B	54.0	66.0	27.0	74	1200g	-6130K	1712.00
1 1/8"	B	56.0	70.0	32.0	66	1100g	-6140K	1869.00
1 1/4"	B	54.0	77.0	36.0	84	1500g	-6150K	2352.00
1 1/2"	B	62.0	89.0	42.0	78	1500g	-6170K	2856.00