

Impact Sockets - 1" & 1½" Square Drive

583 Group




Chrome Molybdenum Impact Sockets & Accessories

Manufactured from high quality chrome molybdenum steel. Black oxidised finish with permanent laser etched markings.

1" Drive Metric, Deep Length, 6-Point

Conform to: **DIN 3129.**



Style A



Style AA



Style B

Socket (mm)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
23	A	54.0	41.0	23.0	100.0	1200g	-6250K	1628.00
24	A	54.0	42.0	24.0	100.0	1200g	-8838K	1628.00
27	A	54.0	46.0	27.0	100.0	1200g	-8839K	1628.00
28	A	54.0	47.0	28.0	100.0	1200g	-8840K	1628.00
30	AA	52.0	52.0	37.0	90.0	956g	-8841K	1097.00
32	AA	52.0	52.0	37.0	90.0	901g	-8842K	1097.00
33	AA	52.0	52.0	37.0	90.0	886g	-8843K	1097.00
34	B	54.0	55.0	34.0	100.0	1400g	-6360K	1638.00
36	B	54.0	56.0	35.0	90.0	999g	-8845K	1208.00
37	B	54.0	59.0	37.0	100.0	1400g	-6390K	1806.00
38	B	54.0	60.0	38.0	100.0	1400g	-8847K	1806.00
41	B	54.0	61.0	58.0	95.0	1116g	-8848K	1523.00
42	B	54.0	65.0	38.0	100.0	1400g	-6440K	1806.00
46	B	54.0	68.0	58.0	95.0	1311g	-8850K	1827.00
50	B	54.0	74.0	62.0	100.0	1569g	-8851K	1974.00
52	B	54.0	77.0	40.0	100.0	1750g	-6540K	4043.00
55	B	54.0	81.0	40.0	100.0	2000g	-8853K	7193.00
56	B	54.0	82.0	40.0	105.0	2000g	-8854K	7193.00
60	B	54.0	87.0	42.0	120.0	2500g	-8855K	7193.00
65	B	54.0	93.0	42.0	125.0	3500g	-8856K	7193.00
70	B	54.0	100.0	42.0	125.0	5000g	-8857K	7193.00
75	B	86.0	106.0	45.0	135.0	6000g	-8858K	8663.00
80	B	86.0	112.0	48.0	135.0	6000g	-8859K	9440.00

1" Universal Ball Joint



Male Drive x Female Drive	Weight each	Order Code KEN-583	Price/1 THB
1" x 1"	640g	-9164K	3234.00

1" Drive Reducers & Adaptors



Male Drive x Female Drive	Weight each	Order Code KEN-583	Price/1 THB
¾" x 1"	335g	-9082K	735.00
1½" x 1"	670g	-9083K	1974.00

1" Drive Extension Bars



Length (mm)	Weight each	Order Code KEN-583	Price/1 THB
100 (4")	933g	-9133K	1376.00
150 (6")	1347g	-9134K	1523.00
200 (8")	1687g	-9135K	2604.00
250 (10")	2100g	-9136K	2531.00
300 (12")	2500g	-9137K	2604.00
380 (15")	2600g	-7720K	2720.00

1" Drive Inch Size, Deep Length, 6-Point

Conform to: **SAE, USA Federal Standard GGG-W-660A.**



Style A

Socket (inch)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
1"	A	51.0	42.0	25.0	90.0	900g	-6760K	2016.00
1¼"	A	51.0	44.0	27.0	90.0	1000g	-6770K	2216.00
1½"	A	51.0	46.0	29.0	90.0	1000g	-6780K	2310.00
1¾"	A	51.0	48.0	30.0	90.0	1000g	-6790K	2310.00
1⅞"	B	51.0	51.0	32.0	90.0	1000g	-6800K	2310.00
2"	C	52.0	53.0	34.0	90.0	1200g	-6810K	2426.00
2¼"	C	52.0	54.0	35.0	90.0	1200g	-8939K	2426.00
2½"	C	52.0	58.0	38.0	92.0	1200g	-6840K	2426.00
2¾"	C	52.0	60.0	38.0	92.0	1200g	-6850K	2489.00
3"	C	52.0	61.5	38.0	92.0	1200g	-8942K	2510.00
3¼"	C	52.0	65.0	38.0	92.0	1200g	-6870K	2730.00
3½"	C	58.0	66.0	38.0	92.0	1400g	-8944K	2961.00
4"	C	58.0	68.0	38.0	92.0	1400g	-6890K	3875.00
4¼"	C	58.0	70.0	38.0	92.0	1600g	-6900K	3119.00
4½"	B	58.0	72.0	38.0	100.0	1500g	-6910K	3696.00
5"	C	58.0	74.0	40.0	95.0	1750g	-6920K	4368.00
5¼"	C	58.0	75.0	40.0	95.0	1750g	-6930K	4473.00
5½"	C	58.0	78.0	40.0	100.0	2000g	-6940K	4578.00
6"	C	62.0	80.0	40.0	100.0	2250g	-8951K	4704.00
6¼"	C	62.0	84.0	40.0	100.0	2500g	-6960K	4893.00
6½"	C	62.0	86.0	40.0	105.0	2500g	-6970K	5040.00
7"	C	62.0	87.0	42.0	105.0	3000g	-6980K	5586.00
7¼"	C	62.0	89.0	42.0	110.0	3000g	-6990K	5712.00
7½"	C	62.0	91.0	42.0	110.0	4000g	-7000K	6048.00
8"	C	62.0	95.0	42.0	125.0	4000g	-7020K	6248.00
8¼"	C	62.0	100.0	42.0	125.0	4000g	-7040K	6384.00
8½"	C	86.0	104.0	42.0	125.0	5000g	-8959K	6657.00
9"	C	86.0	105.0	45.0	135.0	6000g	-7070K	6720.00
9¼"	C	86.0	107.0	48.0	135.0	6000g	-8961K	7056.00
9½"	B	86.0	111.0	48.0	135.0	6000g	-7100K	7392.00

1" Drive BSW Size, Deep Length, 6-Point

Conform to: **SAE, USA Federal Standard GGG-W-660A.**

Socket (BSW)	Style	Dimensions (mm)				Weight each	Order Code KEN-583	Price/1 THB
		D2	D1	L2	L			
¾"	A	54.0	53.0	50.0	100	1500g	-7150K	7728.00
1¾"	B	54.0	81.0	65.0	105	1500g	-7220K	12107.00
1½"	B	54.0	86.0	77.0	120	2000g	-7230K	12432.00

7 Piece Impact Socket Set

Socket sizes: 27, 30, 32, 33, 36, 41 and 46mm.



7 PIECES

Weight each	Order Code KEN-583	Price/1 THB
5.95kg	-9193K	13503.00

1½" Drive Metric Size, Standard Length, 6-Point

Conform to: **SAE, USA Federal Standard GGG-W-660A.**

Socket (mm)	Style	Dimensions (mm)				Order Code KEN-583	Price/1 THB
		D2	D1	L2	L		
30		54.0	56.0	21.0	78.0	-8430K	5061.00
32		86.0	58.0	22.0	78.0	-8628K	5061.00
33		86.0	60.0	22.0	78.0	-8433K	5061.00
36		86.0	64.0	24.0	78.0	-8630K	5061.00
38		86.0	66.0	26.0	80.0	-8631K	5061.00
41		86.0	70.0	28.0	80.0	-8441K	5061.00
46		86.0	76.0	30.0	84.0	-8446K	5061.00
48		86.0	79.0	32.0	87.0	-8448K	5061.00
50		86.0	81.0	32.0	87.0	-8634K	5061.00
52		86.0	83.0	34.0	87.0	-8452K	5061.00
55		86.0	87.0	37.0	90.0	-8455K	5061.00
56		86.0	88.0	37.0	92.0	-8456K	5061.00
60		86.0	94.0	39.0	95.0	-8460K	6384.00
65		86.0	100.0	42.0	100.0	-8637K	7403.00
70		86.0	106.0	46.0	105.0	-8470K	8001.00
75		86.0	112.0	49.0	108.0	-8475K	10091.00
80		86.0	119.0	53.0	115.0	-8640K	12107.00
85		86.0	125.0	56.0	118.0	-8485K	13451.00
95		95.0	137.0	61.0	123.0	-8495K	16821.00