



**Flexon TUFF-GUARD**  
watering done right since 1956

### Cold Water Hoses

- Premium-Duty: 6 ply
- Heavy-Duty: 5 ply
- Standard-Duty: 4 ply
- Light-Duty: 2 and 3 ply
- Super Light-Duty: 1 ply

All have GHT connections. Hoses with aluminum couplings are certified for use in potable water applications. PVC Premium- and Heavy-Duty Hoses are kink-resistant and have crushproof

couplings. Standard-Duty polypropylene hoses feature a helix wrap, providing flexibility. They resist abrasion, crushing, and kinks. Polypropylene material is up to 35% lighter than standard hoses. Collapsible Hose 423J02 is a fabric hose. Super Light-Duty Soaker Hose 423H99 can be used above ground or buried for direct underground soaking.

| Operating Temp.                      | Number of Ply | Hose Inside Dia. | Hose L | Hose Color | Coupling Material | Max. Pressure | Brand      | Item No. |
|--------------------------------------|---------------|------------------|--------|------------|-------------------|---------------|------------|----------|
| <b>Premium-Duty Hoses</b>            |               |                  |        |            |                   |               |            |          |
| <b>PVC</b>                           |               |                  |        |            |                   |               |            |          |
| 130°F Max. Temp.                     | 6             | ¾ in             | 50 ft  | Black      | Aluminum          | 500 psi       | Tough Guy  | 423H80   |
|                                      | 6             | ¾ in             | 100 ft | Black      | Aluminum          | 500 psi       | Tough Guy  | 423H81   |
| <b>Heavy-Duty Hoses</b>              |               |                  |        |            |                   |               |            |          |
| <b>PVC</b>                           |               |                  |        |            |                   |               |            |          |
|                                      | 5             | ¾ in             | 50 ft  | Black      | Aluminum          | 500 psi       | Tough Guy  | 423H86   |
|                                      | 5             | ¾ in             | 50 ft  | Green      | Aluminum          | 500 psi       | Tough Guy  | 423H87   |
|                                      | 5             | ¾ in             | 100 ft | Green      | Aluminum          | 500 psi       | Tough Guy  | 423H88   |
| 130°F Max. Temp.                     | 5             | ¾ in             | 50 ft  | Black      | Aluminum          | 500 psi       | Tough Guy  | 423H89   |
|                                      | 5             | ¾ in             | 50 ft  | Green      | Aluminum          | 500 psi       | Tough Guy  | 423H90   |
|                                      | 5             | ¾ in             | 75 ft  | Black      | Brass             | 500 psi       | Tough Guy  | 423H91   |
|                                      | 5             | ¾ in             | 75 ft  | Green      | Brass             | 500 psi       | Tough Guy  | 423H92   |
| <b>Standard-Duty Hoses</b>           |               |                  |        |            |                   |               |            |          |
| <b>PVC</b>                           |               |                  |        |            |                   |               |            |          |
|                                      | 4             | ¾ in             | 50 ft  | Green      | Brass             | 250 psi       | Tough Guy  | 423H93   |
|                                      | 4             | ¾ in             | 100 ft | Green      | Brass             | 250 psi       | Tough Guy  | 423H94   |
| 90°F Max. Temp.                      | 4             | ½ in             | 50 ft  | White      | Aluminum          | 100 psi       | Tough Guy  | 423H97   |
|                                      | 4             | ¾ in             | 50 ft  | White      | Aluminum          | 100 psi       | Tough Guy  | 423H98   |
|                                      | 4             | ½ in             | 25 ft  | White      | Aluminum          | 100 psi       | Tough Guy  | 423H96   |
|                                      | 4             | ¾ in             | 100 ft | Yellow     | Aluminum          | 250 psi       | Tough Guy  | 491G54   |
| 130°F Max. Temp.                     | 4             | ¾ in             | 100 ft | Green      | Aluminum          | 400 psi       | Flexon     | 423J02   |
| <b>Collapsible Nylon/PVC</b>         |               |                  |        |            |                   |               |            |          |
| 90°F Max. Temp.                      | 0             | ½ in             | 50 ft  | Green      | Aluminum          | 400 psi       | Flexon     | 423J02   |
| <b>Light-Duty Hoses</b>              |               |                  |        |            |                   |               |            |          |
| <b>PVC</b>                           |               |                  |        |            |                   |               |            |          |
| 90°F Max. Temp.                      | 3             | ¾ in             | 50 ft  | Green      | Plastic/Brass     | 175 psi       | Tough Guy  | 423H95   |
|                                      | 3             | ¾ in             | 15 ft  | Green      | Brass             | 175 psi       | —          | 423J01   |
| <b>Polypropylene</b>                 |               |                  |        |            |                   |               |            |          |
|                                      | 2             | ¾ in             | 25 ft  | Blue       | Brass             | 100 psi       | Tuff Guard | 29FX94   |
|                                      | 2             | ¾ in             | 50 ft  | Green      | Brass             | 100 psi       | Tuff Guard | 29FX92   |
|                                      | 2             | ¾ in             | 50 ft  | Red        | Brass             | 100 psi       | Tuff Guard | 29FX93   |
| 158°F Max. Temp.                     | 2             | ¾ in             | 50 ft  | Blue       | Brass             | 100 psi       | Tuff Guard | 12F252   |
|                                      | 2             | ¾ in             | 100 ft | Green      | Brass             | 100 psi       | Tuff Guard | 34FW19   |
|                                      | 2             | ¾ in             | 100 ft | Blue       | Brass             | 100 psi       | Tuff Guard | 12F253   |
| <b>Super Light-Duty Soaker Hoses</b> |               |                  |        |            |                   |               |            |          |
| <b>Rubber/PVC</b>                    |               |                  |        |            |                   |               |            |          |
| 90°F Max. Temp.                      | 1             | ½ in             | 50 ft  | Black      | Plastic           | 100 psi       | Tough Guy  | 423H99   |



423H80



423H87



423H94



423J02



423H95



12F252



423H99



442F17



423H82

### Heavy-Duty Hot/Cold Water Hoses

- GHT connections

Kink-resistant SEBS (Styrene Ethylene Butylene Styrene) hoses, 442F17 and 442F18 are certified for use in potable water applications and NSF 61 Listed. Rubber hoses have crushproof couplings and high-burst pressure.

| Operating Temp.                             | Number of Ply | Hose Inside Dia. | Hose Length | Hose Color | Coupling Material | Max. Pressure | Item No. |
|---|---------------|------------------|-------------|------------|-------------------|---------------|----------|
| <b>Kink-Resistant Rubber Compound Hoses</b> |               |                  |             |            |                   |               |          |
| -40° to 165°F Max. Temp.                    | 4             | ¾ in             | 50 ft       | Red        | Aluminum          | 400 psi       | 442F17   |
| -40° to 160°F Max. Temp.                    | 4             | ¾ in             | 50 ft       | Red        | Aluminum          | 400 psi       | 442F18   |
| <b>Rubber Hoses</b>                         |               |                  |             |            |                   |               |          |
|   | 3             | ¾ in             | 25 ft       | Red        | Aluminum          | 400 psi       | 423H82   |
|   | 3             | ¾ in             | 50 ft       | Red        | Aluminum          | 401 psi       | 423H83   |
| 180°F Max. Temp.                            | 3             | ¾ in             | 75 ft       | Red        | Aluminum          | 402 psi       | 423H84   |
|   | 3             | ¾ in             | 50 ft       | Red        | Aluminum          | 403 psi       | 423H85   |



55AW95

Continental  
ContiTech



55AX13

### EPDM Garden Hoses

- Temp. range: -40° to 190°F
- Safety factor: 4:1

EPDM (ethylene propylene diene monomer) garden hoses provide excellent resistance to UV rays and ozone and are used in landscaping and grounds-maintenance applications. Hoses with coupled assembly feature fittings on both ends for attaching to equipment. Bulk hoses do not come with fittings.

| Hose I.D.               | Max. Working Pressure @ 70°F | 25 ft Item No. | 50 ft Item No. | 75 ft Item No. | 100 ft Item No. |
|-------------------------|------------------------------|----------------|----------------|----------------|-----------------|
| <b>Bulk Hose</b>        |                              |                |                |                |                 |
| ½ in                    | 150 psi                      | 55AW94         | 55AW98         | 55AX03         | 55AX07          |
| ¾ in                    | 150 psi                      | 55AW95         | 55AW99         | 55AX04         | 55AX08          |
| ¾ in                    | 150 psi                      | 55AW96         | 55AX01         | 55AX05         | 55AX09          |
| 1 in                    | 150 psi                      | 55AW97         | 55AX02         | 55AX06         | 55AX10          |
| <b>Coupled Assembly</b> |                              |                |                |                |                 |
| ½ in                    | 150 psi                      | 55AX11         | 55AX15         | 55AX19         | 55AX23          |
| ¾ in                    | 130 psi                      | 55CN83         | 55CN84         | 55CN85         | 55CN86          |
| ¾ in                    | 150 psi                      | 55AX12         | 55AX16         | 55AX20         | 55AX24          |
| ¾ in                    | 150 psi                      | 55AX13         | 55AX17         | 55AX21         | 55AX25          |
| 1 in                    | 150 psi                      | 55AX14         | 55AX18         | 55AX22         | 55AX26          |