



4ZW25



Beam Clamps

- For commercial, construction, and industrial applications
- Adjustable to fit a wide range of beam sizes

Provide a temporary or permanent mount to tapered or flat I-beams. In addition, they position the load beneath the center of the I-beam. Designed to reduce I-beam stress by applying the load inside of the flange edge. Include suspension bar. Comply with ASME Standards.

Safe Working Load	Jaw Cap.	Brand	Item No.
2,000 lb	3 in to 7 1/2 in	Harrington	23XT08
	3 in to 9 in	Dayton	3KR11
4,000 lb	3 in to 9 in	Dayton	3KR12
	3 in to 7 1/2 in	Harrington	23XT09
6,000 lb	3 3/8 in to 12 1/2 in	Dayton	3KR13
	4 in to 12 in	Harrington	23XT10
10,000 lb	3 3/8 in to 12 1/2 in	Dayton	4ZW25
	4 in to 12 in	Harrington	23XT11
20,000 lb	6 in to 13 1/4 in	Harrington	6HJH8



23XR94



1/2- to 10-Ton Push Trolleys

- Load equalizing suspension
- Maintenance-free sealed ball bearings
- Fit both tapered and flat-flanged beams
- Meet ANSI/ASME B30.11 Standards

Feature specially designed contoured wheels that fit both tapered and flat flange beams. Load equalizing suspension distributes the load to all wheels. Sealed precision ball bearings are lubed for life and offer smooth movement, with low friction and long life.

Load Capacity	Fits Beam Flange W	Min. Radius Curve	Head Room To Bail	Item No.
1,000 lb	2 1/2 in to 4 in	13 1/2 in	3 1/4 in	23XR96
2,000 lb	2 1/2 in to 5 in	17 3/4 in	4 1/4 in	23XR97
4,000 lb	3 1/4 in to 6 1/4 in	21 3/4 in	5 1/4 in	23XR98
6,000 lb	3 1/4 in to 6 1/4 in	25 3/4 in	6 1/4 in	23XR99
10,000 lb	4 1/4 in to 8 1/2 in	28 1/2 in	7 1/4 in	23XT01
16,000 lb	5 1/2 in to 8 1/2 in	118 1/2 in	4 3/4 in	23XR94
20,000 lb	5 1/2 in to 8 1/2 in	118 1/2 in	4 3/4 in	23XR95



Adjustable with Hooks
5TDH2



Nonconductive
8N230

Lifting and Spreader Beams



Provide safer lifting and movement for long, heavy objects with hoist or lifting equipment and a single-hook, point-of-lifting contact. Beams comply with ASME Standards.

Working Load Limit	Max. Spread	Min. Spread	Headroom	Overall Length	Item No.
Adjustable Spreader Beams w/Hooks					
4,000 lb	72 in	48 in	48 to 57 in	72 in	5TDH2
	120 in	72 in	72 to 88 in	120 in	5TDH3
	240 in	144 in	132 to 166 in	240 in	5TDH5
10,000 lb	72 in	48 in	55 to 64 in	72 in	5TDH6
	120 in	72 in	79 to 95 in	120 in	5TDH7
	168 in	96 in	102 to 126 in	168 in	5TDH8
20,000 lb	240 in	144 in	138 to 172 in	240 in	5TDH9
	72 in	48 in	60 to 69 in	72 in	5TDJ0
	120 in	72 in	74 to 111 in	120 in	5TDJ1
30,000 lb	168 in	96 in	108 to 132 in	168 in	5TDJ2
	72 in	48 in	64 to 72 in	72 in	5TDJ4
	168 in	96 in	111 to 135 in	168 in	5TDJ6
Nonconductive Battery Spreader Beams					
4,800 lb	36 in	36 in	29 in	36 in	9G315
	42 in	30 in	39 in	36 in	8N230
	36 in	36 in	30 in	36 in	8RH01
7,000 lb	42 in	30 in	40 1/2 in	36 in	8AJD4
	45 in	24 in	18 1/4 in	50 in	5TDK2



39RK28



39RK08



Composite Lifting and Spreader Beams

Beams are designed with an innovative composite material that is bonded together to form lightweight lifting products. Nonconductive, noncorrosive, and less than half the weight of steel. Meet ASME Standards.

Working Load Limit	Max. Spread	Headroom	Usable Upper Bail Length	Usable Upper Bail Width	Overall Length	Item No.
Lifting Beams						
500 lb	24 in	13 1/2 in	2 in	1 1/2 in	24 in	39RK28
	36 in	13 1/2 in	2 in	1 1/2 in	36 in	39RK53
	48 in	13 1/2 in	2 in	1 1/2 in	48 in	39RK68
	72 in	16 1/2 in	2 in	1 1/2 in	72 in	39RK14
1,000 lb	96 in	16 1/2 in	2 in	1 1/2 in	96 in	39RK29
	24 in	13 1/2 in	1 1/2 in	1 1/2 in	24 in	39RJ95
	36 in	13 1/2 in	1 1/2 in	1 1/2 in	36 in	39RK72
	48 in	14 1/2 in	1 1/2 in	1 1/2 in	48 in	39RK40
	72 in	16 1/2 in	1 1/2 in	1 1/2 in	72 in	39RK62
	96 in	18 1/2 in	1 1/2 in	1 1/2 in	96 in	39RK61

Working Load Limit	Max. Spread	Headroom	Usable Upper Bail Length	Usable Upper Bail Width	Overall Length	Item No.
2,000 lb	24 in	19 1/2 in	4 1/2 in	2 1/2 in	24 in	39RK23
	36 in	19 1/2 in	4 1/2 in	2 1/2 in	36 in	39RJ94
	48 in	21 1/2 in	4 1/2 in	2 1/2 in	48 in	39RK43
	72 in	23 1/2 in	4 1/2 in	2 1/2 in	72 in	39RK75
4,000 lb	24 in	21 1/2 in	4 1/2 in	2 1/2 in	24 in	39RK39
	36 in	24 1/2 in	4 1/2 in	2 1/2 in	36 in	39RK51
	48 in	25 1/2 in	4 1/2 in	2 1/2 in	48 in	39RK22
	24 in	24 1/2 in	4 1/2 in	2 1/2 in	24 in	39RK46
6,000 lb	36 in	24 1/2 in	4 1/2 in	2 1/2 in	36 in	39RK32
Spreader Beams						
500 lb	24 in	24 in	5 in	2 1/2 in	24 in	39RK08
	36 in	30 in	5 in	2 1/2 in	36 in	39RK17
	48 in	36 in	5 in	2 1/2 in	48 in	39RK21
	72 in	48 in	5 in	2 1/2 in	72 in	39RK07
1,000 lb	96 in	60 in	5 in	2 1/2 in	96 in	39RK25
	24 in	24 1/2 in	5 in	2 1/2 in	24 in	39RK20
	36 in	30 1/2 in	5 in	2 1/2 in	36 in	39RK27
	48 in	36 1/2 in	5 in	2 1/2 in	48 in	39RK26
2,000 lb	72 in	48 1/2 in	5 in	2 1/2 in	72 in	39RK18
	96 in	62 in	5 in	2 1/2 in	96 in	39RK09
	24 in	25 in	5 in	2 1/2 in	24 in	39RK31
	36 in	31 in	5 in	2 1/2 in	36 in	39RK54
4,000 lb	48 in	37 in	5 in	2 1/2 in	48 in	39RK65
	72 in	51 in	5 in	2 1/2 in	72 in	39RK57
	96 in	64 in	5 in	2 1/2 in	96 in	39RK50
	24 in	27 in	5 in	2 1/2 in	24 in	39RK03
6,000 lb	36 in	33 in	5 in	2 1/2 in	36 in	39RK34
	48 in	40 in	5 in	2 1/2 in	48 in	39RK56
	72 in	53 in	5 in	2 1/2 in	72 in	39RJ96
	96 in	65 in	5 in	2 1/2 in	96 in	39RK33
	24 in	27 in	5 in	2 1/2 in	24 in	39RK10
	36 in	33 in	5 in	2 1/2 in	36 in	39RK13
	48 in	42 in	5 in	2 1/2 in	48 in	39RK42
	72 in	54 in	5 in	2 1/2 in	72 in	39RK35