



Podium Ladders

- Ideal for working at fixed heights
- Comfortable secure feel with 4X Work Zone to reach in all directions
- Large podium platform with toe guard
- Waist high guard rail with Lock-In accessories slots
- EDGE360 bracing with molded large boots
- Overall ladder height is 3 ft. above platform
- Available with and without casters



20KJ26



45ED70

Series	Platform Height	Ladder Height	Material	WITHOUT CASTERS Item No.	WITH CASTERS Item No.
Type IAA, 375 lb Duty Rating					
PD7300	3 ft	6 ft	Fiberglass	36FX50	45ED69
	4 ft	7 ft		36FX51	45ED70
	6 ft	9 ft		36FX52	45ED71
	8 ft	11 ft		36FX53	45ED72
Type IA, 300 lb Duty Rating					
PD6200	3 ft	6 ft	Fiberglass	20KJ26	45ED64
	4 ft	7 ft		20KJ27	45ED65
	6 ft	9 ft		20KJ28	45ED66
	8 ft	11 ft		20KJ29	45ED67
	9½ ft	13 ft		20KJ30	—
	10 ft	—		—	45ED68

Twin Ladders

- Designed for one- or two-person jobs
- Duty Rating applies to each side

T7400 SERIES

- Aluminum extruded top
- EDGE bracing with aluminum external rail shields
- Aluminum internal spreader bars
- Extra-large knee braces on every step
- 14-ft. to 20-ft. heights are Type 1A, 300 lb.

Fiberglass, Type 1AA, 375-lb. Duty Rating

T400 SERIES

- Aluminum extruded top
- Aluminum internal spreader bars
- Extra-large knee braces on every step
- Metal bottom step braces

Aluminum, Type 1AA, 375-lb. Duty Rating

T6200 SERIES

- Molded LockTop® top securely holds tools
 - EDGE360™ Bracing with molded large boots
 - Steel internal spreader bars
 - Fully knee braced on every step
- Fiberglass, Type 1A, 300-lb. Duty Rating

T370 SERIES

- Aluminum extruded top
 - Steel internal spreader bars
 - Metal bottom step braces
 - Slip-resistant foot pads
- Aluminum, Type 1A, 300-lb. Duty Rating

T6000 SERIES

- Molded HolsterTop® securely hold drills and tools
 - EDGE bracing at bottom
 - Steel external spreader bars
- Fiberglass, Type 1, 250-lb. Duty Rating



T7400 Series



T400 Series



T6200 Series



T6000 Series



T370 Series

Series	Ladder Height	Material	Item No.
Type IAA, 375 lb Duty Rating			
T7400	4 ft	Fiberglass	4XP48
	5 ft		41D242
	6 ft		4XP49
	8 ft		4XP50
	10 ft		4XP51
	12 ft		4XP52
T400	4 ft	Aluminum	41D287
	6 ft		41D288
	8 ft		41D289
	10 ft		41D290
	12 ft		41D291

Series	Ladder Height	Material	Item No.
Type IA, 300 lb Duty Rating			
T7400	14 ft	Fiberglass	4XP53
	16 ft		4XP54
	20 ft		4XP55
	3 ft		41D246
	4 ft		6YG79
	5 ft		3AZX6
T6200	6 ft	Fiberglass	6YG80
	8 ft		6YG81
	10 ft		3AZX7
	12 ft		3AZX8
T370	4 ft	Aluminum	3AZY1
	6 ft		3AZY2
	8 ft		3AZY3
	10 ft		3AZY4
Type I, 250 lb Duty Rating			
T6000	4 ft	Fiberglass	9NV38
	6 ft		8CKH1
	8 ft		9GA67



44YY09



Fiberglass Twin Stepladders

The load capacity applies to each side of the ladder and is built for use by two people (one per side) simultaneously. Comes equipped with heavy-duty boots.

Ladder Height	Item No.
Type IAA, 375 lb Duty Rating	
4 ft	44YY09
6 ft	44YY68
8 ft	44YY16
10 ft	44YY42
12 ft	44YY24