



**Obel Series**



**E7400 Series**



**FTP6200 Series**



## Specialty Ladders

### OBEL SERIES

- Custom molded top designed for electrical contractors
  - Integrated retractable conduit holder for cutting pipe
  - Wire spool holders and a multiuse hook
  - EDGE bracing at bottom
  - Internal spreader bars
- Fiberglass Electricians Job Station Stepladders, Type 1AA, 375-lb. Duty Rating

### E7400 SERIES

- Convenient for versatile applications
- Ideal for two-person jobs and working at various heights
- Duty rating applies to each stepladder side

- Double riveted, fully knee braced steps
  - Aluminum external rail shields and EDGE bracing
- Fiberglass Extension Trestle Ladder, Type 1A, 300-lb. Duty Rating

### FTP6200 SERIES

- Back rail fits through studs, tight areas, around corners and uneven surfaces
  - Spreader handle designed for convenient setup and transport
  - Fully based front section
  - Extra-wide stance for stability
  - Available up to 12 ft.
- Fiberglass Tripod Ladder, Type 1A, 300-lb. Duty Rating

Series	Ladder Height	Material	Item No.
<b>Type IAA, 375 lb Duty Rating</b>			
OBEL00	4 ft	Fiberglass	1FCF1
	6 ft		1FCF2
	8 ft		1FCF3
	10 ft		1FCF4
	12 ft		1FCF5
<b>Type IA, 300 lb Duty Rating</b>			
E7400	8 ft	Fiberglass	4XP05
	10 ft		4XP06
	12 ft		4XP07
	14 ft		4XP08
	16 ft		4XP09
FTP6200	4 ft	Fiberglass	4ZY19
	6 ft		4EB99
	8 ft		4ZY20
	10 ft		41D249
	12 ft		41D250



**36GL23**

## Adjustable Enclosed Safety Cages

- Nonconductive, high-strength, fiberglass-resin composite
- Fully adjustable 1-ft. increments

Offer versatile, safe alternative to tie-off, allowing access to constricted areas and drop ceilings while complying with tie-off rules. Help protect operators in a fully enclosed working platform, allowing them to work safely and quickly with 2 hands. Each side adjusts independently to multiple heights; adjusts to work safely on uneven surface and stairs. Models with Wheel Lift™ casters allow cage to move from place to place fully deployed. Built-in Tip & Glide™ wheels make it quick-and-easy to roll anywhere.

Series	Platform Height	Includes	Item No.
<b>Type IAA, 375 lb Duty Rating</b>			
Compact Safety Cage	4 to 6 ft	Tip and Glide Wheels	48RR82
	6 to 10 ft	Net, Outriggers, Side Tip Wheels, Wheel Lift	48RR88
		Outriggers, Ratchet Levelers, Side Tip Wheels, Wheel Lift	48RR89
Adjustable Safety Cage	3 to 5 ft	Net, Wheel Lift	36GL22
	5 to 9 ft		36GL23
	8 to 14 ft	Net, Outriggers, Wheel Lift	36GL24

**Little Giant**  
Ladder Systems



**Aluminum Extension Planks 4XP31**



**4XN82**

## Ladder Jacks, Planks and Leveler

**Aluminum Extension Planks - PA200 Series**—Made of 2" deep box section extrusions for outstanding rigidity in ladder jack, trestle ladder, and step stool applications. Locking mechanism sets plank in 12" increments; positive stops prevent overextending.

**WARNING:** When assembled as a scaffold or staging, planks must be used in conjunction with suitable guardrail protection in compliance with applicable governmental codes, ordinances, regulations, and safe practices.

**Ladder Jack Clamping System**—Ladder jacks mount to either side of extension ladder and clamps securely hold stage platform to ladder jacks. OSHA and ANSI Standards require ladder jacks only be used on Type 1, Type 1A, or Type 1AA ladders.

- Accommodates up to 20"W stage planks

Description	Series	Overall Length	Load Capacity	Material	Item No.
Extension Plank	PA200	6 to 9 ft	250 lb	Aluminum	4XP30
Extension Plank	PA200	8 to 13 ft	250 lb	Aluminum	4XP31
Extension Plank	PA200	10 to 17 ft	250 lb	Aluminum	4XP32
Ladder Jack Clamping System	—	—	300 lb	—	4XN82
Ladder Leveler	—	—	—	Aluminum	4XP35

