Find more information on Rolling Ladders on page 1034.

Height		No. of Steps	Load Capacity	Platform Depth	Platform Width	Bottom Width		PERFORATED Item No.	EXPANDED METAL Item No.	SERRATEI Item No.
Standar	a Base s 2½ in	Dubbor	Dodo							
meruae	50 in	2	450 lb	10 in	16 in	20 in	24 in	20Z347	20Z343	20Z345
20 in	50 in	2	450 lb	10 in	24 in	28 in	24 in	3FMD7	3FMD5	3FMD9
	50 in	2	450 lb	20 in	16 in	20 in	34 in	20Z348	20Z344	20Z346
			450 lb		24 in	28 in	34 in	20Z351	20Z349	20Z340 20Z350
	50 in 60 in	2	450 lb	20 in 10 in	16 in	20 in	30 in	20Z356	20Z352	20Z354
30 in	60 in	3	450 lb	10 in	24 in	28 in	30 in	3UY30	4XM63	3FME1
	60 in	3	450 lb	20 in	16 in	20 in	41 in	20Z357	20Z353	20Z355
	60 in		450 lb	20 in	24 in	28 in	41 in	20Z360	20Z358	20Z359
	70 in	4	450 lb	10 in	16 in	20 in	37 in	20Z365	20Z361	20Z363
40 in	70 in	4	450 lb	10 in	24 in	28 in	37 in	3UY31	4XM66	3FME2
	70 in	4	450 lb	20 in	16 in	20 in	47 in	20Z366	20Z362	20Z364
	70 in	4	450 lb	20 in	24 in	28 in	47 in	20Z369	20Z367	20Z368
50 in	80 in	5	450 lb	10 in	16 in	20 in	43 in	20Z374	20Z370	20Z372
	80 in	5	450 lb	10 in	24 in	28 in	43 in	3FMD8 *	3FMD6 *	3FME3
	80 in	5	450 lb	20 in	16 in	20 in	53 in	20Z375	20Z371	20Z373
	80 in	5	450 lb	20 in	24 in	28 in	54 in	20Z378	20Z376	20Z377
Include			ear Chain							
20 in	50 in	2	450 lb	10 in	16 in	20 in	24 in	21VA53	21VA45	21VA49
	50 in	2	450 lb	10 in	24 in	28 in	24 in	21VA65	21VA57	21VA61
	50 in	2	450 lb	20 in	16 in	20 in	34 in	21VA55	21VA47	21VA51
	50 in	2	450 lb	20 in	24 in	28 in	34 in	21VA67	21VA59	21VA63
	60 in	3	450 lb	10 in	16 in	20 in	31 in	21VC01	21VA92	21VA96
30 in	60 in	3	450 lb	10 in	24 in	28 in	31 in	21VC13	21VC05	21VC09
00 111	60 in	3	450 lb	20 in	16 in	20 in	41 in	21VC03	21VA94	21VA98
	60 in	3	450 lb	20 in	24 in	28 in	41 in	21VC15	21VC07	21VC11
	70 in	4	450 lb	10 in	16 in	20 in	37 in	21VC93	21VC85	21VC89
40 in	70 in	4	450 lb	10 in	24 in	28 in	37 in	21VD06	21VC97	21VD02
40 111	70 in	4	450 lb	20 in	16 in	20 in	47 in	21VC95	21VC87	21VC91
	70 in	4	450 lb	20 in	24 in	28 in	47 in	21VD08	21VC99	21VD04
50 in	80 in	5	450 lb	10 in	16 in	20 in	43 in	21VD54	21VD46	21VD50
	80 in	5	450 lb	10 in	24 in	28 in	43 in	21VD66	21VD58	21VD62
	80 in	5	450 lb	20 in	16 in	20 in	53 in	21VD56	21VD48	21VD52
	80 in	5	450 lb	20 in	24 in	28 in	54 in	21VD68	21VD60	21VD64
nclude	s Remov	able Re	ear Safety	Chain w	ith Snap I	łook				
50 in	80 in	5	450 lb	10 in	24 in	28 in	43 in	36LH58 †	_	_
Straddle	Base									
	s 2½ in	Rubber	Pads							
30 in	60 in	3	350 lb	20 in	24 in	28 in	41 in	3FME6	3FME4	3FME8
40 in	70 in	4	350 lb	20 in	24 in	28 in	47 in	3FME7	3FME5	3FME9
	s Double									
50 in	80 in	5	350 lb	20 in	24 in	28 in	54 in	6MXV4 *	6MXV6 *	6MXV8
60 in	90 in	6	350 lb	20 in	24 in	28 in	60 in	6MXV5 *	6MXV7 *	6MXV9
								fornia OSHA Stai		



- 30"H handrails included
- Ship assembled
- 450-lb. load capacity (standard base);
- 350-lb. load capacity (straddle base)
- Gray
- 59° climbing angle
- No ladder actuation

Ladder rests solidly on four 21/2" rubber pads when climbing. Easily moved by tilting back on 4" wheels with handrails. The balanced design won't allow ladder to scoot away or toward user.

Note: See Grainger.com® for Safety Yellow options.

Platform Height	Overall Height	No. of Steps	Load Capacity	Platform Depth	Platform Width	Bottom Width	Base Depth	SERRATED Item No.	EXPANDED METAL Item No.	
Aluminum										
20 in	50 in	2	350 lb	10 in	16 in	20 in	24 in	20Z511	_	
	50 in	2	350 lb	10 in	24 in	28 in	24 in	3FMH7	_	
	50 in	2	350 lb	20 in	16 in	20 in	34 in	20Z515	_	
	50 in	2	350 lb	20 in	24 in	28 in	34 in	20Z519	_	
30 in	60 in	3	350 lb	10 in	16 in	20 in	30 in	20Z512	_	
	60 in	3	350 lb	10 in	24 in	28 in	30 in	3FMH8	_	
	60 in	3	350 lb	20 in	16 in	20 in	40 in	20Z516	_	
	60 in	3	350 lb	20 in	24 in	28 in	40 in	20Z520	_	
40 in	70 in	4	350 lb	10 in	16 in	20 in	37 in	20Z513	_	
	70 in	4	350 lb	10 in	24 in	28 in	37 in	3FMH9	_	
	70 in	4	350 lb	20 in	16 in	20 in	47 in	20Z517	_	
	70 in	4	350 lb	20 in	24 in	28 in	47 in	20Z521	_	
50 in	80 in	5	350 lb	10 in	16 in	20 in	43 in	20Z514	_	
	80 in	5	350 lb	10 in	24 in	28 in	43 in	3FMJ1 *	_	
	80 in	5	350 lb	20 in	16 in	20 in	54 in	20Z518 *	_	
	80 in	5	350 lb	20 in	24 in	28 in	54 in	20Z522 *	_	
Stainless Steel										
20 in	50 in	2	450 lb	10 in	24 in	28 in	24 in	20Z527	20Z523	
30 in	60 in	3	450 lb	10 in	24 in	28 in	30 in	20Z528	20Z524	
40 in	70 in	4	450 lb	10 in	24 in	28 in	37 in	20Z529	20Z525	
50 in	80 in	5	450 lb	10 in	24 in	28 in	43 in	20Z530 *	20Z526 *	
* Ladders for use in California will be modified to comply with California OSHA Standards.										



- 30"H handrails included
 - 59° climbing angle
- Ship assembled

During climbing, each standard base ladder sits solidly on four 21/2" rubber pads for greater stability. Easily moved by tilting back on 4" wheels with handrails. The balanced design won't allow ladder to scoot away or toward user.

Lock-N-Stock Steel Folding Ladders

- 22"H handrails included
- Ship assembled
- 350-lb. load capacity
- 7" platform depth
- 16" platform width ■ 24" bottom width
- Blue
- Rear exit on 3KNK7 and 3KNK8
- 59° climbing angle
- No ladder actuation

Ladders are easy to climb, roll, fold, and store. Lock in folded or climbing positions. Easy-tomaneuver in open or closed position.

Platform Height	Overall Height	No. of Steps	Base Depth	PERFORATED Item No.
19 in	41 in	2	17 in	3KNK7
28 ½ in	50 ½ in	3	23 in	3KNK8
38 in	60 in	4	30 in	4UDL5





3KNK8