



Indoor Rolling Utility Work Platforms

- Yellow powder-coat finish
- Lightweight
- Can easily be set up and dismantled by one person
- Platform adjusts every 2" in height
- Roll from room to room without disassembling
- 5"-dia. casters with locking wheels

5AB11



Pro-Jax® lightweight, all-steel scaffolds are designed for indoor use. Plywood deck platform has steel frame and supports. Casters are removable for use on stairs. Knurled rungs. Outrigger needed when increasing platform height. Ideal for electrical, painting, acoustical, and finishing work; window cleaning; sign installation and maintenance; building maintenance; and HVAC installation.

Note: Guardrails are required by OSHA on all platforms 10 ft. or higher.

L	W	Platform Height	Platform Length	Work Height	Load Capacity	For Use With	Item No.
6 ft.	29"	2 to 4 ft	72 in	10 ft 6 in	1,000 lb	—	5AA99
6 ft.	29"	2 to 6 ft	72 in	12 ft 6 in	1,000 lb	Guardrail	5AB10
6 ft.	29"	2 to 11 ft 6 in	72 in	18 ft	1,000 lb	Guardrail & Outriggers	5AB11
6 ft.	29"	2 to 17 ft	72 in	23 ft 6 in	1,000 lb	Guardrail & Outriggers	5AB12
Accessories							
		Height Extension Kit, 39"H x 6 ft. L					5AB13
		Height Extension Kit, 69"H x 6 ft. L					5AB14
		Guard Rail Kit, 42"H x 6 ft. L					5AB15
		Outrigger Kit, 18"H x 1.5 ft. L x 18"W					5AB16
		Outrigger Kit, 24"H x 2 ft. L x 18"W					5AB17

5AA87



Indoor/Outdoor Rolling Tower Work Platforms

- Yellow powder-coat finish
- Provide larger platform for multiple persons and materials
- Greater height capability than utility scaffolds
- Can accommodate longer length requirements
- 8"-dia. casters with locking wheels

Complete systems assemble quickly and easily; frames, braces, inserts, attachments, guardrails and workboards. High-strength steel tubing frames have coped and arc welded perimeter joints. Large, adjustable-height work platforms and easy-access guardrail system. Order accessories separately to reconfigure or expand existing tower systems.

L	D	Platform Height	Work Height	Load Capacity	For Use With	Item No.	
7 ft.	60 in	2 to 11 ft	17 ft	2,000 lb	Guardrail	5AB18	
7 ft.	60 in	2 to 16 ft	22 ft	2,000 lb	Guardrail & Outriggers	5AA87	
7 ft.	60 in	2 to 21 ft	27 ft	2,000 lb	Guardrail & Outriggers	5AA88	
10 ft.	60 in	2 to 11 ft	16 ft 10 in	2,000 lb	Guardrail	45NU27	
10 ft.	60 in	2 to 16 ft	21 ft 11 in	2,000 lb	Guardrail & Outriggers	45NU28	
10 ft.	60 in	2 to 21 ft	27 ft	2,000 lb	Guardrail & Outriggers	45NU29	
Accessories							
		Scaffold Frame, 5 ft W x 0 in L					5AA89
		Scaffold Plank, 19 in W x 7 ft L					5AA90
		Guard Rail, 5 ft L					5AA91
		Guard Rail, 7 ft L					5AA92
		Scaffold Toeboard, 6 in H					5AA93
		Scaffold Crossbrace					5AA94
		Scaffold Brace					5AA95
		Scaffold Caster					5AA96
		Scaffold Leveling Jack, 24 in H					5AA97
		Scaffold Pigtail Pin					5AA98

Scaffold Towers

- Towers meet OSHA, ANSI, and CSA requirements

Jobsite Series—Suitable and safe for all types of interior work and can be easily stackable up to 3 units high. Steel construction with yellow powder-coat finish. Include 5" casters for easy mobility.

Saferstack Contractor Series—Complete scaffold tower is 2 sections high with safety guardrails and platforms. Frames stack in 30% less space than regular models, interlock for safer storage and transport, and help prevent stacked frames from sliding. Constructed with steel, aluminum, and wood with a blue antislip, textured powder-coat finish. 38HT50 includes 4 leveling jacks.

L	W	Platform Height	Platform Length	Overall Height	Load Capacity	Item No.	
Jobsite Series							
6 ft.	58½"	12 ft	75 in	14 ft 9 in	840 lb	38HT48	
6 ft.	122"	18 ft	75 in	20 ft 5 in	733 lb	38HT65	
74¾"	29¾"	Adjustable	74 ¾ in	6 ft 3 in	1,000 lb	20TN25	
6½½ ft.	29¾"	6 ft	74 in	6 ft 6 in	1,000 lb	38HT63	
Saferstack							
5 ft.	93½"	10 ft	84 in	14 ft 6 in	2,300 lb	38HT52	
5¾ ft.	93½"	10 ft	84 in	14 ft	2,500 lb	38HT50	
Accessories							
Jobsite Series							
		Scaffold Caster					20TN27
		Guard Rail					20TN30
		Outrigger Kit					20TN31
Saferstack							
		Scaffold Caster					20TN20
		Scaffold Crossbrace					20TN21
		Scaffold Coupling Pin					20TN28

