



For more information on rolling ladders, see page 1034.



4ZY17



38HT59



4XN62



4XP22



## Adjustable Rolling Platforms

### STEEL

**Werner**—Lightweight portable scaffold sets up in seconds. Planks can be positioned at multiple levels. Scaffold rolls on 4 high-grade, mar-resistant locking neoprene wheels. Folds for storage. Meet OSHA and ANSI Standards.

**MetalTech**—Designed for indoor use, scaffold folds and stores easily. 38HT79, 38HT80 and 38HT59 meet OSHA, ANSI, and CSA Standards.

### ALUMINUM

**Werner**—Lightweight and corrosion-resistant. Double-locking legs allow height adjustment up to 12". Base section includes wood-deck plank and 5" swivel lock casters. Towers include base section, upper and guard rail sections, toe boards, and outriggers. Meet OSHA and ANSI Standards.

| Description         | Height     | Platform Width | Depth     | Overall Height | Load Capacity | Brand     | Item No. |
|---------------------|------------|----------------|-----------|----------------|---------------|-----------|----------|
| <b>Steel</b>        |            |                |           |                |               |           |          |
| Rolling Scaffold    | 3 ft 8 in  | 46 in          | 17 in     | 4 ft           | 500 lb        | Werner    | 4ZY17    |
| Scaffold Tower      | 6 ft       | 72 in          | 29 in     | 6 ft 3 in      | 1,000 lb      | Werner    | 41D335   |
| Scaffold            | 3 ft 10 in | 39 in          | 21 1/2 in | 3 ft 3 in      | 500 lb        | Metaltech | 38HT67   |
| Scaffold Tower      | 4 ft       | 46 in          | 57 in     | 4 ft 3 in      | 500 lb        | Metaltech | 38HT79   |
| Portable Scaffold   | 4 ft       | 50 in          | 20 1/2 in | 5 ft 3 in      | 750 lb        | Metaltech | 38HT59   |
| Scaffold Tower      | 5 ft       | 48 in          | 57 in     | 6 ft 3 in      | 900 lb        | Metaltech | 38HT80   |
| <b>Aluminum</b>     |            |                |           |                |               |           |          |
| Scaffold Tower Base | 7 ft 6 in  | 72 in          | 29 in     | 7 ft 6 in      | 500 lb        | Werner    | 4XN62    |
| Scaffold Tower      | 12 ft 6 in | 72 in          | 29 in     | 15 ft 6 in     | 5,000 lb      | Werner    | 4XP22    |
| Scaffold Tower      | 15 ft      | 72 in          | 29 in     | 18 ft 6 in     | 500 lb        | Werner    | 4XP23    |



**Platform 10H719 with Tool Tray 10H725 and Safety Hoist 10H724**



## Adjustable Rolling Steel Platforms

- Can be easily assembled by 1 person in about 5 min.
- Include four 5" locking casters
- Yellow color

Platform height manually adjusts from 2 ft. to 11 ft. (in 6" increments). Platforms come complete with outriggers, toeboards, and guardrails. Outriggers telescope out on all 4 corners for a better than 3:1 height-to-base ratio. Platforms meet OSHA, ANSI, and CSA requirements.

Order accessories separately to reconfigure or expand existing tower systems.

| Height  | Platform Width | Depth | Overall Height          | Load Capacity | Item No. |
|---|----------------|-------|-------------------------|---------------|----------|
| <b>Rolling Work Platforms</b>                             |                |       |                         |               |          |
| 24 in to 132 in   | 19 in          | 72 in | 6 ft 6 in to 14 ft 8 in | 550 lb        | 10H719   |
| 24 in to 132 in   | 19 in          | 96 in | 6 ft 6 in to 14 ft 8 in | 550 lb        | 10H721   |
| 24 in to 132 in   | 22 in          | 72 in | 6 ft 6 in to 14 ft 8 in | 800 lb        | 29EZ42   |
| 24 in to 132 in   | 22 in          | 96 in | 6 ft 6 in to 14 ft 8 in | 800 lb        | 29EZ43   |
| <b>Accessories</b>  |                |       |                         |               |          |
| Height Extension Kit, 78 inH x 6 ft L For Use With 10H719 |                |       |                         |               | 10H720   |
| Height Extension Kit, 78 inH x 8 ft L For Use With 10H721 |                |       |                         |               | 10H722   |
| Height Extension Kit, 72 inH x 6 ft L For Use With 29EZ42 |                |       |                         |               | 29EZ44   |
| Height Extension Kit, 96 inH x 8 ft L For Use With 29EZ43 |                |       |                         |               | 29EZ45   |
| Safety Hoist  |                |       |                         |               | 10H724   |
| Tool Tray, 52 inL x 9 inW                                 |                |       |                         |               | 10H725   |
| Safety Rail Storage Cradle For Use With 10H719 and 10H720 |                |       |                         |               | 10H728   |



## Cotterman® Truck/Trailer Access Ladder

- 800-lb. load rating

Offers easy entry to tractor trailers and cube vans where loading docks or bays are not available. Ladder can be easily moved on two 10"-dia. rear wheels. Features slip-resistant strut treads and 36"H handrails (42" in California) with removable snap hook chains. 50° climbing angle for easy descent. Meets OSHA and ANSI Standards.

| No. of Steps | Platform Length | Platform Width | Step Width | Bottom Width | Base Depth | Item No. |
|--------------|-----------------|----------------|------------|--------------|------------|----------|
| 5-Step       | 24 in           | 27 in          | 24 in      | 27 1/2 in    | 69 in      | 5FE6     |



## Refrigerator Truck Rolling Access Platform

- Height adjusts in 4" increments

Provides fall protection during routine maintenance and inspection of refrigeration units on small- to medium-sized box trucks. 24"L x 120"W platform provides a comfortable and safe work surface. Serrated tread surface for slip resistance and drainage; ladders on both sides for dual access. Reinforced lifting points accommodate adjustability using standard engine puller and designated lifting point for using rope and bucket for bringing items from ground to platform.



| Height           | Platform Width | Depth  | Overall Height | Load Capacity | Item No. |
|------------------|----------------|--------|----------------|---------------|----------|
| 103 in to 115 in | 24 in          | 130 in | 12 to 13 ft    | 500 lb        | 4RC13    |