



**2-Step, No Handrails F2125**



**4-Step, Double Handrails F2130**



No. of Steps	Platform Height	Step Width	Bottom Width	Base Depth	► CHOOSE: Color	DOUBLE HANDRAILS		LEFT HANDRAIL		RIGHT HANDRAIL		NO HANDRAILS	
						Overall Height	Item No.	Overall Height	Item No.	Overall Height	Item No.	Overall Height	Item No.
<b>8 in Platform Depth</b>													
2	18 in	16 in	22 in	20 in	Black, Blue, Brown, Gray, Red	48 in	F2126	48 in	D5249	48 in	D5254	—	—
2	18"	16 in	22 in	20 in	Gray, Red	—	—	—	—	—	—	22 in	F2125
3	27 in	16 in	24 in	27 in	Black, Blue, Brown, Gray, Red	57 in	F2128	57 in	D5251	57 in	D5255	—	—
3	27"	16 in	24 in	27 in	Gray	—	—	—	—	—	—	31 in	F2127
4	36 in	16 in	25 in	34 in	—	66 in	F2130	66 in	D5252	66 in	D5256	40 in	F2129
5	45 in	16 in	26 in	40 in	Black, Blue, Brown, Gray, Red	75 in	F2132	75 in	D5253	75 in	D5257	49 in	F2131
6	54 in	16 in	27 in	48 in	—	84 in	D5248	—	—	—	—	—	—
<b>14 in Platform Depth</b>													
2	18 in	16 in	22 in	26 in	Black, Blue, Brown, Gray, Red	48 in	D5264	48 in	D5269	48 in	D5274	—	—
2	18"	16 in	22 in	26 in	Red	—	—	—	—	—	—	22 in	D5259
3	27"	16 in	24 in	32 in	Blue, Gray, Red	—	—	—	—	—	—	31 in	D5261
3	27 in	16 in	24 in	32 in	—	57 in	D5265	57 in	D5271	57 in	D5275	—	—
4	36 in	16 in	25 in	39 in	—	66 in	D5266	66 in	D5272 †	66 in	D5276 †	40 in	D5262 †
5	45 in	16 in	26 in	46 in	Black, Blue, Brown, Gray, Red	75 in	D5267	75 in	D5273 †	75 in	D5277 †	49 in	D5263 †
6	54 in	16 in	27 in	53 in	—	84 in	D5268	—	—	—	—	—	—

\* Ladders for use in California will be modified to California Standards. † Not for use in California.

**Office Ladders**

- 450-lb. load rating
- 8"D steps, 8" or 14"D top step
- Molded polyurethane on polyolefin casters with Delrin bearings
- Powder-coat finish

1-pc. welded construction of 1" square tubes. Solid steel steps with black rubber tread matting. Roll easily on four 2" spring-loaded casters protected by caster cup housings. 1- to 5-step models without handrails ship fully assembled; 2- to 6-step models with handrails require assembly. Meet OSHA and ANSI Standards.

**Cotterman®**



46C355

**Cotterman® StockNStore Ladders**

- 350-lb. load rating
- 16"W x 7"D step with 10"D top step
- Roll in collapsed or set-up positions

Ladders open smoothly during the transition from rolling to setting down on rubber feet. Include a cable-release system for weight-activated hinges with no pinch points. Hinges automatically lock in place. For use where space is limited but quick access to elevated areas is required.

No. of Steps	Platform Height	Overall Height	Bottom Width	PERFORATED TREAD Item No.	SERRATED TREAD Item No.	ANTISLIP VINYL TREAD Item No.
<b>Powder-Coat Steel</b>						
2	20 in	50 in	20 in	46C346	46C352	46C349
3	30 in	60 in	20 in	46C347	46C353	46C350
4	40 in	70 in	20 in	46C348	46C354	46C351
<b>Aluminum</b>						
2	20 in	50 in	20 in	46C355	46C361	46C358
3	30 in	60 in	20 in	46C356	46C362	46C359
4	40 in	70 in	20 in	46C357	46C363	46C360

2-Step 4RC74



**Folding Ladder Stands**

- 350-lb. load rating
- 16"W x 7"D step with 10"D top step
- Powder-coat finish

Combine the utility of a mobile rolling ladder with the convenience of a folding step stand. Able to roll while in closed or set-up positions. Fold for easy storage. Meet OSHA and ANSI Standards.

No. of Steps	Platform Height	Overall Height	Bottom Width	Base Depth	PERFORATED TREAD Item No.
2	20 in	44 in	21 in	20 in	4RC74
3	30 in	54 in	21 in	27 in	4RC75
4	40 in	64 in	21 in	34 in	4RC76



4ZY18



**Fold-Up Work Platforms**

Provide a workspace along walls and windows. Nonskid surface with slip-resistant rubber feet protect floors. Easily set up and fold for storage. 4ZY18 meets ANSI and OSHA Standards.

Platform Depth	Platform Height	Platform Width	Load Capacity	Brand	Item No.
<b>Aluminum</b>					
39 1/2 in	20 9/16 in	12 in	225 lb	Werner	4ZY18
<b>Fiberglass</b>					
36 in	21 in	12 in	300 lb	Louisville	33J771

**Base Level with Add-On Level and Rubber Matting with Yellow Border**



**50C INDUSTRIAL**

**Add-A-Level Work Platforms**

Allow work areas to be customized to correct height and width. Additional matting can be added-on to top level. Lightweight, recycled plastic material resists rust, oils, grease, most acids, and chemicals. Open grid, flow-through pattern for decontamination environments.

Bottom Width	Base Depth	Overall Height	Item No.	Width	Length	Overall Height	Item No.
<b>Base Levels</b>				<b>Rubber Matting with Yellow Border</b>			
24 in	36 in	2 1/2 in	1DPC9	24 in	36 in	7/8 in	459W20
24 in	48 in	2 1/2 in	2KUW1	24 in	48 in	7/8 in	459W22
24 in	66 in	2 1/2 in	1DPD3	24 in	66 in	7/8 in	459W24
24 in	96 in	2 1/2 in	2KUW3	24 in	96 in	7/8 in	459W26
36 in	36 in	2 1/2 in	4RNR5	36 in	36 in	7/8 in	459W28
36 in	66 in	2 1/2 in	4RNR7	36 in	66 in	7/8 in	459W30
36 in	96 in	2 1/2 in	1DPD4	<b>Rubber Matting without Border</b>			
<b>Add-On Levels</b>				24 in	48 in	7/8 in	459W21
24 in	36 in	2 1/2 in	1DPD1	24 in	66 in	7/8 in	459W23
24 in	48 in	2 1/2 in	2KUW2	24 in	96 in	7/8 in	459W25
24 in	66 in	2 1/2 in	1DPD2	36 in	36 in	7/8 in	459W27
24 in	96 in	2 1/2 in	2KUW4	36 in	66 in	7/8 in	459W29
36 in	36 in	2 1/2 in	4RNR6	36 in	96 in	7/8 in	459W31
36 in	66 in	2 1/2 in	4RNR8	<b>Poly-Clip Horizontal Connectors</b>			
36 in	96 in	2 1/2 in	1DPD5	4DB39			