



H4-Rated Electric Chain Hoists

- Pendant control
- CSA and HMI Certified

Gearbox, brake, and slip clutch are maintenance-free for up to 10 yr. Simple plug connections are located in a centralized area.

Load Capacity	Lift Speed	Motor HP	Voltage	Phase	Amps @ Low Volts	16-ft. Lift 2- to 12-ft. Control Cord Item No.	26-ft. Lift 12- to 22-ft. Control Cord Item No.
2-Speed							
250 lb	32/8 fpm	0.3 hp	230	3	2.9 A	33Z983	33Z984
			460	3	1.35 A	33Z981	33Z982
			575	3	1.2 A	33Z985	33Z986
500 lb	24/6 fpm	0.48 hp	230	3	3 A	33Z989	—
			460	3	1.55 A	33Z987	33Z988
			575	3	1.0 A	33Z990	—
1000 lb	18/4.5 fpm	0.66 hp	230	3	5 A	33Z993	—
			460	3	2.5 A	33Z991	33Z992
			575	3	1.8 A	33Z994	—
2000 lb	16/4 fpm	1.2 hp	230	3	4.5 A	33Z997	—
			460	3	2.25 A	33Z995	33Z996
			575	3	1.6 A	33Z998	—
4000 lb	16/4 fpm	2.4 hp	460	3	6.1 A	33Z999	34A001
			575	3	3.9 A	34A002	—
Variable Speed							
250 lb	0 to 100 fpm	0.98 hp	480	3	3.1 A	34A033	34A034
500 lb	0 to 52 fpm		480	3	3.1 A	34A035	34A036
1000 lb	0 to 26 fpm		480	3	2.9 A	34A037	34A038
2000 lb	0 to 20 fpm	2.95 hp	480	3	4.5 A	34A039	34A040
	0 to 40 fpm		480	3	4.5 A	34A041	—
4000 lb	0 to 20 fpm		480	3	4.5 A	34A042	34A043
5000 lb	0 to 20 fpm		480	3	4.5 A	34A044	—
	0 to 13 fpm		480	3	4.5 A	34A044	—



H4-Rated NER Food-Grade 3-Phase Electric Chain Hoists

- Food-grade lubricants meet FDA standards
- Epoxy paint
- Nickel-painted load chain
- Stainless steel and nickel-plated components
- Designed for the food processing industry
- ASME H4 classification for high-duty cycle
- RoHS Compliant
- Meet ANSI/ASME B30.16

Load Capacity	Lift Speed	Motor HP	Voltage	Min. Between Hooks	Amps @ Low Volts	10 ft Hoist Lift 6 ft Control Cord Item No.	15 ft Hoist Lift 11 ft Control Cord Item No.	20 ft Hoist Lift 16 ft Control Cord Item No.
500 lb	15 fpm	0.75 hp	230/460	13 13/16 in	3.4 A	33RV52	33RV53	33RV54
	15/2.5 fpm	0.75 hp	460	13 13/16 in	3.4 A	33RV64	33RV65	33RV66
1,000 lb	15 fpm	0.75 hp	230/460	14 5/8 in	3.4 A	33RV55	33RV56	33RV57
	15/2.5 fpm	0.75 hp	460	14 5/8 in	3.4 A	33RV67	33RV68	33RV69
2,000 lb	14 fpm	1.2 hp	230/460	17 in	4.8 A	33RV58	33RV59	33RV60
	14/2.5 fpm	1.2 hp	460	17 in	4.8 A	33RV70	33RV71	33RV72
4,000 lb	14 fpm	2.4 hp	230/460	22 5/8 in	2.4 A	33RV61	33RV62	33RV63
	14/2.5 fpm	2.4 hp	460	22 5/8 in	2.4 A	33RV73	33RV74	33RV75



H4-Rated TNER Theatrical Electric Hoists

- Matches common speed requirements
- Can fit in common road cases
- Handles offered as standard
- Outdoor-rated as standard
- Grease-packed gear-box
- Designed for the unique requirements of the theater industry
- 5-yr. brake warranty

Load Capacity	Lift Speed	Motor HP	Voltage	Min. Between Hooks	Amps @ Low Volts	10 ft Hoist Lift Item No.	60 ft Hoist Lift Item No.
1,000 lb	16 fpm	0.65 hp	230/460	13 13/16 in	3.7 A	33RW49	33RW50
2,000 lb	16 fpm	1.3 hp	230/460	16 in	5.6 A	33RW51	33RW52
4,000 lb	8 fpm	1.3 hp	230/460	22 13/16 in	5.6 A	33RW53	33RW54

