




Adjustable-Height Steel



Adjustable- and Fixed-Height Gantry Cranes

- Balanced design for easy rolling even under load
- Simple, bolt-together construction
- Easy set-up and maintenance
- Conform to AISC, OSHA, and CMAA Specifications



Adjustable-Height Aluminum—Lightweight, all-aluminum gantry cranes are perfect for applications where crane weight is critical. Height and span are adjustable. Height adjusts down from maximum in 6" increments.

- 4 phenolic swivel casters

Adjustable-Height Steel—Heavy-duty, supported leg design. Adjustable span on 10- to 16-ft. models. Height adjusts down from maximum in 12" increments.

- 4 steel swivel casters

Fixed-Height Steel—Designed with supported legs for heavy-duty applications. Adjustable span is standard. Assembly instructions provided.


- 4 steel swivel casters

Load Capacity	Min. I Beam Height	Max. I Beam Height	Gantry Crane Span	Gantry Crane Clear Span	I Beam Height	I Beam Flange Width	Wheel Dia.	Item No.
Adjustable-Height Aluminum - DAYTON								
2000 lb	92 in	122 in	6 ft 10 in	6 ft	6.0 in	3.3 in	8 in	4EER2
	92 in	122 in	6 ft 7 in	6 ft	6.0 in	3.44 in	8 in	55AJ07
	92 in	122 in	8 ft 8 in	8 ft	6.0 in	3.44 in	8 in	55AJ08
	92 in	122 in	10 ft 8 in	10 ft	8.0 in	4.0 in	8 in	55AJ09
	114 in	144 in	8 ft 8 in	8 ft	6.0 in	3.44 in	8 in	55AJ10
4000 lb	92 in	122 in	7 ft 2 in	6 ft 4 in	8.0 in	4.0 in	8 in	55AJ11
	92 in	122 in	11 ft 2 in	10 ft 4 in	8.0 in	4.0 in	8 in	55AJ12
	114 in	144 in	11 ft 2 in	10 ft 4 in	8.0 in	4.0 in	8 in	55AJ13
Adjustable-Height Steel - CALDWELL								
2000 lb	70 1/8 in	108 in	14 ft 11 1/2 in	14 ft 4 in	8.0 in	4.0 in	6 in	40M901
	72 in	108 in	12 ft 11 1/2 in	12 ft 5 in	8.0 in	4.0 in	6 in	40M899
	84 in	120 in	10 ft 11 1/2 in	10 ft 5 in	6.0 in	3.33 in	6 in	40M905
	88 1/8 in	144 in	14 ft 11 1/2 in	14 ft 4 in	8.0 in	4.0 in	6 in	40M913
	96 in	144 in	10 ft 11 1/2 in	10 ft 5 in	6.0 in	3.33 in	6 in	40M911
	96 in	144 in	12 ft 11 1/2 in	12 ft 5 in	8.0 in	4.0 in	6 in	40M912
	108 in	168 in	10 ft 11 1/2 in	10 ft 5 in	6.0 in	3.33 in	6 in	40M917
4000 lb	74 1/2 in	108 in	10 ft 11 1/2 in	10 ft 5 in	8.0 in	4.0 in	8 in	40M935
	86 1/2 in	120 in	10 ft 11 1/2 in	10 ft 5 in	8.0 in	4.0 in	8 in	40M941
	92 in	144 in	14 ft 11 1/2 in	14 ft 4 in	10.0 in	4.66 in	8 in	40M949
	98 in	144 in	10 ft 11 1/2 in	10 ft 5 in	8.0 in	4.0 in	8 in	40M947
	98 in	144 in	12 ft 11 1/2 in	12 ft 5 in	8.0 in	4.0 in	8 in	40M948
	104 1/8 in	168 in	14 ft 11 1/2 in	14 ft 4 in	10.0 in	4.66 in	8 in	40M955
	110 1/2 in	168 in	10 ft 11 1/2 in	10 ft 5 in	8.0 in	4.0 in	8 in	40M953
6000 lb	110 1/2 in	168 in	12 ft 11 1/2 in	12 ft 5 in	8.0 in	4.0 in	8 in	40M954
	128 1/8 in	192 in	12 ft 11 1/2 in	12 ft 4 in	8.0 in	4.0 in	8 in	21ZF10
	84 in	120 in	10 ft 5 1/2 in	9 ft 5 in	10.0 in	4.66 in	8 in	40M977
	106 1/8 in	168 in	14 ft 5 1/2 in	9 ft 5 in	10.0 in	4.66 in	8 in	40M991
	108 in	168 in	10 ft 5 1/2 in	9 ft 5 in	10.0 in	4.66 in	8 in	40M989
	108 in	168 in	12 ft 5 1/2 in	11 ft 5 in	10.0 in	4.66 in	8 in	40M990
	94 1/8 in	144 in	14 ft 5 1/2 in	13 ft 4 in	12.0 in	5.5 in	8 in	40N022
8000 lb	96 in	144 in	10 ft 5 1/2 in	9 ft 5 in	10.0 in	4.66 in	8 in	40N020
	106 1/8 in	168 in	14 ft 5 1/2 in	13 ft 4 in	12.0 in	5.5 in	8 in	40N028
	108 in	168 in	20 ft 4 in	19 ft 5 in	15.0 in	5.5 in	8 in	40N030
10000 lb	108 in	168 in	10 ft 5 1/2 in	9 ft 5 in	12.0 in	5.5 in	8 in	40N062
Fixed-Height Steel - CALDWELL								
2000 lb	120 in	120 in	12 ft 11 in	12 ft 4 in	8.0 in	4.0 in	6 in	40M748
	120 in	120 in	14 ft 11 in	14 ft 4 in	8.0 in	4.0 in	6 in	40M749
	120 in	120 in	10 ft 11 in	10 ft 4 in	6.0 in	3.33 in	6 in	40M747
	144 in	144 in	12 ft 11 in	12 ft 4 in	8.0 in	4.0 in	6 in	40M754
4000 lb	120 in	120 in	12 ft 11 in	12 ft 4 in	8.0 in	4.0 in	8 in	40M772
	120 in	120 in	14 ft 11 in	14 ft 4 in	10.0 in	4.66 in	8 in	40M773
	144 in	144 in	12 ft 11 in	12 ft 4 in	8.0 in	4.0 in	8 in	40M778
	192 in	192 in	16 ft 11 in	16 ft 4 in	10.0 in	4.66 in	8 in	40M792
10000 lb	120 in	120 in	10 ft 4 1/2 in	9 ft 4 in	12.0 in	5.5 in	8 in	40M844
	192 in	192 in	14 ft 4 1/2 in	13 ft 4 in	15.0 in	5.5 in	8 in	40M864
16000 lb	192 in	192 in	20 ft	18 ft 6 in	16.43 in	7.12 in	8 in	40M890



Heavy-Duty Steel

Heavy-Duty Aluminum



Portable Steel and Aluminum Gantry Cranes

- 4 swivel casters
- 2 uprights and 1 crossbar I-beam

Accept most manual and electric hoists and trolleys (not included). Ship unassembled.

Heavy-Duty Steel—Casters feature a 4-position swivel lock in 90° intervals.

Heavy-Duty Aluminum—Suitable for two-person assembly in the field or

where repeated assembly and knock-down is required. Pinned-together modular design completely disassembles. Casters feature 4-position swivel locks in 90° intervals.

Adjustable-Height Models—Adjust in 6" increments by using come-along, fork truck, or overhead crane (not included). Uprights have ratchet puller/come-along attachment points.

Load Capacity	Min. I Beam Height	Max. I Beam Height	Gantry Crane Span	Gantry Crane Clear Span	I Beam Height	I Beam Flange Width	Wheel Dia.	Color	Item No.
Fixed-Height Heavy-Duty Steel									
2,000 lb	90 in	90 in	6 ft	5 ft 9 in	4.0 in	2.66 in	5 in	Blue	48TC36
	120 in	120 in	10 ft	7 ft 6 in	6.0 in	4.0 in	8 in	Blue	48TC30
	120 in	120 in	20 ft	17 ft 6 in	10.0 in	4.0 in	8 in	Blue	48TC31
4,000 lb	120 in	120 in	10 ft	7 ft 6 in	8.0 in	4.0 in	8 in	Blue	48TC32
Adjustable-Height Heavy-Duty Steel									
2,000 lb	90 in	144 in	10 ft	7 ft 6 in	6.0 in	4.0 in	8 in	Blue	48TC25
	102 in	168 in	15 ft	12 ft 6 in	6.0 in	4.0 in	8 in	Blue	48TC27
	114 in	169 in	10 ft	7 ft 6 in	6.0 in	4.0 in	8 in	Blue	48TC26
4,000 lb	90 in	144 in	10 ft	7 ft 6 in	8.12 in	4.0 in	8 in	Blue	48TC28
	102 in	168 in	10 ft	7 ft 6 in	8.12 in	4.0 in	8 in	Blue	48TC29
Adjustable-Height Heavy-Duty Aluminum									
2,000 lb	114 in	144 in	8 ft	6 ft	6.0 in	3.31 in	8 in	Gray	48TC23
	114 in	144 in	12 ft	10 ft	8.0 in	4.0 in	8 in	Gray	48TC22
4,000 lb	92 in	122 in	10 ft	8 ft	8.0 in	4.19 in	8 in	Gray	48TC24