



## Steel Davit Cranes

Individually tested and certified at 125%. Each davit crane features 360° rotation with four different boom height adjustments. Optional AC and DC winches. Cranes include mounting base and steel cable.

Cap.	Lift Range	Finish	Base Type	115V AC OPERATION Item No.	12V DC OPERATION Item No.	MANUAL OPERATION Item No.
1,000 lb	0 in to 540 in	Zinc Plated	Socket Base	302J61	302J64	—
		Zinc Plated	Pedestal Base	302J62	302J63	—
	0 in to 660 in	Zinc Plated	Wall Mount Base	321H28	321H29	—
		Zinc Plated	Socket Base	—	—	302J59
		Zinc Plated	Pedestal Base	—	—	302J60
		Zinc Plated	Wall Mount Base	—	—	321H27



## Truck/Floor-Mount Jib Cranes

Mount to truck trailer bed or floor. Crane swivels 360°, and boom manually telescopes. Steel construction with painted finish. Mounting base has predrilled holes (hardware not included).

### MANUAL WINCH

■ 8" x 8" base plate

Boom is raised with manual hydraulic hand pump. Cable winch raises and lowers the lifting hook.

### POWER WINCHES

■ 12" x 12" base plate

#### DC Models

50-ft., 3/16"-dia. wire cable and 12 1/2-ft. power cord for attaching to truck battery (battery not included). Handheld remote control on 8-ft. cord.

#### AC Models

25-ft., 1/4"-dia. wire cable and 9-ft. power cord have molded plug. They operate with toggle switch on side of winch.

Cap.	Reach	Lift Range	Item No.
<b>Manual Winch</b>			
400 lb	0 in to 38.5 in	0 in to 120 in	4ZB24
<b>Power Winches, 12V DC</b>			
1,500 lb	43.06 in to 66.75 in	47 1/2 in to 73 3/4 in	4ZB22
2,000 lb	51.25 in to 87.25 in	59 1/2 in to 106 1/2 in	4ZB20
<b>Power Winches, 115V AC</b>			
1,500 lb	43.06 in to 66.75 in	48 1/2 in to 73 3/4 in	4ZB23
2,000 lb	51.25 in to 87.25 in	59 1/2 in to 106 1/2 in	4ZB21



**49P538**  
Base and Cable  
Not Included



## CompOZite Davit Cranes

Davit Cranes use a combination of advanced composite materials and Mil-Spec, zinc-plated steel to create a light, long-lasting, and easy-to-use system for lifting. Composite material also has excellent corrosion resistance. Each crane is proof tested and includes a test certificate.

### MOUNTING BASES

Include mounting pattern template. Wall-mount base has a 360° swivel angle.

### CABLES

Galvanized assembly is good for general purpose use, and stainless steel is ideal for corrosive environments.

Cap.	Lift Range	Finish	Operation Mode	Item No.
<b>Davit Cranes</b>				
1,200 lb	0 in to 540 in	High Gloss	115V AC	48RD46
1,200 lb	0 in to 540 in	High Gloss	12V DC	48RD47
1,200 lb	0 in to 660 in	High Gloss	Manual	49P538

Description	Cap.	Finish	Item No.
<b>Mounting Bases</b>			
Socket Base	1,200 lb	Mil-Spec Zinc Plated	49P539
Pedestal Base	1,200 lb	Mil-Spec Zinc Plated	49P540
Wall Mount Base	1,200 lb	Powder Coated	53DN42

Cable Size	L	Working Load Limit	Material	Item No.
<b>Cables for 49P538</b>				
3/16 in	80 ft	800 lb	Galvanized Steel	49P541
3/16 in	80 ft	800 lb	Stainless Steel	49P542
1/4 in	55 ft	1,200 lb	Galvanized Steel	49P543
1/4 in	55 ft	1,200 lb	Stainless Steel	49P544

Description	Item No.
<b>Cables for 48RD46, 48RD47</b>	
Cable Assembly, Galvanized, 3/16" x 90 ft.	58RH60
Cable Assembly, Stainless Steel, 3/16" x 90 ft.	58RH61
Cable Assembly, Galvanized, 1/4" x 45 ft.	58RH62
Cable Assembly, Stainless Steel, 1/4" x 45 ft.	58RH63



## Counterbalanced Mobile Floor Cranes

Counterbalanced design eliminates the need for front legs. Allows easier maneuverability in tight and hard-to-reach areas. Boom is raised with a manual hydraulic hand pump.

Cap.	Lifting Height Max. (in.)	Lifting Height Min. (in.)	Boom Length (in.)	Item No.
500	90 in	5 in	53 1/2 a 77 1/2	5XP63
1,000	90 in	5 in	53 1/2 a 77 1/2	5XP64
2,000	96 in	15 in	53 1/2 a 77 1/2	5XP65