



Lever and Ratchet Load Binders

Ideal for most trucking and marine industry chain binding applications. Drop-forged steel construction. See Grainger.com for applicable standards.

WARNING: Do not exceed working load limit. Working load limit of an assembly is determined by the component with the lowest working load limit.

Working Load Limit	Trade Size G30/G43	Trade Size G70	Brand	Item No.
Lever Load Binders				
2,600 lb	¼ in to ⅝ in	—	Kinedyne	48PX61
5,400 lb	¾ in	¾ in	Kinedyne	22P610
5,400 lb	¾ in	¾ in	Kinedyne	22P609
5,400 lb	¾ in	¾ in	—	4EB92
5,400 lb	¾ in	¾ in	Kinedyne	22P608
9,200 lb	½ in	¾ in	Kinedyne	22P612
Ratchet Load Binders				
5,400 lb	¾ in	¾ in	Kinedyne	22P607
6,600 lb	¾ in to ¾ in	¾ in to ¾ in	B/A Products Co.	3YDG1
9,200 lb	½ in	¾ in	Kinedyne	22P611
13,000 lb	½ in to ¾ in	—	Kinedyne	48PX60
Accessories				
Lever Binder Lok			Kinedyne	48PX77



Chain Binders and Transport Chains

Binder Chains—Ideal for towing or securing loads to trailers. All have clevis grab hooks, except 1DJV1 has a welded, grab-style hook. Steel construction. Meet National Association of Chain Manufacturers' Standards.

Transport Chains—Gold dichromate color. Meet NACM Standard.

Safety Chains—Tagged with grade and WLL DOT-Approved Grade 70 chain.

Trade Size	L	Grade	Rated Capacity	Brand	Item No.
Binder Chains					
⅝ in	20 ft	70	4,700 lb.	Dayton	1DJU8
¾ in	20 ft	43	5,400 lb.	Dayton	1DJU9
¾ in	20 ft	70	6,600 lb.	Dayton	1DJV1
¾ in	20 ft	70	6,600 lb.	Dayton	1DJV2
Transport Chains with Grab Hook					
⅝ in	16 ft	70	4,700 lb	Kinedyne	22P598
⅝ in	20 ft	70	4,700 lb	Kinedyne	22P599 *
⅝ in	20 ft	70	4,700 lb	Kinedyne	22P601
⅝ in	25 ft	70	4,700 lb	Kinedyne	22P602
¾ in	16 ft	70	6,600 lb	Kinedyne	22P603
¾ in	20 ft	70	6,600 lb	Kinedyne	22P604 *
¾ in	20 ft	70	6,600 lb	Kinedyne	22P605
¾ in	25 ft	70	6,600 lb	Kinedyne	22P606
Safety Chains					
⅝ in	12 ft	70	4,700 lb	B/A Products Co.	3YFW6

* Come packaged as 25 pieces of 20-ft. chain in a barrel.



Flip Ring
5JDU9



Recessed Anchor Ring
3VUJ1

Truck and Trailer Anchors

Provide a safe, secure, and easily accessible anchor point for tie-downs or rope. Mount on the inside of a pickup truck box, bed, or walls of a trailer. Rust-resistant.

Description	Working Load Limit	Ring Dia.	Finish	Material	Item No.	Pkg. Qty.
Surface Mount Anchor	400 lb	¼ in	Zinc Plated	Steel	4HXF1	12
Flip Ring	5,000 lb	¾ in	Natural	Forged Steel	5JDU9	10
Screw Mount Anchor Ring	1,300 lb	2 in	Zinc Plated	Steel	34RY81	1
Recessed Anchor Ring	6,000 lb	1 ½ in	Zinc Plated	Steel	3VUJ1	1