



Antistatic Industrial PVC Strip Doors

Designed to reduce the buildup of static electricity from contact with the material, dissipate static electric discharge, and prevent dust and airborne particles from adhering. Aluminum mounting hardware.

Strip Width	Opening Width	Opening Height	No. of Strips	% Overlap	Item No.
3 ft	7 ft	6	50		36LT49
4 ft	7 ft	8	50		36LT50
5 ft	7 ft	10	50		36LT51
6 ft	7 ft	12	50		36LT52
8 in	3 ft	8 ft	6	50	36LT53
4 ft	8 ft	8	50		36LT54
5 ft	8 ft	10	50		36LT55
6 ft	8 ft	12	50		36LT56
8 ft	8 ft	16	50		36LT57
8 ft	8 ft	12	67		36LT58
8 ft	10 ft	12	67		36LT59
12 in	10 ft	10 ft	15	67	36LT60
10 ft	12 ft	15	67		36LT61
12 ft	12 ft	18	67		36LT62



36LT49

Strip Width	Strip Length	No. of Strips	Item No.
Replacement Strips			
8 in	7 ft 3 in	5	36LT66
	8 ft 3 in	5	36LT67
	8 ft 3 in	5	36LT68
12 in	10 ft 3 in	5	36LT69
	12 ft 3 in	5	36LT70



Sliding Bug Screens

■ Simple under-header installation

Flexible sliding barriers keep out insects, birds, and dust, while letting in sunlight and fresh air; help improve employee comfort and productivity, as well as facility sanitation. The roller-and-track mechanism can be easily slid open or closed by a single individual. Hook-and-loop fasteners and steel bar-reinforced side seams help seal the sides of the screen. All-weather vinyl-coated polyester construction is UV-resistant.



Opening Width	Opening Height	Item No.
8 ft	8 ft	483L35
8 ft	9 ft	483L36
	10 ft	483L37
9 ft	10 ft	483L38
	8 ft	483L39
10 ft	10 ft	483L40
	12 ft	483L41
	10 ft	483L42
12 ft	12 ft	483L43
	14 ft	483L44



Strip Door



Swinging Doors



Walk-In Cooler/Freezer Doors

Designed to act as a secondary barrier for walk-in coolers and freezers, refrigeration doors are made from low-temperature PVC approved for incidental food contact.

Strip Width	Opening Width	Opening Height	Gauge	No. of Strips	Mounting Hardware Material	Item No.
Strip Doors						
6 in	3 ft 4 in	7 ft	0.06	10	Polypropylene	1VKB7
8 in	3 ft 4 in	6 ft 8 in	0.08	7	Polypropylene	1VKB8
8 in	3 ft 4 in	7 ft	0.08	7	Polypropylene	1VKB9
8 in	3 ft 4 in	7 ft	0.08	7	Aluminum	3TB33
Replacement Strips						
8 in	—	7 ft.	0.08	4	—	3TB16
Flexible Swinging Doors						
Door Thickness	Opening Width	Opening Height	Mounting Hardware Material			
3/4 in	2 ft 10 in	6 ft 8 in	Stainless Steel			
3/4 in	3 ft	7 ft	Stainless Steel			
3/4 in	4 ft	7 ft	Stainless Steel			
3/4 in	5 ft	7 ft	Stainless Steel			
3/4 in	5 ft	8 ft	Stainless Steel			



4EE10



Curtain Wall Partitions

Curtains are PVC-coated polyester with an optional clear vision panel. The kits include roller track hardware with universal track supports and hook/loop closures to link multiple curtains. NFPA-701 Compliant.

W	H	Item No.
Solid Blue		
6 ft	8 ft	4EE19
	10 ft	4EE20
	12 ft	4EE21
12 ft	8 ft	4EE22
	10 ft	4EE23
	12 ft	4EE24
24 ft	8 ft	4EE25
	10 ft	4EE26
	12 ft	4EE27
90° Curved Track		
—	—	4EE28



6GJKO



Specialty Flexible PVC Bulk Rolls

Specialty materials help reduce static discharge, block welding flash, or remain flexible at low temperatures.

Strip Width	Strip Thickness	Roll Length	Strip Color	Item No.
Welding				
8 in	0.08 in	300 ft	Amber Weld Tint	6GJJ4
12 in	0.12 in	200 ft	Amber Weld Tint	6GJJ5
8 in	0.08 in	300 ft	Red Weld Tint	6GJK0
12 in	0.12 in	200 ft	Red Weld Tint	6GJK1
Standard				
48 in	0.08 in	30 ft	Clear	6GJH9
	0.08 in	60 ft	Clear	6GJJ0