



Hollow Core
15V470



Solid Core
15V482



Solid Core
Metal-Detectable
30D659



Connector
15V476

Fenner Drives **EAGLE**
POLYURETHANE BELTING & O-RINGS

Eagle Round Belting

- Temp. range: -22° to 150°F
- Sold in 100-ft. lengths

Polyurethane belts can be cut to required length; weld endless or use connectors for hollow-core belts to extend length. Smooth belts are FDA compliant. Solid-core metal-detectable belting is used in food processing and pharmaceutical applications.

Dia.	Min. Pulley Dia.	Mfr. Model	Item No.
Hollow Core			
Clear, Smooth, Shore A 85			
3/16 in	2 in	4934009	15V470
1/4 in	2 1/2 in	4934012	15V471
5/16 in	3 in	4934015	15V472
3/8 in	3 1/2 in	4934018	15V473
1/2 in	4 1/2 in	4934024	15V474
5/8 in	5 1/2 in	4934030	15V475
Yellow, Smooth, Shore A 85			
3/16 in	2 in	4934021	15V465
1/4 in	2 1/2 in	4934022	15V466
5/16 in	3 in	4934023	15V467
3/8 in	3 1/2 in	4934025	15V468
1/2 in	4 1/2 in	4934026	15V469

Dia.	Min. Pulley Dia.	Mfr. Model	Item No.
Solid Core			
Orange, Smooth, Shore A 85			
3/32 in	3/4 in	1032003	15V482
1/8 in	1 3/8 in	1032004	15V483
3/16 in	1 1/2 in	1032006	15V484
1/4 in	2 in	1032008	15V485
5/16 in	2 1/2 in	1032010	15V486
3/8 in	3 in	1032012	15V487
1/2 in	4 in	1032016	15V488
5/8 in	4 1/2 in	1032018	15V489
3/4 in	5 in	1032020	15V490
7/8 in	6 in	1032024	15V491
Clear, Smooth, Shore A 95			
3/32 in	1 in	4907003	15V492
1/8 in	1 1/4 in	4907006	15V493
3/16 in	1 7/8 in	4907009	15V494
1/4 in	2 1/2 in	4907012	15V495
5/16 in	3 1/8 in	4907015	15V496
3/8 in	3 3/4 in	4907018	15V497
1/2 in	5 in	4907024	15V498
5/8 in	5 5/8 in	4907027	15V499
3/4 in	6 1/4 in	4907030	15V501
7/8 in	7 1/2 in	4907033	15V502

Dia.	Min. Pulley Dia.	Mfr. Model	Item No.
Green, Rough, Shore A 89			
2 mm	3/4 in	4905302	15V506
3 mm	1 in	4905303	15V507
4 mm	1 1/8 in	4905304	15V508
5 mm	1 3/4 in	4905305	15V509
6 mm	2 1/8 in	4905306	15V510
7 mm	2 1/2 in	4905307	15V511
8 mm	2 5/8 in	4905308	15V512
10 mm	3 1/2 in	4905310	15V513
12 mm	4 1/4 in	4905312	15V514
15 mm	5 1/4 in	4905315	15V515

Dia.	Min. Pulley Dia.	Mfr. Model	Item No.
Solid Core Reinforced			
Orange, Smooth, Shore A 85			
1/4 in	2 1/2 in	4940058	15V503
5/16 in	3 1/8 in	4940059	15V504
3/8 in	3 3/4 in	4940060	15V505
Solid Core Metal-Detectable			
Blue, Smooth, Shore A 80			
3/16 in	1 5/8 in	4941100	30D659
1/4 in	1 3/4 in	4941101	30D660
5/16 in	2 3/8 in	4941102	30D661
3/8 in	2 5/8 in	4941103	30D662

Dia.	Pkg. Qty.	Mfr. Model	Item No.
Aluminum Round Belt Connectors, For Use with Hollow Core Belts			
3/16 in	25	4935009	15V476
1/4 in	25	L04CON6S	15V477
5/16 in	25	L04CON8S	15V478
3/8 in	20	L04CON10S	15V479
1/2 in	20	L04CON13S	15V480
5/8 in	15	4935030	15V481

Fenner Drives

EAGLE
POLYURETHANE BELTING & O-RINGS

Eagle Twisted O-Rings

- Clear, smooth texture, Shore A 85 hardness
- Sold in packages of 50

Quick-connect polyurethane twisted O-rings are a great fast-fit solution for live roller conveyors. No need to dismantle drive components, providing an easy way to avoid system downtime. Metal hooks are included.




Dia.	Overall Length	Mfr. Model	Item No.
3/16 in	6 in	5050003	19RT86
	10 1/2 in	5050015	19RT98
	10 5/8 in	5050004	19RT94
	11 in	5050012	19RT95
	11 1/2 in	5050911	19RT97
	12 in	5050016	19RT99
	12 1/2 in	5050005	19RT87
	12 3/4 in	5050002	19RT92
	12 7/8 in	5050006	19RT88
	13 in	5050007	19RT89
	13 1/4 in	5050017	19RU01
	13 1/2 in	5050009	19RT90
	13 3/4 in	5050014	19RT96
	14 in	5050008	19RT93
14 1/2 in	5050010	19RT91	



Round Endless Belts

- Temp. Range: -30° to 140°F

Allow minimal stretch and have no splice, making them extra durable and efficient. Made from rubber with nylon reinforcement cords and designed for 1-quarter turn or twisted drives where more than an O-ring is required. Also suitable for serpentine drives, power turn and line shaft conveyors, and commercial sewing machines.



Dia.	Inside Length	Min. Pulley Dia.	Mfr. Model	Item No.
Reinforced Gum Rubber, Black, Shore A 80				
3/8 in	36 in	3 in	88201234	1NKL7
	98 in		88201486	1NKK4
	34 in		88201835	1NKL4
	77 1/4 in		88202008	1NKL9
	166 in		88203491	1NKN4
	176 in		88203492	1NKN5
7/16 in	190 in	5 1/2 in	88203493	1NKN2
	200 in		88203469	1NKL8
	210 in		88203486	1NKL3
	233 in		88203470	1NKK7
	250 in		88203494	1NKK5
	270 in		88203471	1NKK6
	308 in		88203472	1NKK9
	331 in		88203473	1NKL2
	345 in		88203495	1NKL5
	386 in		88203474	1NKL1
	416 in		88203475	1NKL6
	447 in		88203484	1NKN1
465 in	88203476	1NKN3		
564 in	88203477	1NKK8		
660 in	88203478	1NKN6		



Fenner Drives **EAGLE**
POLYURETHANE BELTING & O-RINGS

Eagle Cordless Belt Welding Kit

Freestyle cordless welder is powered by 2 rechargeable batteries to complete up to 30 welds per charge. Features built-in profile clamping dies for both round and V belt profiles. Kit includes cordless welder, flat plate adapters, battery charger, 4 NiMH D batteries, cutting shears, flash cutters, blade release tape, and tool bag.

Description	Mfr. Model	Item No.
Used for Round and V-Belts	5700539	5HYN7

Fenner Drives **EAGLE**
POLYURETHANE BELTING & O-RINGS

Eagle Belt Heating Tool

This belt heating tool can join all Eagle non-reinforced belting and some reinforced polyurethane belting. Device allows you to apply heat to the 2 ends of a length of belting, and then join the belt ends for a completed belt. Tool comes with a holder and 2" blade. 120V.

Description	Item No.
Heat Iron Complete, Tip And Paddle, For Use With Butt Welding Kit	33Z789

