

Industrial Tricycles

- Front cantilever V-brakes
- Durable steel frames

Industrial-quality tricycles are the quick-and-easy way to get around large facilities. Rider-friendly—these 3-wheel bikes are capable of handling various size loads. Easy-to-grab hand

brakes. Wide cruiser seat adjusts for differing heights. Large wire basket on 437V12, 437V13, 437V16, and 437V17.

Basket—60-lb. capacity. Fits 437V15 and 437V19.

Description	Load Capacity	Wheel Dia.	Spokes	Color	Item No.
Tricycles					
Standard Duty Chain	250 lb	24 in	0.08 ga	Blue	437V12
	250 lb	24 in	0.08 ga	Green	437V13
	250 lb	24 in	0.08 ga	Purple	437V16
	250 lb	24 in	0.08 ga	Red	437V17
Medium Duty Chain	350 lb	24 in	0.08 ga	Yellow	437V15
Heavy Duty Chain	500 lb	26 in	0.105 ga	Yellow	437V19
Basket					
Basket, 21 x 15 x 9 in	—	—	—	—	437V14



Trailer-Stabilizing Jacks and Notice Sign

Jacks prevent up-ending semitrailers not connected to tractors, level trailers parked on slopes, and prevent landing gear from sinking into soft surfaces. High-strength steel. Flush-type zerk fitting for relubricating Acme screw. With reflective night-visible collar.

GAS-ACTIVATED JACKS

Gas-operated system automatically raises the stand and operator locks in place.

HYDRAULIC JACK

Lift heavy loads using force created by a hydraulic cylinder. The force is created by the pressure in the cylinder chamber.

RATCHET JACKS

Have 8"-dia. wheels.

4W287—Triangular base has 18" sides. Two-way reversible ratchet with 2"-dia. thread screw allows a 12" adjustment range. 8"-dia. swivel head.

3KR77—Extra-wide 6"W x 24"L lifting beam aids trailer support. Two handles assist positioning

jack under trailer. Two-way reversible ratchet for adjusting height.

2W878—With easily reversible 2-way ratchet, 2½"-dia. thread screw, and 12" adjustment range. 8"-dia. swivel head, 8"-dia. solid rubber wheels.

SPIN TOP JACKS

Manually turned Acme thread screw raises and lowers jack for fast installation and removal.

Lifting Capacity	Static Load Capacity	Adjustment Range	Wheel Dia.	Brand	Item No.
Gas Activated					
Not Rated	100,000 lb	37 in to 48 in	16 in	Ideal Warehouse Innovations, Inc.	458R40
		39¼ in to 52½ in	10 in	Dayton	26W613
Hydraulic					
40,000 lb	100,000 lb	41 in to 47 in	10 in	Dayton	26W618
Ratchet					
40,000 lb	80,000 lb	39 in to 51½ in	10 in	Dayton	26W612
		39 in to 51 in	8 in	Dayton	4W287
		39½ in to 51 in	8 in	Dayton	3KR77
		39 in to 51½ in	10 in	Dayton	26W614
50,000 lb	100,000 lb	44½ in to 57 in	10 in	Dayton	26W615
		39 in to 51 in	8 in	Dayton	2W878
Spin Top					
5,000 lb	50,000 lb	41 in to 57½ in	8 in	Dayton	26W617
		44 in to 51 in	None	Dayton	2W877
		44 in to 51 in	None	Dayton	26W616
40,000 lb	100,000 lb	39 in to 51 in	8 in	Dayton	1F144
Not Rated		38½ in to 49½ in	10 in	Ideal Warehouse Innovations, Inc.	458R41
Notice Sign					
Aluminum, 9½ x 11½ in				Dayton	26W611



26W613



3KR77



2W878



2W877



1F144



26W611

Telescopic Support Braces

Provide extra support for leveling and stabilizing floor beams and joists during construction and repairs. Telescopic style with removable pins lets you properly position the brace for better leveling. End pad includes screw and turning bar for height adjustment. Welded steel construction.

Min. Service Height	Max. Service Height	No. of Sections	Cap. @ Min. Height	Cap. @ Max. Height	Item No.
12 in	16 in	1	9,738	9,738	3CA86
19 in	36 in	2	9,738	8,663	3CA84
54 in	100 in	2	8,438	5,600	3CA85
54 in	150 in	3	11,200	2,588	3CA83

2 Sections
3CA84

Steel Yard Ramps

These ramps are designed to load trailers from ground level. Deep side members prevent run-off for forklift use. The usable width of 78" allows transit of most lift trucks and electric vehicles.

Load Capacity	Overall Length	Overall Width	Lowered Height	Raised Height	Brand	Item No.
16,000 lb	30 ft	84 in	40 in	72 in	Bluff	9DL31
	36 ft Including a 6 ft Level Off	84 in	33 in	67 in	Bluff	8AKJ2
20,000 lb	30 ft	84 in	40 in	72 in	Bluff	8AKJ3
	36 ft Including a 6 ft Level Off	84 in	33 in	67 in	Bluff	32KG02
30,000 lb	30 ft	84 in	40 in	72 in	Bluff	32KG03
	36 ft Including a 6 ft Level Off	84 in	33 in	67 in	Bluff	32KG05
	36 ft Including a 6 ft Level Off	84 in	33 in	67 in	Bluff	20G280



20G280