



Dockplates, Dockboards, and Container Ramps

Aluminum Dockplates—Nonskid tread plate. Zinc-plated handle or hand-holds on each side. Locking legs secure dockplate when in use.

Aluminum Fork Truck Dockboards with

Aluminum Curbs—Handle higher load capacities than dockplates. Feature safety curbs. Positive traction treadplate with beveled entrance and exit lip. Legs allow easy fork truck positioning and secure dockboard when in use, for OSHA compliance. When using 3-wheeled fork truck, order dockboard with capacity at least four times the lifting capacity of the fork truck.

			Service		
Load	Overall	Overall	Height		Item
Capacity	Length	Width	Range	Brand	No.
Aluminur	n Dockpla	ites			
1,400 lb	48 in	30 in	7 in	_	4LGV4
1,800 lb	60 in	48 in	9 in	_	4LGU7
1,900 lb	48 in	36 in	7 in	_	4LGV6
2,500 lb	36 in	36 in	5 in	_	4LGV3
2,600 lb	48 in	48 in	7 in	_	4LGV9
2,900 lb	48 in	60 in	7 in	_	4LGU8
3,000 lb	30 in	36 in	4 in	_	4LGV5
3,300 lb	30 in	42 in	4 in	_	4LGV7
3,500 lb	36 in	48 in	5 in		4LGU6
3,600 lb	24 in	36 in	3 in	_	4LGV2
3,800 lb	48 in	48 in	7 in	_	4LGU9
4,100 lb	36 in	60 in	5 in		4LGW1
4,000 lb	24 in	36 in	1 in	Bluff	8Y787
5,200 lb	24 in	48 in	3 in	_	4LGV8
5,300 lb	36 in	48 in	5 in		4LGW2
6,600 lb	36 in	60 in	5 in		4LGV1
9,500 lb	30 in	72 in	4 in		4LGW3
11,350 lb	30 in	72 in	2 in	Bluff	9HPE2
Aluminum Fork Truck Dockboards with Aluminum Curbs					rbs
5,000 lb	30 in	60 in	3 in to 4 in	_	6XW86
8,000 lb	48 in	72 in	5½ in to 7 in	_	4W598
15,000 lb	59 ¾ in	60 in	7 in to 10 in	_	6XW90

Aluminum Fork Truck Dockboards with Steel Curbs—Structural steel safety curbs are bolted to each side of dockboard. When using 3-wheeled fork truck, order dockboard with capacity at least four times the lifting capacity of the fork truck.

Aluminum Hand Truck Dockboards—Use with 2-wheel hand trucks only. Diamond tread surface and beveled edges. Bolted locking legs for OSHA compliance.

Container Ramps—For fast loading and unloading at ground level. Eliminate the need for queuing.

Load Capacity		Overall Width	Service Height Range	Brand	Item No.
Aluminur	n Fork Tru	ick Dockb	oards with S	teel Curbs	
10,000 lb	72 in	60 in	8½ in to 11 in	Bluff	9MHD0
15,000 lb	60 in	60 in	7 in to 9 in	Bluff	9MHD1
	36 in	60 in	5 in	_	6XX29
20,000 lb	36 in	72 in	5 in		6XX31
20,000 10	48 in	60 in	7 in	_	6XX30
	48 in	72 in	7 in	_	6XX32
Aluminun		uck Dockl			
800 lb	59 % in	37 ¼ in	10 in	_	6XW74
Steel Cor	ıtainer Ra	amps			
	60 in	60 in	7 in to 9 in	Bluff	20G252
15,000 lb	72 in	60 in	8½ in to 11 in	Bluff	20G253
	72 in	72 in	8½ in to 11 in	Bluff	20G258
20,000 lb	60 in	72 in	7 in to 9 in	Bluff	20G262
Aluminur	n, Epoxy (Grit Coat (Container Ra	mps	
	36 in	36 in	1 in to 6 in	Heavy Duty Ramps	60UG07
8,000 lb	48 in	36 in	1 in to 8 in	Heavy Duty Ramps	60UG08
	48 in	45 in	1 in to 8 in	Heavy Duty	60UG09



Polyethylene Dockplates—Designed for lightduty applications. Integrated guardrails and handles. Hardware included. Meet 0SHA 1910.30(a).

Steel Fork Truck Dockboards with Steel

Curbs—Lever lift mechanism raises front edge of dockboard off the ground to allow for one-person operation. Lever automatically falls to rest position as dockboard is lifted. When using 3-wheeled fork truck, select capacity +20% greater than the lifting capacity of the fork truck.

Load Capacity	Overall Length	Overall Width	Service Height Range	Brand	Item No.
12,000 lb	48 in	63 in	1 in to 8 in	Heavy Duty Ramps	60UG10
	60 in	63 in	1 in to 10 in	Heavy Duty Ramps	60UG11
Polyethy	lene Dock	plates		· ·	
750 lb	36 in	35 in	4 in		5AB23
	36 in	48 in	4 in		6PEC2
Steel For			s with Steel	Curbs	
	36 in	72 in	5 in	_	6XX34
10,000 lb	48 in	60 in	5 in to 7 in	Bluff	20G233
10,000 10	48 in	72 in	7 in		4W600
	60 in	60 in	7 in to 9 in	Bluff	20G234
	36 in	72 in	5 in		4W601
	48 in	60 in	5 in to 7 in	Bluff	9GEN7
	48 in	72 in	5 in to 7 in	Bluff	8CEG6
	48 in	72 in	7 in		6XX37
15,000 lb	54 in	72 in	81/2 in		4W602
	60 in	60 in	7 in to 9 in	Bluff	9HY65
	60 in	72 in	7 in to 9 in	Bluff	20G243
	72 in	72 in	8½ in to 11 in	Bluff	8AKH9
	48 in	72 in	5 in to 7 in	Bluff	20G248
20.000 lb	48 in	84 in	5 in to 7 in	Bluff	20G272
20,000 ID	72 in	84 in	8½ in to 11 in	Bluff	20G274



Load Capacity	Overall Width	Overall Length	Service Height Range	Item No.		
Adjustable I	Ramps - Wi	thout Side				
800 lb	32 in	1 ft	1 in to 2 in	32KK54		
800 lb	32 in	2 ft	2 in to 4 in	32KK56		
800 lb	32 in	3 ft	31/2 in to 6 in	32KK58		
800 lb	32 in	4 ft	4 in to 6 in	32KK60		
800 lb	36 in	1 ft	1 in to 2 in	32KK55		
800 lb	36 in	2 ft	2 in to 4 in	32KK57		
800 lb	36 in	3 ft	3½ in to 6 in	32KK59		
800 lb	36 in	4 ft	4 in to 6 in	32KK61		
Multi Fold R	amps - 1 1/	in Side R	ail			
800 lb	30 in	5 ft	5 in to 10 in	32KK41		

Load Capacity	Overall Width	Overall Service Length Height Range		Item No.
800 lb	30 in	6 ft	6 in to 12 in	32KK42
800 lb	30 in	7 ft	7 in to 14 in	32KK43
800 lb	30 in	8 ft	8 in to 16 in	32KK44
Ramps with	Handrails ·		Rail	
850 lb	36 in	4 ft	4 in to 8 in	32KK68
850 lb	36 in	5 ft	5 in to 10 in	32KK69
850 lb	36 in	6 ft	6 in to 12 in	32KK70
850 lb	36 in	7 ft	7 in to 14 in	32KK71
850 lb	36 in	8 ft	8 in to 16 in	32KK72
Single Fold	Ramps - 1	½ in Side l	Rail	
800 lb	30 in	2 ft	2 in to 4 in	32KK34
800 lb	30 in	3 ft	3 in to 6 in	32KK35
800 lb	30 in	4 ft	4 in to 8 in	32KK36
800 lb	30 in	5 ft	5 in to 10 in	32KK37
Solid Ramps		ide Rail		
800 lb	30 in	3 ft	3 in to 6 in	32KK62
800 lb	30 in	4 ft	4 in to 8 in	32KK64
800 lb	30 in	5 ft	5 in to 10 in	32KK66
800 lb	36 in	3 ft	3 in to 6 in	32KK63
800 lb	36 in	4 ft	4 in to 8 in	32KK65
800 lb	36 in	5 ft	5 in to 10 in	32KK67
Solid Ramps				
1,000 lb	40 in	16 ft	6 to 62 in	1VKD8
1,200 lb	38 in	14 ft	6 to 54 in	1VKD6
1,400 lb	28 in	12 ft	6 to 46 in	1VKD5
1,400 lb	38 in	12 ft	6 to 48 in	4YFP2
1,400 lb	40 in	12 ft	6 to 46 in	1VKD7
1,500 lb	38 in	10 ft	6 to 38 in	1VKD4
1,700 lb	28 in	8 ft	6 to 29 in	1VKD2

Alum	inum
Walk	Ramps

Nonskid surfaces

1VKC9 and 1VKD1 to 1VKD8 have $3\%^{\rm H}$ Curb. 1FC73 to 1FC75 have $4\%^{\rm H}$ side rails to keep load safely on ramp. Two 36"L safety chains hold ramp in place.

Note: Ramps are designed for use with hand trucks. Do not use with powered equipment or pallet jacks.

Load Capacity	Overall Width	Overall Length	Service Height Range	Item No.
1,700 lb	38 in	8 ft	6 to 29 in	1VKD3
2,000 lb	28 in	6 ft	6 to 21 in	1VKC9
2,000 lb	38 in	6 ft	6 to 21 in	1VKD1
Solid Ramps				
2,200 lb	39 ½ in	10 ft	2 to 37 in	1FC75
2,500 lb	29 in	8 ft	2 to 31 in	1FC74
2,800 lb	29 in	69 in	2 to 21 in	1FC73
Threshold R		hout Side		
600 lb	32 in	8 in	½ in to 1¼ in	32KK47
600 lb	32 in	10 in	1/2 in to 11/4 in	32KK48
600 lb	32 in	12 in	1 in to 2 in	32KK49
600 lb	32 in	16 in	11/4 in to 21/2 in	32KK50
600 lb	32 in	24 in	2 in to 4 in	32KK52
600 lb	36 in	16 in	11/4 in to 21/2 in	32KK51
600 lb	36 in	24 in	2 in to 4 in	32KK53



Loading Ramps

For loading machines and small vehicles. Ramps have rubber-tipped fingers that provide traction and prevent scratching. Safety straps included.

		Load			item
	Description	Capacity	L	W	No.
Ī	1-Piece Steel	1000 lb / Pair	72 in	9 in	1DLU8
	1-Piece Steel	1000 lb / Pair	96 in	9 in	1DLU9
	Centerfold Steel Mesh Ramp	1,600 lb	80 in	11 in	52JU43
Ī	Straight Aluminum Ramp	1,400 lb	72 in	15 in	52JU42
	Folding Aluminum	1,500 lb	78 in	50 in	1TFZ3