

1-800-GRAINGER (472-4643)



## Antistatic Industrial PVC Strip Doors

Designed to reduce the buildup of static electricity from contact with the material, dissipate static electric discharge, and prevent dust and airborne particles from adhering. Aluminum mounting hardware.

Strip Width	Opening Width	Opening Height	No. of Strips	% Overlap	Item No.
8 in	3 ft	7 ft	6	50	36LT49
	4 ft	7 ft	8	50	36LT50
	5 ft	7 ft	10	50	36LT51
	6 ft	7 ft	12	50	36LT52
	3 ft	8 ft	6	50	36LT53
	4 ft	8 ft	8	50	36LT54
12 in	5 ft	8 ft	10	50	36LT55
	6 ft	8 ft	12	50	36LT56
	8 ft	8 ft	16	50	36LT57
	8 ft	8 ft	12	67	36LT58
	8 ft	10 ft	12	67	36LT59
	10 ft	10 ft	15	67	36LT60
	10 ft	12 ft	15	67	36LT61
	12 ft	12 ft	18	67	36LT62




36LT49

Strip Width	Strip Length	No. of Strips	Item No.
<b>Replacement Strips</b>			
8 in	7 ft 3 in	5	36LT66
	8 ft 3 in	5	36LT67
	8 ft 3 in	5	36LT68
12 in	10 ft 3 in	5	36LT69
	12 ft 3 in	5	36LT70



## Specialty Flexible PVC Bulk Rolls

Specialty materials help reduce static discharge, block welding flash, or remain flexible at low temperatures.



6GJKO

Strip Width	Strip Thickness	Roll Length	Strip Color	Item No.
<b>Welding</b>				
8 in	0.08 in	300 ft	Amber Weld Tint	6GJJ4
12 in	0.12 in	200 ft	Amber Weld Tint	6GJJ5
8 in	0.08 in	300 ft	Red Weld Tint	6GJKO
12 in	0.12 in	200 ft	Red Weld Tint	6GJK1
<b>Standard</b>				
48 in	0.08 in	30 ft	Clear	6GJH9
	0.08 in	60 ft	Clear	6GJJ0



## Walk-In Cooler/Freezer Doors

Designed to act as a secondary barrier for walk-in coolers and freezers, refrigeration doors are made from low-temperature PVC approved for incidental food contact.



Strip Door

Strip Width	Opening Width	Opening Height	Gauge	No. of Strips	Mounting Hardware Material	Item No.
<b>Strip Doors</b>						
6 in	3 ft 4 in	7 ft	0.06	10	Polypropylene	1VKB7
8 in	3 ft 4 in	6 ft 8 in	0.08	7	Polypropylene	1VKB8
8 in	3 ft 4 in	7 ft	0.08	7	Polypropylene	1VKB9
8 in	3 ft 4 in	7 ft	0.08	7	Aluminum	3TB33
<b>Replacement Strips</b>						
8 in	—	7 ft.	0.08	4	—	3TB16
<b>Flexible Swinging Doors</b>						
Door Thickness	Opening Width	Opening Height	Mounting Hardware Material	Item No.		
5/8 in	2 ft 10 in	6 ft 8 in	Stainless Steel	4EY32		
5/8 in	3 ft	7 ft	Stainless Steel	4EY33		
5/8 in	4 ft	7 ft	Stainless Steel	4EY34		
5/8 in	5 ft	7 ft	Stainless Steel	4EY35		
5/8 in	5 ft	8 ft	Stainless Steel	4EY36		



Swinging Doors

## Curtain Wall Partitions

Curtains are PVC-coated polyester with an optional clear vision panel. The kits include roller track hardware with universal track supports and hook/loop closures to link multiple curtains. NFPA-701 Compliant.



4EE10

W	H	Item No.
<b>Solid Blue with Clear Vision Panel</b>		
6 ft	8 ft	4EE10
	10 ft	4EE11
	12 ft	4EE12
12 ft	8 ft	4EE13
	10 ft	4EE14
	12 ft	4EE15
24 ft	8 ft	4EE16
	10 ft	4EE17
	12 ft	4EE18
<b>Solid Blue</b>		
6 ft	8 ft	4EE19
	10 ft	4EE20
	12 ft	4EE21
12 ft	8 ft	4EE22
	10 ft	4EE23
	12 ft	4EE24
24 ft	8 ft	4EE25
	10 ft	4EE26
	12 ft	4EE27
<b>90° Curved Track</b>		
—	—	4EE28



## Flexible PVC Swinging Doors

Opening Width	Opening Height	Item No.
<b>Industrial Flexible PVC Swinging Door</b>		
8 ft	8 ft	4EY37
	10 ft	4EY38
	9 ft	4EY39
	10 ft	4EY40
<b>Industrial Swinging Door with Impact Panel</b>		
8 ft	8 ft	4EY41
	10 ft	4EY42
	9 ft	4EY43
	10 ft	4EY44



4EY41



## Sliding Bug Screens

Simple under-header installation

Flexible sliding barriers keep out insects, birds, and dust, while letting in sunlight and fresh air; help improve employee comfort and productivity, as well as facility sanitation. The roller-and-track mechanism can be easily slid open or closed by a single individual. Hook-and-loop fasteners and steel bar-reinforced side seams help seal the sides of the screen. All-weather vinyl-coated polyester construction is UV-resistant.

Opening Width	Opening Height	Item No.
8 ft	8 ft	483L35
	9 ft	483L36
	10 ft	483L37
9 ft	10 ft	483L38
	8 ft	483L39
10 ft	10 ft	483L40
	12 ft	483L41
	10 ft	483L42
12 ft	12 ft	483L43
	14 ft	483L44

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**