



General Purpose Pallet Jacks

Manual jacks with fixed-width forks are for use in warehouses, loading docks, manufacturing, and other industrial settings.

Fast lift can raise empty stacks of pallets and other light loads faster than other types of manual pallet jacks. Loads that are heavier than the pallet jacks' maximum fast-lift weight capacity are raised at a slower rate.

Four-way forks can fit into standard openings on the front and back of the pallets as well as low-entry cutouts on the pallets' side stringers, allowing them to enter pallets from all four sides.

| Load Capacity | Fork LxW | Width Across Forks | Width Between Forks | Overall LxWxH | Brand | Item No. |
|--------------------------------|------------------|--------------------|---------------------|-------------------------------|--------|----------|
| Standard Forks | | | | | | |
| 3,800 lb | 48 in x 6 in | 27 in | 15 in | 63 in x 27 in x 48 in | — | 12U124 |
| 4,400 lb | 48 in x 6 3/8 in | 27 in | 14 3/8 in | 63 1/2 in x 27 in x 48 in | Dayton | 2ZE59 |
| 5,000 lb | 48 in x 7 in | 27 in | 13 in | 63 1/2 in x 27 in x 48 in | Dayton | 24L322 |
| | 48 in x 6 1/4 in | 27 in | 14 1/2 in | 63 in x 27 in x 48 in | — | 12U125 |
| 5,500 lb | 36 in x 6 3/8 in | 27 in | 14 3/8 in | 50 in x 27 in x 48 in | Dayton | 2TUR7 |
| | 42 in x 6 3/8 in | 27 in | 14 3/8 in | 56 1/2 in x 27 in x 48 in | Dayton | 2TUR5 |
| | 48 in x 6 1/4 in | 27 in | 14 3/8 in | 63 1/2 in x 27 in x 48 in | Dayton | 490207 |
| | 48 in x 6 1/4 in | 27 in | 14 1/2 in | 63 1/2 in x 27 in x 48 in | Dayton | 12U123 * |
| 6,000 lb | 48 in x 6 in | 27 in | 14 3/8 in | 63 in x 27 in x 48 in | Dayton | 493X18 |
| 8,000 lb | 48 in x 6 in | 27 in | 14 3/8 in | 63 in x 27 in x 48 in | Dayton | 493X17 |
| Standard Fork Fast Lift | | | | | | |
| 5,500 lb | 48 in x 6 in | 27 in | 15 in | 63 in x 27 in x 48 in | — | 445K83 |
| | 48 in x 6 1/4 in | 27 in | 14 3/8 in | 63 1/2 in x 27 in x 48 in | Dayton | 490206 |
| Long Forks | | | | | | |
| 3,300 lb | 98 in x 6 in | 27 in | 15 in | 114 in x 27 in x 48 in | — | 445K85 |
| 4,400 lb | 70 in x 6 1/4 in | 27 in | 14 1/2 in | 87 1/4 in x 27 in x 48 3/8 in | Dayton | 30LU68 |
| | 78 in x 6 in | 27 in | 15 in | 93 in x 27 in x 49 in | — | 445K84 |
| 4-Way Forks | | | | | | |
| 4,400 lb | 48 in x 7 in | 33 in | 19 in | 63 1/8 in x 33.5 in x 48 in | Dayton | 30LU67 |
| Narrow Forks | | | | | | |
| 4,400 lb | 48 in x 6 3/8 in | 20 1/2 in | 7 1/8 in | 63 1/2 in x 20 1/2 in x 48 in | Dayton | 2ZE63 |
| | 36 in x 6 3/8 in | 20 1/2 in | 7 1/8 in | 50 in x 20 1/2 in x 48 in | Dayton | 2TUR8 |
| | 42 in x 6 3/8 in | 20 1/2 in | 7 1/8 in | 56 1/2 in x 20 1/2 in x 48 in | Dayton | 2TUR6 |
| 5,500 lb | 48 in x 6 3/8 in | 20 1/2 in | 7 1/8 in | 61 1/8 in x 20 1/2 in x 48 in | Dayton | 2ZE58 |

* Includes hand brake.



Dayton

Corrosion-Resistant Pallet Jacks

2ZE62 is constructed of stainless steel and is suited for food processing, clean-rooms, and other applications requiring washdown.

2TUR3, 24L321, and 2TUR4 have galvanized steel frames for use in cold storage environments requiring cleanliness.

| Load Capacity | Fork LxW | Width Across Forks | Width Between Forks | Overall LxWxH | Frame Material | Item No. |
|-----------------|------------------|--------------------|---------------------|---------------------------|-----------------|----------|
| Standard | | | | | | |
| 4,400 lb | 48 in x 6 3/8 in | 27 in | 14 3/8 in | 62 in x 27 in x 48 in | Stainless Steel | 2ZE62 |
| 5,500 lb | 48 in x 6 3/8 in | 27 in | 14 3/8 in | 62 in x 27 in x 48 in | Steel | 2TUR3 |
| | 48 in x 6 1/4 in | 27 in | 14 1/2 in | 64 in x 27 in x 48 in | Steel | 24L321 |
| Narrow | | | | | | |
| 5,500 lb | 48 in x 6 3/8 in | 20 1/2 in | 7 1/8 in | 62 in x 20 1/2 in x 48 in | Steel | 2TUR4 |

Dayton

Weigh-&-Go Manual Pallet Jack

Features built-in scale for weighing loads that are placed on the forks. Cushion grip with a 3-position lever and a flow valve for controlled lowering. Scale operates on (6) AA batteries.



| Load Capacity | Fork LxW | Width Across Forks | Width Between Forks | Overall LxWxH | Item No. |
|---------------|--------------|--------------------|---------------------|-------------------------------|----------|
| 4,400 lb | 48 in x 7 in | 27 3/4 in | 13 1/4 in | 66 in x 27 3/4 in x 47 1/4 in | 54YG30 |



Bishamon

Pallet Jack Accessories

Wheel stops prevent pallet jacks from moving as they are being transported or stored. Help prevent damage to doors, walls, and other surfaces. 1XFD7 has a magnetic back for securing to pallet truck for storage.

Storage caddy attaches to pallet jacks and has molded compartments, pockets, and holders for storing beverages, tools, pens, pencils, and clipboards. Large rear compartment can serve as a wastebasket.

Table top converts compatible powered-lift/manual-push high-lift pallet jacks into mobile lift tables. The work surface attachments rest on top of the pallet jacks' forks to provide a solid surface for work tasks.

| Item | Material | Overall Length | Overall Width | Overall Height | Brand | Item No. |
|---------------|----------|----------------|---------------|----------------|----------|----------|
| Wheel Stop | Urethane | 5 3/4 in | 4 in | 2 1/4 in | — | 1XFD7 |
| | Rubber | 13 3/4 in | 12 in | 1 3/4 in | — | 33N455 |
| Storage Caddy | Plastic | 8 1/8 in | 16 1/4 in | 19 in | — | 2YA32 |
| Table Top | — | 43 7/8 in | 27 1/2 in | — | Bishamon | 9P468 |