



## Dayton

## **High-Lift Pallet Jacks**

## Steel frame

Manual jacks have a foot pedal or handle that operators pump to activate the hydraulic pump and lift the forks.

Powered-lift/manual-push iacks can lift loads faster with less physical effort. An electric motor activates a hydraulic pump to lift and lower the forks and keep them positioned at any height within their travel range. Motor is powered by a rechargeable battery and controlled with a push button. Jacks must be pushed or pulled by hand.

Load Capacity	Width Across Forks	Width Handle Between Forks Type		Fork Style	ltem No.					
Manual Hig	Manual High-Lift Pallet Jacks									
Hand Pump	Lift Control									
2.200 lb	21 1/2 in	9 in	Tiller	Narrow	2PLH9					
2,200 ID	27 in	14 ½ in	Tiller	Narrow Standard Narrow Standard d Standard ed Narrow Narrow	2PLH7					
2.000 lb	20 1/2 in	8 in	Tiller	Narrow	11K277					
3,000 lb	27 in	14 ½ in	Tiller	Standard	11K278					
Foot Pump	Lift Control									
1,100 lb	27 in	14 in	Raised	Standard	11K273					
2.200 lb	20 1/2 in	8 in	Dual Tiller/Raised	Narrow	11K275					
2,200 ID	27 in	14 in	Dual Tiller/Raised	Standard	11K276					
Powered-Lit	ft/Manual-Push	<b>High-Lift Pallet</b>	Jacks							
Hand Pump	Lift Control	-								
3.000 lb	20 1/2 in	8 in	Tiller	Narrow	11K280					
3,000 10	27 in	14 ½ in	Tiller	Standard	11K281					





## **Container Tilters**

Raise and tilt bulk bins, totes, gaylords, crates, and containers on skids or pallets to allow operators to easily access the contents. Forks have a 90-degree range of motion and can position loads at any angle within that range.

Manual tilter requires operators to pump the handle to activate the hydraulic pump and lift and tilt the forks.

Powered-lift/manual-push tilters can raise and tilt loads faster with less physical effort. Motor is powered by a rechargeable battery and controlled with a push button. Tilters must be pushed or pulled by hand.

Load Capacity	Width Across Forks	Width Between Forks	Handle Type	Fork Style	Brand	ltem No.		
Manual Container Tilters								
Hand Pump	Lift Contr	ol						
2,200 lb	22 in	9 ½ in	Tiller	Standard	Dayton	33W285		
Powered-Lift/Manual-Push Container Tilters								
Push Butto	n Lift Cont	rol						
2,000 lb	24 ½ in	11 ½ in	Raised	Standard	Southworth	6WU48		



SOUTHWORTH

Built-in fork pockets make relocating pallets easy. Low-friction, bearing-supported turntable top is easily rotated, with a center pivot and cross bar.

Compression Spring-No need for manual adjustments or tools.

Pneumatic—Pressure-adjustable air bag automatically positions load with 75 psi of shop air. 38TA15 includes vinyl bellows. 4FE90 is powered with a foot valve.

Hydraulic—Work on standard 115V power. 2MNX3 is a roll-on unit for use with hand pallet trucks.

Lift Mechanism	Lift Mobility	Load Capacity	Raised Height	Lowered Height	Platform Size	Brand	ltem No.
<b>Corrosion-Resistant</b>	Manual Pallet	Positioners	5				
Compression Spring	Automatic Lift	4,500 lb	27 ¾ in	9 in	43% in Dia	Southworth	2RDN8
<b>Manual Pallet Posit</b>	ioners						
Compression Spring	Automatic Lift	4,400 lb	27 ¾ in	9 ½ in	43% in Dia	Dayton	45NC12
	Automatic Lift	4,500 lb	27 ¾ in	9 ½ in	43% in Dia	Southworth	38TA16
	Automatic Lift		28 in	9 ½ in	43% in Dia	Southworth	4ZC16
	Automatic Lift	4,000 lb	30 ½ in	10 ½ in	43 in Dia	Bishamon	10C448
Pneumatic	Automatic Lift	4,500 lb	27 ¾ in	9 ½ in	43% in Dia	Southworth	4ZC17
	Automatic Lift		27 ¾ in	9 ½ in	43% in Dia	Southworth	38TA15
<b>Powered Pallet Lift</b>	ers						
Hydraulic	Automatic Lift	2,000 lb	32 11/16 in	8 11/16 in	43% in Dia	Southworth	36Y006
	Automatic Lift	4,000 lb	32 11/16 in	8 11/16 in	43% in Dia	Southworth	36Y007
Pneumatic	Electric Lift	2,000 lb	33 7/16 in	9 7/16 in	43% in Dia	Southworth	4FE90
<b>Roll-On Powered Pa</b>	llet Lifter						
Hydraulic	Electric Lift	2 500 lb	30 in	1 3/4 in	4016 in Dia	Richamon	2MNX3

1128 GRAINGER

Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)