



Manual Stackers

Adjustable and Fixed Fork units have a foot pump, and Fixed Invertible Fork units have a hand crank, that operators use to activate the stackers' lifting mechanism. Suitable for intermittent use and applications where loads will be moved and lifted over short distances.



Load Capacity	Fork Size		Lifting Height Range	Overall Dim.			Brand	Item No.
	L	W		L	W	H		
Straddle Stackers								
Adjustable Forks								
1,000 lb	30 in	3 in	1 in to 4 ft 8 in	48 in	32 ½ in	75 in	Wesco	8EEK2
	30 in	3 in	1 in to 4 ft 8 in	47 in	32 in	72 in	Dayton	2MPT8
	30 in	3 in	1 in to 5 ft 4 in	47 in	32 in	80 in	Dayton	2MPT9
	30 in	3 in	1 in to 6 ft 4 in	47 in	32 in	92 in	Dayton	2MPU1
2,000 lb	36 in	4 in	2 ¾ in to 5 ft 3 in	56 in	54 in	79 ½ in	Dayton	4VME8
	36 in	4 in	2 ¾ in to 8 ft 2 in	56 in	54 in	69 ¾ in	Dayton	4VME9
	36 in	4 in	2 ¾ in to 9 ft 10 in	56 in	54 in	79 ½ in	Dayton	4VMF1
Fixed Invertible Forks								
350 lb	22 ½ in	3 ½ in	2 in to 11 ft 8 in	43 in	43 ½ in	78 ½ in	Genie	4YZ81
	22 ½ in	3 ½ in	3 ½ in to 13 ft 9 in	43 in	43 ½ in	91 in	Genie	4YZ82
400 lb	22 ½ in	3 ½ in	3 ½ in to 10 ft 5 in	43 in	43 ½ in	67 ½ in	Genie	4YZ86
500 lb	22 ½ in	3 ½ in	3 ½ in to 5 ft 11 in	43 in	43 ½ in	67 ½ in	Genie	4YZ84
Fork-Over Stackers								
Adjustable Forks								
750 lb	18 in	3 in	½ in to 4 ft 6 in	30 in	21 ¼ in	60 ½ in	Dayton	2MPU9
	18 in	3 in	5 ¾ in to 4 ft 6 in	32 in	24 in	60 ½ in	Wesco	445K89
Fixed Forks								
2,000 lb	43 in	6 ¼ in	3 ¼ in to 8 ft 2 in	63 in	28 ½ in	72 in	Dayton	4VME2
	43 in	6 ¼ in	3 ¼ in to 9 ft 10 in	63 in	28 ½ in	82 in	Dayton	4VME3
3,000 lb	43 in	6 ¼ in	3 ¼ in to 5 ft 3 in	63 in	28 ½ in	80 in	Dayton	4VME1
Fixed Invertible Forks								
400 lb	22 ½ in	3 ½ in	3 ½ in to 10 ft 5 in	34 ¾ in	27 in	67 ½ in	Genie	4YZ85
500 lb	22 ½ in	3 in	3 ½ in to 5 ft 11 in	34 ¾ in	27 in	67 ½ in	Genie	4YZ83
Counterbalanced Stackers								
Fixed Invertible Forks								
350 lb	22 ½ in	3 in	3 ½ in to 11 ft 8 in	28 ½ in	43 ½ in	78 ½ in	Genie	18F634
400 lb	22 ½ in	3 in	3 ½ in to 10 ft 5 in	28 ½ in	43 ½ in	67 ½ in	Genie	18F633
500 lb	22 ½ in	3 in	3 ½ in to 5 ft 11 in	28 ½ in	43 ½ in	67 ½ in	Genie	18F632



Manual Platform Lifts

Suitable for intermittent use and applications where loads will be moved and lifted over short distances. Compact footprint can maneuver in tight spaces such as aisles, loading docks, and store rooms. Can also be used as adjustable-height work tables and for feeding materials into machines.

Manual platform lift trucks have the outrigger legs positioned directly underneath the platform.

Manual platform lift trucks/stackers have a removable platform and adjustable-width forks. The platform is used for moving and raising loads that are not stored on pallets or skids, and the forks are used for moving and raising loads that are stored on pallets and skids.

Manual hand-truck-style platform lifts have two large rear wheels and are tilted back and rolled to move loads for short distances. The nose of the platform sits on the ground when the trucks are upright, for easy loading of items onto the platform.

Portable manual platform lift trucks have a handle and additional set of wheels mounted to the top of the frame that allow them to be tilted back and loaded into and out of vehicles when empty. The outrigger legs are positioned directly underneath the platform.

Load Capacity	Platform Dim.		Lifting Height Range	Overall Dim.			Brand	Item No.
	L	W		L	W	H		
Manual Platform Lift Trucks								
Steel Fixed Base with Hand Winch Chain/Cable Lift								
750 lb	22 in	22 in	5 ¾ in to 54 in	32 in	22 in	60 ½ in	—	8A125
	30 in	22 in	5 ¾ in to 54 in	32 in	22 in	60 ½ in	Wesco	8DTY9
Steel Fixed Base with Foot Pump Hydraulic Lift								
750 lb	16 in	20 in	5 ¾ in to 40 in	32 in	22 ½ in	48 ½ in	—	8Y719
	22 in	22 in	5 ¾ in to 54 in	32 in	22 ½ in	60 ½ in	Dayton	2MPU7
	22 in	30 in	5 ¾ in to 54 in	32 in	30 in	60 ½ in	Dayton	2MPU8
	22 in	30 in	5 ¾ in to 54 in	32 in	30 in	60 ½ in	—	8A080
880 lb	25 ½ in	21 ½ in	8 in to 33 ½ in	40 in	23 ⅜ in	38 ⅜ in	Dayton	4ECW8
	25 ½ in	21 ½ in	8 in to 47 in	40 in	23 ⅜ in	52 ⅜ in	Dayton	4ECW9
	25 ½ in	21 ½ in	8 in to 59 in	40 in	23 ⅜ in	64 ⅜ in	Dayton	4ECX1
1,000 lb	16 in	24 in	5 ¾ in to 60 in	40 in	25 ½ in	75 in	Wesco	9GNA0
	24 in	24 in	5 ¾ in to 60 in	36 in	25 ½ in	72 in	Dayton	2MPT2
	24 in	24 in	5 ¾ in to 68 in	40 in	25 ½ in	80 in	Dayton	2MPT3
	24 in	25 ½ in	5 ¾ in to 80 in	36 in	25 ½ in	92 in	Dayton	2MPT4
	30 in	32 in	5 ¾ in to 60 in	44 in	32 in	72 in	Dayton	2MPT5
	30 in	32 in	5 ¾ in to 68 in	44 in	32 in	80 in	Dayton	2MPT6
	30 in	32 in	5 ¾ in to 80 in	44 in	32 in	92 in	Dayton	2MPT7
	30 in	24 in	5 ¾ in to 80 in	40 in	25 ½ in	94 in	Wesco	8EAC6

Load Capacity	Platform Dim.		Lifting	Overall Dim.				Item No.
	L	W	Height Range	L	W	H	Brand	
2,000 lb	30 in	32 in	6 in to 63 in	54 in	34 in	79 1/2 in	Dayton	4VME4
	30 in	32 in	6 in to 98 in	54 in	34 in	120 in	Dayton	4VME6
	30 in	32 in	6 in to 118 in	54 in	34 in	84 in	Dayton	4VME7
3,000 lb	30 in	32 in	6 in to 63 in	54 in	34 in	81 1/2 in	Dayton	4VME5
Stainless Steel Adjustable Base with Foot Pump Hydraulic Lift								
750 lb	30 in	22 in	5 3/4 in to 54 in	32 in	22 1/2 in	60 1/2 in	Wesco	445K88
Manual Platform Lift Trucks/Stackers								
Steel Fixed Base with Foot Pump Hydraulic Lift								
880 lb	25 1/2 in	22 3/4 in	3 3/8 in to 47 in	40 3/4 in	23 3/8 in	56 1/8 in	Dayton	4ECW6
	25 1/2 in	22 3/4 in	3 3/8 in to 59 in	40 3/4 in	23 3/8 in	67 1/8 in	Dayton	4ECW7
Manual Hand-Truck-Style Platform Lifts								
Steel Fixed Base with Foot Pump Hydraulic Lift								
750 lb	22 in	22 in	1/2 in to 54 in	32 in	22 1/2 in	60 1/2 in	Dayton	2MPU5
	22 in	30 in	1/2 in to 54 in	32 in	30 in	60 1/2 in	Dayton	2MPU6
Portable Manual Platform Lift Trucks								
Steel Fixed Base with Hand Winch Chain/Cable Lift								
500 lb	20 in	20 in	3 1/4 in to 58 in	28 1/2 in	20 in	66 1/4 in	Dayton	26Y451
	20 in	24 in	6 1/4 in to 59 in	28 1/2 in	27 1/4 in	69 1/2 in	Dayton	26Y452
	20 in	20 in	1/4 in to 55 in	30 in	30 1/2 in	66 1/2 in	Dayton	26Y453
Aluminum Fixed Base with Hand Winch Chain/Cable Lift								
400 lb	20 in	20 in	3 1/8 in to 58 in	33 1/2 in	20 in	66 1/2 in	—	1XFE4
	20 in	24 in	6 1/8 in to 60 in	33 1/2 in	27 1/8 in	69 3/8 in	—	1XFE5