

Carbon Steel Transport Drums

Lined drums feature a modified phenolic coating that resists corrosion and chemical reactivity. Unlined drums are treated with a mild rust inhibitor.

Open-Head—Removable covers are EPDM-gasketed with either a UN-qualified lever lock or bolt. No tools, torque, or ring gap measurements are required for lever lock ring. **Closed-Head**—Drum lids are permanently secured and include 2" and 3/4" steel plugs and flanges with Buna gaskets.

Salvage/Overpack—Use open drums for transporting leaking or damaged containers. Covers are EPDM-gasketed and secured with lever lock ring closures or bolt. Yellow drums with red cover feature "Salvage Drum" logo.

						•	•
Volume		UN Rating	UN Rating	Overall	Inside		Item
Capacity		Solid	Liquid	Height	Dia.	Drum Color	No.
Open He							
Bolt Ring	Closure						
5 gal	20 20	1A2/X60/S	1A2/Y1.8/150	10 % in	14 in	Black w/White Cover	19K299
10 gal		1A2/X120/S	1A2/Y1.8/150	19 in	14 in	Black w/White Cover	4GY27
16 gal	20	1A2/X200/S	1A2/Y1.5/150	27 1/8 in	14 in	Black w/White Cover	1HBG8
20 gal	18	1A2/X220/S 1A2/X235/S	1A2/Y1.5/150 1A2/Y1.5/150	21 ¾ in	18.25 in	Black w/White Cover	1HBG9
	20	1A2/X235/S	1A2/Y1.5/150	29 in	18.25 in	Black w/White Cover	5ERH3
30 gal	18	1A2/X235/S	1A2/Y1.5/150	29 in	18.25 in	Black w/White Cover	4GY28
	18/20/20	1A2/Y425/S	1A2/Y1.2/100	34 ½ in	22 5 in	Black w/White Cover	5ERH2
	16	1A2/X430/S	1A2/Y1.5/175	34 ½ in	22.5 in 22.5 in	Black w/White Cover	1HBH2
	18	1A2/X435/S	1A2/Y1.5/150	34 ½ in	22.5 in	Black w/White Cover	4GY29
	18/18/18	1A2/X400/S	1A2/Y1.8/200	34 ½ in	22.5 in	Black	9KYY6
55 aal	18/18/20	1A2/X400/S	1A2/Y1.8/200	34 ½ in	22.5 in 22.5 in	Blue	23Y332
55 gal	18/18/20	1A2/X400/S	1A2/Y1.8/200		22.5 III		23Y345
				34 ½ in	22.5 in	Gray	
	16/18/18 18/18/19	1A2/X400/S 1A2/X400/S	1A2/Y1.8/200	35 in 35 in	23.5 in 23.5 in	Black w/White Cover	484X61
	18/18/19	1A2/X400/S	1A2/Y1.8/200	35 IN	23.5 In	Black w/White Cover	484X62
	18/18/20		1A2/Y1.6/200	35 in	23.5 in	Black w/White Cover	484X63
	g Closure,	Lined					
10 gal	20	1A2/X120/S	1A2/Y1.8/150	19 in	14 in	Black w/White Cover	1MKZ5
30 gal	18	1A2/X235/S	1A2/Y1.5/150	29 in	18.25 in	Black w/White Cover	1MKZ9
Bolt Rine	Closure.	Lined with 2	x 3/4" Fittings in	n the Cove	er		
55 gal	18	1A2/X435/S	1A2/Y1.5/150	34 ½ in	22.5 in	Black w/White Cover	2GTW7
Bolt Rin	Closure v	vith 2 x 3/4" Fi	ittings in the C	over			
30 gal	18	1A2/X235/S	1A2/Y1 5/150	29 in	18.25 in	Black w/White Cover	2GTW9
55 gal	18	1A2/X435/S	1A2/Y1.5/150 1A2/Y1.5/150	34 ½ in	22.5 in	Black w/White Cover	2GTW5
Lever In	ck Ring Cl	neuro	1712/11.0/100	01 /2 111	LL.0 III	Diddik W/William Cover	Laiwo
16 gal	18/20/20	1/10//200/6		27 in	27 in	Black w/White Cover	1MKZ7
20 gal	10/20/20	1A2/Y200/S 1A2/X220/S		21 ½ in	18 25 in	Black w/White Cover	1MKZ8
20 gai	18	1A2/X235/S		29 in	18.25 in 18.25 in	Black w/White Cover	1MLA1
30 gal		TAZ/AZ33/3		29 111	10.23 111		
CC1	18/18/20	1 4 0 0 / 4 0 5 / 0		34 ½ in 34 ½ in	22.5 in 22.5 in	Black	21YK41
55 gal	18; 20	1A2/Y425/S		34 ½ III	22.5 III	Black w/White Cover	5ERH4
	18	1A2/X435/S		34 ½ in	22.5 in	Black w/White Cover	1MLA2
		osure, Lined					
_55 gal	18	1A2/X435/S		34 ½ in	22.5 in	Black w/White Cover	2GTW4
Closed H	lead						
Lined							
10 gal	20	_	1A1/X1.4/250	19 ¼ in	14 in	Black w/White Cover	1MLA4
16 gal	20	_	1A1/X1.4/250	27 1/4 in	14 in	Black w/White Cover	19K309
30 gal	16/16/20 18/18/20	_	1A1/X1.8/300 1A1/X1.8/300	29 ½ in 34 ¾ in	18.25 in 22.5 in	Black w/White Cover	2GTX6
	18/18/20		1A1/X1.8/300	34 ¾ in	22.5 in	Black	19H067
	18/18/20		1A1/X1.8/300	34 ¾ in	22.5 in	Gray	23Y339
	18/18/20		1A1/X1.8/300	34 ¾ in	22.5 in	Blue	23Y341
55 gal	16		1A1/X1.8/300	35 1/4 in	22.5 in	Black w/White Cover	2GTX7
	18/18/20		1A1/X1.8/300	34 % in	22.5 in	Black	9CEJ1
	18/18/20		1A1/X1.6/300	36 in	22.5 in	Black w/White Cover	476H48
Unlined	10/10/20		TAT/AT.0/300	30 111	22.3 111	DIACK W/WITHE GOVE	4701140
5 gol	20		1A1/X1.6/250	10 % in	14 in	Black w/White Cover	19K302
5 gal 10 gal	20		1A1/X1.0/230	10 98 III	14 in	Black W/Wille Cover	4GY30
10 gal	20 20		1A1/X1.4/250 1A1/X1.4/250	19 ½ in 27 in	14 in	Black w/White Cover	1MLA5
_16 gal	20		1A1/X1.4/250	27 III		Black w/White Cover	
30 gal	20		1A1/Y1.5/300	29 ½ in	18.25 in	Black w/White Cover	4GY31
3	16/16/20		1A1/X1.8/300	29 ½ in	18.25 in	Black w/White Cover	2GTX4
	16		1A1/X1.8/300	35 ¼ in	22.5 in	Black w/White Cover	1MLA8
55 gal	18/18/20	_	1A1/X1.6/300	36 in	22.5 in	Black w/White Cover	476H50
JJ yai	18	_	1A1/X1.8/300	36 in	22.5 in	Black w/White Cover	476H51
	20/20/20	_	1A1/Y1.4/200	34 ¾ in	22.5 in	Black w/White Cover	476H49
Salvage	Drums						
Bolt Rin	Closure						
5 nal	20/20/20	1A2/X60/S	1A2/Y1.8/150	10 ½ in	14 in	Yellow w/Red Cover	20UK65
30 gal	16/18/18	1A2/X235/S	1A2/Y1 5/150	29 in	18.25 in	Yellow w/Red Cover	5ERJ3
55 gal	16/18/18	1A2/X400/S	1A2/Y1 5/150	34 ½ in	22.5 in	Yellow w/Red Cover	2GTY3
85 gal	18	1A2/X400/S 1A2/X440/S	1A2/Y1.5/150 1A2/Y1.5/150 1A2/Y320/S	39 ½ in	26 in	Yellow	2GTY4
06 gal	16	1A2/X440/S	17121/1020/0	42 ¾ in	26 in	Yellow w/Red Cover	2GTX8
96 gal		1A2/X440/S 1A2/Y409/S					10110
110 gal	16			42 ¾ in	30 in	Yellow w/Red Cover	1MLA9
	ck Ring Cl			10:	4.4 :	Vallaurur/DI O	403/00
10 gal		1A2/X120/S		19 in	14 in	Yellow w/Red Cover	4GY33
20 gal	18	1A2/X220/S		21 ½ in	18.25 in	Yellow w/Red Cover	4GY34
55 gal	16/18/18	1A2/X400/S		34 ½ in	22.5 in	Yellow w/Red Cover	4GY35
85 gal	18	1A2/X440/S	1A2T/Y320/S	38 ¾ in	26 in	Yellow	4GY36



Stainless Steel Transport Drums

Stainless steel drums feature better corrosion resistance and tensile strength than carbon steel drums. Type 304, 2B finish. Open-head drums close easily with a carbon steel bolt ring closure. Closed-head drums feature a 2" x %4" flanged fitting with a Buna gasket.

Volume Cap.	Gauge	UN Rating Solid	UN Rating Liquid	Overall Height	Inside Dia.	Item No.
Open Head	uauye	UN Hattily Sullu	Liquiu	пенуни	Dia.	NU.
5 gal	20/20/20	1A2/X60/S	1A2/Y1.5/150	10 ¾ in	14 in	20UK70
8 gal	20	1A2/X96/S	1A2/Y1.8/150	15 % in	14 in	5ERJ6
10 gal	20	1A2/X120/S	1A2/Y1.8/150	19 in	14 in	1MLC2
16 gal	20	1A2/X120/S	1A2/Y1.5/150	27 in	14 in	2GTY7
20 gal	16/18/18	1A2/X160/S	1A2/Y1.5/150	21 ½ in	18.25 in	2GTY5
30 gal	16/18/18	1A2/X100/3	1A2/Y1.5/150	29 in	18.25 in	1HBH3
ou yai						
	16/18/18	1A2/X440/S	1A2/Y1.5/150	35 1/4 in	22.5 in	1MLC4
55 gal	16	1A2/X430/S	1A2/Y1.5/200	34 ½ in	22.5 in	4GY38
	18/18/18			36 in	22.5 in	20UL06
85 gal	16/16/16	1A2/X440/S		39 in	26 in	20UK71
Open Head with 2 and 34" Fittings in the Cover						
55 gal	16	1A2/X430/S	1A2/Y1.5/200	34 ½ in	22.5 in	2GTY9
Closed Head						
8 gal	20	_	1A1/X1.4/250	16 ¾ in	14 in	5ERJ7
10 gal	20		1A1/X1.4/250	19 ¼ in	14 in	1MLC1
16 gal	20		1A1/X1.2/250	27 in	14 in	2GTY8
20 gal	18		1A1/X1.2/300	21 ½ in	18.25 in	2GTY6
	18		1A1/X1.2/300	29 ½ in	18.25 in	1MLC3
30 gal -	18/18/18		1A1/X1.2/300	29 ½ in	18.25 in	20UK83 *
	16		1A1/X1.8/550	35 1/4 in	22.5 in	19K327
55 gal -	18		1A1/X1.8/300	35 1/4 in	22.5 in	4GY37
	18/18/18		1A1/X1.8/300	35 1/4 in	22.5 in	20UK84 *
* Type 316, 2B finish.						



Fiber Transport Drums

For dry or solid materials. Open-head drums with carbon steel covers, lever lock ring closures, and galvanized chime bands.

Volume Cap.	UN Rating Solid	Height	Dia.	No.
With Fiber Lid				
5 gal	1G/Y60/S	8 ¾ in	11.625 in	8DRE7
47 gal	_	31 in	_	23Y340
55 gal	_	35 ½ in	21.5 in	23Y338
With Plastic Lid				
55 gal	_	35 ½ in	21.5 in	23Y347
55 gal	1G/Y235/S	36 in	21.5 in	23Y348
With Steel Lid				
15 gal	1G/Y106/S	19 ½ in	15.5 in	19H071
30 gal	1G/Y140/S	27 in	18.5 in	19H066
55 gal	1G/Y260/S	35 ½ in	21.5 in	19H072