16C236





Metal Shelf and Utility Carts with Ventilated Walls

Metal mesh walls surround the top shelf on these carts to provide maximum protection against items falling off the shelf while the carts are moving. The mesh walls also allow air to flow through them for ventilation and let users see items on the shelf. The carts have a lipped bottom shelf.

Load Capacity	Shelf Length	Shelf Width	Overall Length	Overall Width	Overall Height	Distance Between Shelves	ltem No.
1 400 lb	30 in	18 in	42 in	24 1/2 in	37 ½ in	14 in	16C236
1,400 lb	30 in	24 in	36 in	24 1/2 in	37 ½ in	14 in	16C238
3,600 lb	48 in	24 in	52 in	24 ½ in	39 ½ in	14 in	16C245



Flow-Through Metal Shelf and Utility Carts

These flow-through utility carts have metal shelves with openings that let debris and liquid fall through them, which helps keep the carts clean when used in dirty or wet areas. **Perforated** shelves have small holes. **Slotted** shelves have long vertical openings.

No. of Shelves	Load Capacity	Shelf Length	Shelf Width	Overall Length	Overall Width	Overall Height	Distance Between Shelves		ltem No.
Perforat	ed Lipped	Shelves							
	1,000 lb	36 in	24 in	42 ¼ in	24 1/4 in	34 ½ in	18 1⁄% in	_	19C185
2	1,000 lb	48 in	24 in	52 in	24 ½ in	30 ½ in	18 1/8 in	_	19C186
2	1,200 lb	36 in	24 in	42 1/4 in	24 1/4 in	35 1/s in	24 1/4 in	_	19G831
	1,200 lb	36 in	24 in	42 ¼ in	24 1/4 in	32 ½ in	18 1/s in	_	19G878
3	1,200 lb	60 in	30 in	66 ¼ in	30 1/4 in	63 in	24 5% in	_	19C135
4	1,600 lb	60 in	30 in	65 ½ in	30 in	63 in	16 in	Little Giant	19C137
5	2,000 lb	48 in	24 in	52 in	24 1/2 in	63 in	11 3 in	_	19C138
5	2,000 lb	60 in	30 in	65 ½ in	30 in	63 in	11 ½ in	Little Giant	19C139
Corrosio	n-Resista	nt Slotted	Flush Sl	ielves					
0	600 lb	41 in	19 in	47 in	19 in	47 ½ in	29 in	_	414X83
2	1.000 lb	41 in	19 in	48 in	19 in	42 in	20 in	_	12G993



Low-Profile Metal Shelf and Utility Carts

The top shelf on these carts is set at a lower height than other styles of metal shelf and utility carts. This reduces how far bulky or heavy items must be lifted when loading them onto the top shelf. **Easy access and load** carts have two rear corner posts and a front central pillar that support the carts' top shelf and reduce obstructions when moving items onto or off of the carts. They also have flush tube shelves that let items slide onto or off of the shelves and allow dirt and debris to fall through the spaces between the tubes.

Load Capacity	Shelf Length	Shelf Width	Overall Length	Overall Width	Overall Height	Distance Between Shelves	Brand	ltem No.
Easy Acce	ess & Ľoad	Carts wit	h Tube Fran	1e				
2 Shelves	and Raise	d Handle						
1,400 lb -	36 in	18 in	42 ½ in	24 ½ in	39 in	17 ¾ in	_	16C390
	36 in	24 in	42 ½ in	24 ½ in	36 in	17 ¾ in	—	9AKU3
	48 in	18 in	52 in	24 ½ in	35 ½ in	17 ¾ in	_	16C391
	48 in	24 in	54 ½ in	24 ½ in	36 in	17 ¾ in	—	8DLD3
	Flush Shel							
2 Shelves	and Raise							
	24 in	18 in	43 in	25 ½ in	34 in	13 1/8 in		49Y588
	30 in	18 in	36 ½ in	18 ¼ in	40 ¹ 1⁄16 in	20 in		16C180
	30 in	24 in	31 in	25 in	37 in	17 in	Jamco	8EN38
	32 in	18 in	43 in	25 ½ in	34 in	13 1/8 in	_	10F443
	36 in	18 in	36 in	23 in	40 ½ in	20 in		16C181
	36 in	24 in	39 in	25 ½ in	34 in	16 ¾ in		16C804
	36 in	24 in	40 in	24 in	36 in	17 in		10F444
1,200 lb	36 in	24 in	43 in	25 ½ in	31 in	16 ¾ in		4YW64
	36 in	24 in	43 in	25 ½ in	35 ½ in	16 ¾ in	_	4YW68
	36 in	24 in	44 in	25 ½ in	35 ½ in	20 in	_	16C182
	48 in	24 in	52 in	26 in	39 in	13 1/8 in		10F445
	48 in	24 in	52 in	30 ½ in	34 ½ in	16 ¾ in	_	16C805
	48 in	30 in	51 in	30 ¼ in	36 in	13 1/8 in	—	10F446
	60 in	24 in	66 in	25 in	43 in	17 in	Jamco	16C806
	60 in	30 in	66 ½ in	30 ½ in	38 in	13 1/8 in	_	10F447
	30 in	18 in	43 in	25 ½ in	35 ½ in	16 ¾ in	—	8EK82
	36 in	24 in	43 in	25 ½ in	35 ½ in	16 ¾ in	_	8WC16
1,400 lb	36 in	30 in	48 in	30 ½ in	34 ½ in	16 ¾ in	_	16C770
1,400 ID	48 in	24 in	52 in	26 in	39 in	16 ¾ in		16C787
	48 in	30 in	52 in	30 ¼ in	31 in	16 ¾ in	_	4YW73
	72 in	30 in	78 ½ in	30 ½ in	34 in	16 ¾ in	—	160773
2,400 lb	30 in	24 in	36 in	25 in	40 in	17 in	Jamco	16C835
	36 in	30 in	42 in	31 in	40 in	17 in	Jamco	16C840
	48 in	24 in	54 in	25 in	40 in	17 in	Jamco	16C837
	48 in	30 in	54 in	31 in	40 in	17 in	Jamco	16C841
	60 in	30 in	66 in	31 in	40 in	17 in	Jamco	16C842
4.800 lb	30 in	24 in	36 in	25 in	42 in	17 in	Jamco	16C824
,	48 in	36 in	54 in	37 in	42 in	17 in	Jamco	16C833
	and Raise							
1,400 lb	36 in	24 in	43 in	25 ½ in	39 5⁄% in	7 5⁄8 in		4DKP9
4,800 lb	60 in	30 in	66 ½ in	30 ½ in	40 in	9 1⁄8 in		4DKT7
Lipped Sh								
2 Shelves	and Raise		10.1	0.0.1 ()		10.111		
	24 in	18 in	43 in	25 ½ in	34 in	13 ¼ in	_	49Y595
	32 in	18 in	39 in	30 ½ in	40 in	13 1/4 in	_	10F448
1,200 lb	36 in	24 in	39 in	30 ½ in	40 in	16 ¾ in	—	49Y596
	48 in	24 in	54 ½ in	30 ½ in	30 in	13 ¼ in	_	10F450
	48 in	30 in	54 ½ in	30 ½ in	39 in	13 ¼ in		10F451
	60 in	30 in	66 ½ in	30 ½ in	38 in	13 ¼ in	_	10F452
	60 in	30 in	66 ½ in	30 ½ in	36 in	16 ¾ in	_	49Y171

1150 **GRAINGER**

Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)