



## Self-Dumping Steel Hoppers

- Red powder-coat finish on hopper, black base

### HOPPERS

Automatically dump loads when locking latch is released, then return to locked position. Constructed with precision robotic weld; base is formed steel. Safety chain secures hopper to fork truck, while cable enables dumping from fork truck seat.

### Low-Profile

Feature a 90° dump angle and half-length fork entry. Hoppers return

to locked position when lowered to ground.

### Front-Release

Bumper dumps hopper a minimum of 70° when activated. Full-length fork entry. Predrilled for caster kit.

### OPTIONAL CASTER KITS

Casters are field installable with hardware included. Include 2 rigid and 2 swivel casters. Intended for use on front-release hoppers only.



Low-Profile



Standard-Base



Optional Caster Kit

Volume Cap.	Overall Length	Overall Width	Overall Height	2000 lb. Item No.	4000 lb. Item No.	6000 lb. Item No.		
<b>Low Profile Self-Dumping Hoppers</b>								
¼ cu. yd.	46 in	25 in	18 ¼ in	5PKE8	5PKE9	5PKF0		
½ cu. yd.	51 ¼ in	25 in	28 in	5PKF1	5PKF2	5PKF3		
1 cu. yd.	51 ¼ in	49 in	28 in	5PKF4	5PKF5	5PKF6		
1½ cu. yd.	51 ¼ in	49 in	41 in	5PKF7	5PKF8	5PKF9		
<b>Front Self-Dumping Hoppers</b>								
¼ cu. yd.	49 ¼ in	26 in	38 ¼ in	—	—	5PKG1		
½ cu. yd.	52 in	26 in	38 ¼ in	5PKG0	—	—		
¾ cu. yd.	52 in	33 ½ in	38 ¼ in	5PKG2	—	5PKG3		
1 cu. yd.	61 ½ in	31 ½ in	43 in	5PKG4	—	5PKG5		
1½ cu. yd.	61 ½ in	41 ½ in	43 in	5PKG6	—	5PKG7		
2 cu. yd.	69 in	43 ½ in	52 in	5PKG8	—	5PKG9		
2½ cu. yd.	69 in	56 ½ in	52 in	5PKH0	5PKH1	5PKH2		
3 cu. yd.	69 in	69 ½ in	52 in	5PKH3	—	5PKH4		
3 cu. yd.	69 in	81 ¾ in	52 in	5PKH5	5PKH6	5PKH7		
				<b>Wheel/Tread Material</b>		<b>Load Rating</b>	<b>6 in-dia. Wheels Item No.</b>	<b>8 in-dia. Wheels Item No.</b>
				<b>Standard Plate Caster Kits</b>				
				Rubber		2400 lb	5PKH8	5PKH9
				Polyurethane		4800 lb	5PKJ2	5PKJ3
				Nylon		4800 lb	5PKJ4	5PKJ5

With Casters  
F1970



Without Casters  
F1975

## Self-Dumping Poly Hoppers

- Dump up to 40° below horizontal
- All-welded steel framework
- Bumper release

Seamless, molded polyethylene bodies are supported by steel tubular frames.

Hoppers with casters have 2 swivel, 2 rigid casters. Hoppers without casters are forklift capable for elevated dumping and mobility.

Volume Cap.	Load Capacity	Overall Length	Overall Width	Overall Height	► CHOOSE: Color	Item No.
<b>Hoppers with (4) 6 in Rubber Casters</b>						
¾ cu. yd.	750 lb.	59 in	26 in	42 in	Blue, Green, Red, White, Yellow	F1970
1 cu. yd.	1000 lb.	71 in	31 in	46 in	Blue, Green, Red, White, Yellow	F1972
1½ cu. yd.	1200 lb.	80 in	40 in	62 ½ in	Blue, Green, Red, White, Yellow	F1974
2¼ cu. yd.	1500 lb.	80 in	51 in	55 in	Blue, Green, Red, White, Yellow	F1976
<b>Hoppers without Casters</b>						
½ cu. yd.	750 lb.	59 in	26 in	42 in	Blue, Green, Red, White, Yellow	F1969
1 cu. yd.	1000 lb.	71 in	32 in	46 in	Blue, Gray, Green, Red, White, Yellow	F1971
1½ cu. yd.	1200 lb.	80 in	40 in	55 in	Gray	F1974 *
1¾ cu. yd.	1200 lb.	80 in	40 in	55 in	Blue, Green, Red, White, Yellow	F1973
2¼ cu. yd.	1500 lb.	80 in	51 in	55 in	Blue, Gray, Green, Red, White, Yellow	F1975

\* Not forklift capable.



300-Lb. Capacity



## 2-Wheel Wheelbarrows

These wheelbarrows have large 20"-dia. wheels and a one-piece plastic container that won't leak, cleans easily, and resists mild chemicals.

Cubic Ft. Capacity	Load Capacity	Wheel Material	Wheel Type	Item No.
3 ½ cu ft	200 lb	Rubber	Semi-Pneumatic	2KTD7
7 ½ cu ft	300 lb	Vulcanized Rubber	Pneumatic	4W504



46V230

## 2-Wheel Steel Trailer Carts

2-wheel steel trailer carts can be pulled by all-terrain and utility task vehicles (ATVs and UTVs). Feature rust-resistant powder-coated finish and pneumatic tires that roll smoothly across rough terrain.

Volume Cap.	Load Capacity	Overall Length	Overall Width	Overall Height	Wheel Dia.	Wheel Width	Item No.
10.3 cu ft	500 lb	58 ¾ in	30 ½ in	30 in	15 in	3 ½ in	46V231
18.4 cu ft	1,000 lb	80 in	32 ¾ in	38 ¾ in	16 in	5 in	46V233
13.6 cu ft	1,500 lb	67 ¾ in	45 in	37 ¾ in	18 in	8 in	46V234
18.4 cu ft	1,500 lb	80 ¼ in	37 ¾ in	32 ¾ in	16 in	5 in	46V230