



For information on selecting casters, see page 1147.



Swivel Caster
w/Brake
26Y501

Low-Profile
Easy-Turn
Stem Casters

Used on equipment that must be kept low to the ground to maximize its stability while rolling, such as business machines, vending machines, store fixtures, lab equipment, refrigeration units, dollies, and server cabinets. Each caster has two small wheels mounted on one axle, which reduces friction between the floor and the wheels and allows the casters to swivel more easily than single-wheel casters. All are swivel casters and can rotate 360°.

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	SWIVEL CASTER Item No.	Pkg. Qty.	SWIVEL CASTER WITH BRAKE Item No.	Pkg. Qty.
Friction-Ring Stem							
Rubber Tread with Plain Wheel Bearing							
2"	200 lb	2 3/4"	1/16" x 1 1/2"	26Y503	1	—	—
Nylon Tread with Plain Wheel Bearing							
2"	110 lb	2 5/8"	1/16" x 1/8"	416P10	5	—	—
Threaded Stem							
Rubber Tread with Plain Wheel Bearing							
2"	200 lb	2 3/4"	1/2"-13 x 1 1/2"	—	—	26Y501	1
3"	350 lb	3 3/4"	1/2"-13 x 1 1/2"	26Y502	1	—	—



Antimicrobial
Expanding
Stem w/
Total Lock
455U33

Debris-
Resistant
Friction-Ring
32J932

Corrosion- and
Debris-Resistant
Stem Casters

Antimicrobial casters have wheels that are impregnated with an antimicrobial compound that prevents damaging or odor-causing microbes from growing on them. **Corrosion-resistant** casters will not rust or corrode in environments when exposed to water or cleaning chemicals. **Debris-resistant** casters have a thread guard that stops debris from getting inside the caster and damaging or contaminating it. Suitable for racks, carts, and other equipment that will be used in areas where the casters will be exposed to dirt or frequent washdowns, such as laundry rooms, textile factories, food-service facilities, restaurants, offices, government buildings, and schools. All are swivel casters and can rotate 360°.

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	Wheel Bearing Type	SWIVEL CASTER Item No.	SWIVEL CASTER WITH BRAKE Item No.
Antimicrobial Corrosion- & Debris-Resistant Expanding Stem						
Thermoplastic Rubber Tread						
3"	165 lb	4 1/8"	1/2"-13 x 2 1/4"	Precision Ball	455U23	455U39 *
4"	190 lb	5 1/8"	1/2"-13 x 2 1/4"	Precision Ball	455U27	455U33 *
5"	220 lb	6 1/8"	1/2"-13 x 2 1/4"	Precision Ball	455U25	455U40 *
6"	240 lb	7 1/8"	1/2"-13 x 2 1/4"	Precision Ball	455U41	455U34 *
Corrosion- & Debris-Resistant Threaded Stem						
Polyolefin Tread						
3"	110 lb	4 5/8"	3/18"-16 x 3/4"	Delrin	429H21	429H22
	110 lb	4 5/8"	5/16"-18 x 1"	Delrin	429H19	429H20
Debris-Resistant Friction-Ring Stem						
Polyurethane Tread						
5"	300 lb	5 13/16"	27/32" x 2 3/4"	Precision Ball	32J932	—
Debris-Resistant Threaded Stem						
Thermoplastic Rubber Tread						
5"	280 lb	6 1/4"	1/2"-13 x 1"	Precision Ball	29XW85	—

* With total lock.



Friction-
Ring Stem
2G001



Threaded
Stem
1G004

Furniture Stem Casters

Swivel casters install on chairs, carts, fixtures, and similar items in offices, retail settings, and other areas where they won't be exposed to heavy loads, chemicals, liquids, or high temperatures. Soft tread casters are less likely to damage hard tile or wood floors than hard tread casters, and hard tread casters won't grab or snag carpets.

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	Wheel Bearing Type	Features	Item No.	Pkg. Qty.
Friction-Ring Stem							
Nylon Tread							
2"	110 lb	2 9/32"	1/16" x 3/8"	Plain	Hooded, Noiseless Stem	416P09	4
	375 lb	2 1/2"	1/16" x 3/8"	Plain	Hooded Wheel	416P18	5
	440 lb	2 1/16"	1/16" x 1/8"	Plain	Hard Tread	19YX32	4
	440 lb	2 9/32"	1/16" x 1/8"	Plain	Soft Tread	19YX30	4
2"	550 lb	2 1/16"	1/16" x 1/8"	Plain	Hard Tread	19YX33	5
Polyolefin Tread							
2"	75 lb	2 3/64"	1/16" x 1/8"	Plain	Multipurpose Ball	19YX27	1
	80 lb	2 5/8"	3/8" x 1"	Plain	Sealed Precision Bearing Raceway	487G49	1
	80 lb	2 5/8"	1/16" x 1 1/16"	Plain	Swivel Force Reduction	454N48	1
Polyurethane Tread							
2"	550 lb	2 1/16"	1/16" x 3/8"	Plain	Soft Tread	19YX31	5
Rubber Tread							
2"	75 lb	2 1/2"	3/8" x 1"	Plain	Soft Tread	3A785	1
	75 lb	2 1/2"	3/8" x 1"	Precision Ball	Soft Tread	3A778	1
	75 lb	2 1/2"	1/16" x 3/8"	Plain	Fully Heat Treated	429H23	1
	75 lb	2 1/2"	1/16" x 1/8"	Precision Ball	Soft Tread	2G009	1
	75 lb	2 1/2"	1/16" x 1 3/8"	Plain	Hard Tread	1G011	1
	75 lb	2 1/2"	1/16" x 1 3/8"	Plain	Soft Tread	3A787	1
	75 lb	2 1/2"	1/16" x 1 3/8"	Precision Ball	Soft Tread	3A779	1
	75 lb	2 1/16"	1/16" x 1/8"	Plain	Soft Tread	2G001	1
	75 lb	3"	3/8" x 1"	Precision Ball	Soft Tread	2G003	1
	75 lb	3 3/32"	3/8" x 1"	Plain	—	429H16	1
2 1/2"	75 lb	3 3/32"	1/16" x 1 3/8"	Plain	—	429H17	1
	75 lb	3 3/32"	1/16" x 1/8"	Plain	—	429H11	1
	110 lb	3 3/8"	1/16" x 1 3/8"	Plain	Soft Tread	1G005	1
3"	165 lb	3 3/4"	1/16" x 1 3/8"	Plain	—	429H07	1
Threaded Stem							
Polyolefin Tread							
2"	75 lb	2 9/16"	5/16" x 1"	Plain	Multipurpose Ball	429H24	1
	80 lb	2 5/8"	5/16" x 1"	Plain	Sealed Precision Bearing Raceway	487G48	1
Rubber Tread							
2"	75 lb	2 1/2"	5/16"-18 x 1"	Plain	Soft Tread	4A002	1
	75 lb	2 1/2"	5/16"-18 x 3/4"	Plain	Soft Tread	34TA55	1
	75 lb	2 1/2"	5/16"-18 x 1 1/2"	Plain	Hard Tread	1G013	1
	75 lb	2 1/2"	3/8"-16 x 1 1/2"	Plain	Soft Tread	1G002	1
	75 lb	2 1/2"	3/8"-16 x 1"	Plain	Soft Tread	1G001	1
	75 lb	2 1/2"	3/8"-16 x 1"	Plain	Hard Tread	1G003	1
	75 lb	2 1/2"	3/8"-16 x 1 1/2"	Plain	Soft Tread	416P11	1
	75 lb	2 1/2"	3/8"-16 x 1 1/2"	Plain	Hard Tread	1G004	1
2 1/2"	110 lb	3 3/4"	3/8"-16 x 1 1/2"	Plain	Soft Tread	1G016	1
	110 lb	3 3/8"	3/8"-16 x 3/4"	Plain	Soft Tread	1G007	1
3"	165 lb	3 3/4"	3/8"-16 x 1 1/2"	Plain	Hard Tread	1G018	1
	175 lb	3 3/4"	3/8"-16 x 3/4"	Plain	Hard Tread	1G010	1