

## Manual Stackers WESCO

Dayton

Presto Genia.

Adjustable and Fixed Fork units have a foot pump, and Fixed Invertible Fork units have a hand crank, that operators use to activate the stackers' lifting mechanism. Suitable for intermittent use and applications where loads will be moved and lifted over short distances.

Load	Fork Size			Overall Dim.				Item	
Capacity	L	W	Lifting Height Range	L	W	Н	Brand	No.	
Straddle									
Adjustabl	e Forks								
1,000 lb	30 in	3 in	1 in to 4 ft 8 in	48 in	32 ½ in	75 in	Wesco	8EEX2	
	30 in	3 in	1 in to 4 ft 8 in	47 in	32 in	72 in	Dayton	2MPT8	
	30 in	3 in	1 in to 5 ft 4 in	47 in	32 in	80 in	Dayton	2MPT9	
	30 in	3 in	1 in to 6 ft 4 in	47 in	32 in	92 in	Dayton	2MPU1	
	30 in	3 in	3 1/4 in to 4 ft 2 in	49 in	33 in	66 in	Presto Lifts	16X838	
2,000 lb	36 in	4 in	2 ¾ in to 5 ft 3 in	56 in	54 in	79 ½ in	Dayton	4VME8	
	36 in	4 in	2 ¾ in to 8 ft 2 in	56 in	54 in	69 ¾ in	Dayton	4VME9	
	36 in	4 in	2 ¾ in to 9 ft 10 in	56 in	54 in	79 ½ in	Dayton	4VMF1	
Fixed Invertible Forks									
350 lb	22 ½ in	3 ½ in	2 in to 11 ft 8 in	43 in	43 ½ in	78 ½ in	Genie	4YZ81	
	22 ½ in	3 ½ in	3 ½ in to 13 ft 9 in	43 in	43 ½ in	91 in	Genie	4YZ82	
400 lb	22 ½ in	3 ½ in	3 ½ in to 10 ft 5 in	43 in	43 ½ in	67 ½ in	Genie	4YZ86	
500 lb	22 ½ in	3 ½ in	3 ½ in to 5 ft 11 in	43 in	43 ½ in	67 ½ in	Genie	4YZ84	
Fork-Over Stackers									
Adjustabl	e Forks								
750 lb	18 in	3 in	1/2 in to 4 ft 6 in	30 in	21 % in	60 ½ in	Dayton	2MPU9	
	18 in	3 in	5 ¾ in to 4 ft 6 in	32 in	24 in	60 ½ in	Wesco	445K89	
Fixed Forks									
2,000 lb	43 in	6 1/4 in	3 1/4 in to 8 ft 2 in	63 in	28 ½ in	72 in	Dayton	4VME2	
2,000 10	43 in	6 1/4 in	3 1/4 in to 9 ft 10 in	63 in	28 ½ in	82 in	Dayton	4VME3	
3,000 lb	43 in	6 1/4 in	3 1/4 in to 5 ft 3 in	63 in	28 ½ in	80 in	Dayton	4VME1	
Fixed Inv	ertible For	ks							
400 lb	22 ½ in	3 ½ in	3 ½ in to 10 ft 5 in	34 ¾ in	27 in	67 ½ in	Genie	4YZ85	
500 lb	22 ½ in	3 in	3 ½ in to 5 ft 11 in	34 ¾ in	27 in	67 ½ in	Genie	4YZ83	
Counterb	alanced St	ackers							
Fixed Invertible Forks									
350 lb	22 ½ in	3 in	3 ½ in to 11 ft 8 in	28 ½ in	43 ½ in	78 ½ in	Genie	18F634	
400 lb	22 ½ in	3 in	3 ½ in to 10 ft 5 in	28 ½ in	43 ½ in	67 ½ in	Genie	18F633	
500 lb	22 ½ in	3 in	3 ½ in to 5 ft 11 in	28 ½ in	43 ½ in	67 ½ in	Genie	18F632	







## Presto

## **Manual Platform Lifts**

Suitable for intermittent use and applications where loads will be moved and lifted over short distances. Compact footprint can maneuver in tight spaces such as aisles, loading docks, and store rooms. Can also be used as adjustable-height work tables and for feeding materials into machines.

Manual platform lift trucks have the outrigger legs positioned directly underneath the platform.

**Manual platform lift trucks/stackers** have a removable platform and adjustable-width forks. The platform is used for moving and raising loads that are not stored on pallets or skids, and the forks are used for moving and raising loads that are stored on pallets and skids.

**Manual hand-truck-style platform lifts** have two large rear wheels and are tilted back and rolled to move loads for short distances. The nose of the platform sits on the ground when the trucks are upright, for easy loading of items onto the platform.

**Portable manual platform lift trucks** have a handle and additional set of wheels mounted to the top of the frame that allow them to be tilted back and loaded into and out of vehicles when empty. The outrigger legs are positioned directly underneath the platform.

Load	Platfor	m Dim.	Lifting		verall Din		Item			
Capacity	L	W	Height Range	L	W	Н	Brand	No.		
Manual P	latform Li	ft Trucks								
Steel Fix	ed Base w	ith Hand V	Vinch Chain/Cab	le Lift						
750 lb	22 in	22 in	5 ¾ in to 54 in	32 in	22 in	60 ½ in	_	8A125		
	30 in	22 in	5 ¾ in to 54 in	32 in	22 in	60 ½ in	Wesco	8DTY9		
Steel Fixed Base with Foot Pump Hydraulic Lift										
	16 in	20 in	5 ¾ in to 40 in	32 in	22 ½ in	48 ½ in	_	8Y719		
750 lb	22 in	22 in	5 ¾ in to 54 in	32 in	22 ½ in	60 ½ in	Dayton	2MPU7		
750 10	22 in	30 in	5 ¾ in to 54 in	32 in	30 in	60 ½ in	Dayton	2MPU8		
	22 in	30 in	5 ¾ in to 54 in	32 in	30 in	60 ½ in	_	8A080		
	25 % in	21 ½ in	8 in to 33 ½ in	40 in	23 3/16 in	38 % in	Dayton	4ECW8		
880 lb	25 % in	21 ½ in	8 in to 47 in	40 in	23 3/16 in	52 ¾ in	Dayton	4ECW9		
	25 % in	21 ½ in	8 in to 59 in	40 in	23 3/16 in	64 3/16 in	Dayton	4ECX1		
	16 in	24 in	5 ¾ in to 60 in	40 in	25 ½ in	75 in	Wesco	9GNA0		
	24 in	24 in	5 ¾ in to 60 in	36 in	25 ½ in	72 in	Dayton	2MPT2		
	24 in	24 in	5 ¾ in to 68 in	40 in	25 ½ in	80 in	Dayton	2MPT3		
	24 in	25 ½ in	5 ¾ in to 80 in	36 in	25 ½ in	92 in	Dayton	2MPT4		
1,000 lb	24 in	24 in	5 ½ in to 52 in	53 ½ in	25 in	66 in	Presto Lifts	16X837		
	30 in	32 in	5 ¾ in to 60 in	44 in	32 in	72 in	Dayton	2MPT5		
	30 in	32 in	5 ¾ in to 68 in	44 in	32 in	80 in	Dayton	2MPT6		
	30 in	32 in	5 ¾ in to 80 in	44 in	32 in	92 in	Dayton	2MPT7		
	30 in	24 in	5 ¾ in to 80 in	40 in	25 ½ in	94 in	Wesco	8EAC6		



Load	Platform Dim.		Lifting	C	verall Din		Item			
Capacity	L	W	Height Range	L	W	Н	Brand	No.		
2,000 lb	30 in	32 in	6 in to 63 in	54 in	34 in	79 ½ in	Dayton	4VME4		
	30 in	32 in	6 in to 98 in	54 in	34 in	120 in	Dayton	4VME6		
	30 in	32 in	6 in to 118 in	54 in	34 in	84 in	Dayton	4VME7		
3,000 lb	30 in	32 in	6 in to 63 in	54 in	34 in	81 ½ in	Dayton	4VME5		
Stainless Steel Adjustable Base with Foot Pump Hydraulic Lift										
750 lb	30 in	22 in	5 ¾ in to 54 in	32 in	22 ½ in	60 ½ in	Wesco	445K88		
Manual Platform Lift Trucks/Stackers										
Steel Fixed Base with Foot Pump Hydraulic Lift										
880 lb	25 % in	22 ¾ in	3 % in to 47 in	40 ¾ in	23 5/16 in	56 1/8 in	Dayton	4ECW6		
	25 % in	22 ¾ in	3 % in to 59 in	40 ¾ in	23 5/16 in	67 % in	Dayton	4ECW7		
Manual Hand-Truck-Style Platform Lifts										
Steel Fixed Base with Foot Pump Hydraulic Lift										
750 lb	22 in	22 in	½ in to 54 in	32 in	22 ½ in	60 ½ in	Dayton	2MPU5		
	22 in	30 in	½ in to 54 in	32 in	30 in	60 ½ in	Dayton	2MPU6		
Portable Manual Platform Lift Trucks										
Steel Fixed Base with Hand Winch Chain/Cable Lift										
500 lb	20 in	20 in	3 1/4 in to 58 in	28 ½ in	20 in	66 1/4 in	Dayton	26Y451		
	20 in	24 in	6 1/4 in to 59 in	28 ½ in	27 1/4 in	69 ½ in	Dayton	26Y452		
	20 in	20 in	1/4 in to 55 in	30 in	30 ½ in	66 ½ in	Dayton	26Y453		
Aluminum Fixed Base with Hand Winch Chain/Cable Lift										
400 lb	20 in	20 in	3 1/8 in to 58 in	33 1/8 in	20 in	66 ½ in	_	1XFE4		
	20 in	24 in	6 1/8 in to 60 in	33 1/8 in	27 1/8 in	69 5/16 in		1XFE5		