



2KMA7



Leveling Jacks

Designed for permanent installation, these screw-style jacks hold platforms and portable equipment in place and keep them stabilized. Typically, for use with work platform applications. Include folding crank handle.

Cap. (lb.)	Overall H (in.)	Min. Height Below Equip Frame (in.)	Max. Extended Height Below Equip Frame (in.)	Screw Travel	Finish	Item No.
5,000 lb	18 in	4 1/2 in	13 1/2 in	9 in	Stainless Steel	2KMA7
5,000 lb	26 in	4 1/2 in	21 1/2 in	17 in	Stainless Steel	2KMA8
5,000 lb	30 in	4 1/2 in	25 1/2 in	21 in	Chrome	2KMA6
5,000 lb	30 in	4 1/2 in	25 1/2 in	21 in	Stainless Steel	2KMA9



1XEX1



29AU76



Threaded Tube Ends

Material is glass-fiber reinforced polyamide based (PA) technopolymer. Resistant to solvents, oils, grease, and other chemical agents. Standard execution. Brass boss, threaded pass-through hole. Black matte finish.

Tube Wall Size	Brand	Outside Dia.	ROUND Load Capacity	Item No.	Outside Dia.	SQUARE Load Capacity	Item No.
1 in Thread Size							
0.079 in	Elesa	1.75 in	1,232 lb	29AU90	—	—	—
3/8-16 Thread Size							
0.065 in	S & W	1.5 in	1,500 lb	1XEY1	1 1/2 in sq	1,500 lb	1XEX1
	Elesa	—	—	—	1.5 in	1,344 lb	29AU81
1/2-13 Thread Size							
S & W		1.5 in	1,500 lb	1XEY2	1 1/2 in sq	1,500 lb	1XEX2
0.065 in	S & W	2 in	2,000 lb	1XEY4	2 in sq	2,000 lb	1XEX6
	Elesa	1.5 in	1,120 lb	29AU85	—	—	—
0.12 in	S & W	—	—	—	1 1/2 in sq	1,500 lb	1XEX4
	S & W	—	—	—	2 in sq	2,000 lb	1XEX7
	Elesa	—	—	—	1.5 in	1,344 lb	29AU82
27/49 Thread Size							
0.079 in	Elesa	1.181 in	1,008 lb	29AU77	1.378 in	1,344 lb	29AU75
	Elesa	1.654 in	1,120 lb	29AU79	—	—	—
5/8-11 Thread Size							
0.065 in	S & W	1.5 in	1,500 lb	1XEY3	1 1/2 in sq	1,500 lb	1XEX3
	Elesa	1.5 in	1,120 lb	29AU86	1.5 in	1,344 lb	29AU83
0.079 in	Elesa	1.75 in	1,232 lb	29AU88	—	—	—
0.12 in	S & W	—	—	—	1 1/2 in sq	1,500 lb	1XEX5
	S & W	—	—	—	2 in sq	2,000 lb	1XEX8
3/4-10 Thread Size							
0.065 in	Elesa	1.5 in	1,120 lb	29AU87	1.5 in	1,792 lb	29AU80
0.079 in	Elesa	1.75 in	1,232 lb	29AU89	—	—	—
0.12 in	S & W	—	—	—	2 in sq	2,000 lb	1XEX9
	Elesa	—	—	—	1.5 in	1,792 lb	29AU84
42/89 Thread Size							
0.079 in	Elesa	1.181 in	1,008 lb	29AU76	1.378 in	1,344 lb	29AU74
M12 Thread Size							
0.079 in	Elesa	1.654 in	1,120 lb	29AU78	1.181 in	1,008 lb	29AU72
M14 Thread Size							
0.079 in	Elesa	—	—	—	1.181 in	1,008 lb	29AU73



4NYH2



4TPX7



20KK63



4TRY5



Boltless Leveling Mounts

Level-It—Choose from steel, nonskid steel, stainless steel, and Delrin base. See Grainger.com for additional leveling mounts.

PolyMount—Polyglass-filled nylon base is corrosion-resistant. Lag holes allow permanent floor mounting. For washdown applications. See Grainger.com for additional leveling mounts.

Base Dia.	H	Hex	Load Capacity	Base	Finish	Item No.	
Level-It							
1/4"-20							
1 in	0.81 in	1/2 in	200 lb	Delrin	Stainless Steel	4TPW8	
		1/2 in	750 lb	Steel w/ Non-Skid Pad	Yellow Zinc-Plated	4NYH2	
3/8"-16							
1.07 in	0.88 in	3/8 in	3750 lb	Steel	Black Oxide-Coated	20KK61	
		3/8 in	3750 lb		Yellow Zinc-Plated	26377	
		3/8 in	3750 lb		Nickel-Plated	26378	
1 1/4 in	1 in	3/8 in	300 lb	Delrin w/ Non-Skid Pad	Yellow Zinc-Plated	4TPW3	
		3/8 in	1800 lb	Steel w/ Non-Skid Pad	Yellow Zinc-Plated	4NYH3	
		3/8 in	1800 lb	Nickel-Plated		4TVE9	
1/2"-13							
1.88 in	1.13 in	3/4 in	700 lb	Delrin	Yellow Zinc-Plated	4NYU4	
		3/4 in	5000 lb	Steel	Yellow Zinc-Plated	26379	
		3/4 in	5000 lb		Nickel-Plated	26380	
	1.25 in	3/4 in	5000 lb	Delrin w/ Non-Skid Pad	Black Oxide-Coated	20KK62	
		3/4 in	700 lb		Stainless Steel	4TPX7	
		3/4 in	3750 lb		Yellow Zinc-Plated	4NYH4	
	3/4 in	3750 lb	Steel w/ Non-Skid Pad	Nickel-Plated	4TVF1		
5/8"-11							
2 1/2 in	1.25 in	7/8 in	6000 lb	Steel	Yellow Zinc-Plated	26381	
		7/8 in	6000 lb		Nickel-Plated	26382	
	1.38 in	7/8 in	6000 lb	Delrin w/ Non-Skid Pad	Black Oxide-Coated	20KK63	
		7/8 in	1200 lb		Stainless Steel	4TPX8	
	7/8 in	4500 lb	Steel w/ Non-Skid Pad	Yellow Zinc-Plated	4NYH5		
3/4"-10							
3 in	1.5 in	1 1/8 in	7400 lb	Steel	Yellow Zinc-Plated	26383	
		1 1/8 in	7400 lb		Nickel-Plated	26384	
		1 1/8 in	7400 lb		Black Oxide-Coated	20KK64	
	1.63 in	1 1/8 in	5550 lb	Steel w/ Non-Skid Pad	Yellow Zinc-Plated	4NYH6	
		1 1/8 in	5550 lb		Nickel-Plated	4TVF3	
		1 1/8 in	5550 lb		Stainless Steel w/ Non-Skid Pad	Stainless Steel	4NYJ3
1"-8							
4 in	1.88 in	1 3/8 in	20,000 lb	Steel	Yellow Zinc-Plated	26385	
M8							
1 in	0.81 in	1/2 in	1000 lb	Stainless Steel	Stainless Steel	14H426	
M16							
2 1/2 in	1.38 in	7/8 in	6000 lb	Stainless Steel	Stainless Steel	14H429	
M20							
3 in	1.63 in	1 1/8 in	7400 lb	Steel	Yellow Zinc-Plated	14H424	
		1 1/8 in	7400 lb	Stainless Steel	Stainless Steel	14H430	
M24							
4 in	2 in	1 3/8 in	20,000 lb	Steel	Yellow Zinc-Plated	14H425	
PolyMount							
3/4"-16							
2 in	1.44 in	3/4 in	4000 lb	Nylon w/ Non-Skid Pad	Nylon	Clear Zinc-Plated	4TRX4
		3/4 in	4000 lb		Stainless Steel	4TRY9	
4 in	1.69 in	3/4 in	3000 lb		Nylon	Clear Zinc-Plated	4TTA5
		3/4 in	3750 lb		Stainless Steel	4TTD5	
5/8"-11							
3 in	1.69 in	7/8 in	5000 lb	Nylon	Clear Zinc-Plated	4TRX7	
4 in	1.88 in	7/8 in	6000 lb	Nylon w/ Non-Skid Pad	Clear Zinc-Plated	4TRY1	
		7/8 in	4500 lb		Clear Zinc-Plated	4TTC2	
3/4"-10							
4 in	2 in	1 1/8 in	7500 lb	Nylon	Stainless Steel	4TRZ7	
5 in	3 in	1 1/8 in	10,000 lb	Nylon	Clear Zinc-Plated	4TRY5	
1"-8							
5 in	3.31 in	1 3/8 in	7500 lb	Nylon w/ Non-Skid Pad	Stainless Steel	4TTE3	