

**1-800-GRAINGER (472-4643)**



**Fork Truck Work Platforms and Accessories**

- 1000-lb. capacity
- Powder-coat finish

Use platforms to lift personnel along with light tools and equipment, allowing work and inspections to be safely performed on elevated equipment. Include 42" railing, 4" toe guard, safety strap, and lock.

NOTE: OSHA requirement; before platform is purchased contact the manufacturer of the fork lift before using the platform, as the load label affixed to the forklift truck will need to accommodate the platform load.

**DAYTON**

Feature autoclosing entry door with lanyard attachment rail. Double-Door models have 2 autoclosing entry doors, allowing access from both sides of platform.



**BALLYMORE**

Heavy-duty forklifts feature 60"H screen that shields operator from the forklift mast. Rugged steel construction with a nonskid platform. Convenient 2" x 7" fork pockets are mounted on 29" centers. 4" swivel casters on base permit easy positioning. Ship flat in box for easy assembly or order assembled.

**ACCESSORIES**

**Sliding Tool Tray**— $\frac{3}{4}$ " lip keeps tools and parts from sliding off.

| Description                                    | Base Length  | Base Width        | Overall Height | Item No.          |          |
|--|--------------|-------------------|----------------|-------------------|----------|
| <b>Dayton Assembled Forklift Work Platform</b> |              |                   |                |                   |          |
| Single Door                                    | 36 in        | 36 in             | 66 in          | 5UEW0             |          |
|  | 48 in        | 36 in             | 66 in          | 5UEW1             |          |
|  | 48 in        | 48 in             | 66 in          | 5UEW2             |          |
| Double Door                                    | 37 in        | 37 in             | 66 in          | 5UEW6             |          |
|  | 36 in        | 36 in             | 66 in          | 5UEW3             |          |
|  | 48 in        | 36 in             | 66 in          | 5UEW4             |          |
| 48 in  | 48 in        | 66 in             | 5UEW5          |                   |          |
| <b>Baltimore Forklift Work Platform</b>        |              |                   |                |                   |          |
| Unassembled                                    | 36 in        | 36 in             | 66 in          | 8E631             |          |
|  | 40 in        | 48 in             | 66 in          | 8EFA4             |          |
|  | 48 in        | 36 in             | 66 in          | 9C9E2             |          |
| Assembled                                      | 36 in        | 36 in             | 66 in          | 8DZ92             |          |
|  | 40 in        | 48 in             | 66 in          | 8DZ93             |          |
|  | 48 in        | 36 in             | 66 in          | 8VXW4             |          |
| <b>Dayton® Accessories</b>                     |              |                   |                |                   |          |
| Item   | For Use With | L                 | W              | H                 | Item No. |
| Sliding Tool Tray                              | 5UEW2        | 8 $\frac{1}{4}$ " | 49"            | 1 $\frac{3}{4}$ " | 5UEW8    |



**Caldwell Fork Truck Booms**

- 7 $\frac{1}{2}$ "W x 2 $\frac{1}{2}$ "H usable fork pockets
- Include restraining chain with grab hook

Provide extra reach to lift and move heavy items safely.

**Telescoping** booms extend to a maximum horizontal reach of 12 ft. Feature alternate hook positions and a boom locking T-pin.

**Pivoting** booms have all the features of a telescoping boom, and can also be adjusted vertically in five increments up to 40°.

**Reach Over** boom is for use when clearance is a factor. Features swivel hooks with hook latches and multiple hook positions.

**Precision Lifting** booms are compact, versatile units that turn a standard forklift truck into a portable crane. Hook travels approximately 20 ft. Can be adjusted horizontally and vertically with easy toggle button control. Feature self-contained 12VDC power supply and 100 Ah battery with charger.

| Max. Cap.                               | Horizontal Reach  | Pocket Spacing                                   | Item No. |
|---|---|--|----------|
| <b>Forklift Booms</b>                   |   |  |          |
| <b>Telescoping</b>                      |   |  |          |
| 3,000 lb                                | Boom Hook 3ft to 6 ft, Lifting Hook 7 ft to 12 ft         | 22 in Outside Edge to Outside Edge               | 426G82   |
| 4,000 lb                                | 7 ft to 12 ft Adjustable in 1 ft Increments               | 22 in Outside Edge to Outside Edge               | 8AHG8    |
| 6,000 lb                                |   | 22 in Outside Edge to Outside Edge               | 8Z498    |
| 8,000 lb                                |   | 22 in Outside Edge to Outside Edge               | 9G163    |
| <b>Fixed Length</b>                     |   |  |          |
| 1,500 lb                                | 7 ft Fixed Length   | 18 $\frac{1}{2}$ in                              | 41D504   |
| 2,500 lb                                | 15 ft Fixed Length, Hook Adjusts 12 ft to 15 ft           | 41 $\frac{3}{4}$ in                              | 41D507   |
| 4,000 lb                                | 8 ft Fixed Length, Hook Adjusts 4 ft to 8 ft              | 20 $\frac{1}{4}$ in                              | 41D506   |
| <b>Pivoting Forklift Booms</b>          |   |  |          |
| <b>Telescoping</b>                      |   |  |          |
| 3,000 lb                                | Boom Hook 3ft to 6 ft, Lifting Hook 7 ft to 12 ft         | 22 in Outside Edge to Outside Edge               | 426G83   |
| 4,000 lb                                | 7 ft to 12 ft Adjustable in 1 ft Increments               | 22 $\frac{1}{2}$ in                              | 9PR23    |
| 6,000 lb                                |   | 22 $\frac{1}{2}$ in                              | 9CHT4    |
| 8,000 lb                                |   | 22 $\frac{1}{2}$ in                              | 9KZ2E    |
| <b>Reach Over Forklift Boom</b>         |   |  |          |
| <b>Fixed Length</b>                     |   |  |          |
| 4,000 lb                                | 4ft to 6 ft, Adjustable in 1 ft Increments                | 20 in  | 41D511   |
| <b>Precision Lifting Forklift Booms</b> |   |  |          |
| <b>Telescoping</b>                      |   |  |          |
| 6,000 lb                                | Boom Hook 3ft to 6 ft, Lifting Hook 7 ft to 12 ft         | 22 $\frac{1}{2}$ in                              | 41D509   |
| <b>Fixed Length</b>                     |   |  |          |
| 2,500 lb                                | 12 ft to 14 ft Boom Hook, 15 ft Fixed Length Lifting Hook | 41 $\frac{3}{4}$ in                              | 41D510   |
| 6,000 lb                                | Boom Hook 3ft to 6 ft, Lifting Hook 7 ft to 12 ft         | 22 $\frac{1}{2}$ in Outside Edge to Outside Edge | 41D508   |

**Fork Truck Rams**

Can be fork mounted with 7 $\frac{1}{2}$ "W x 2 $\frac{1}{2}$ "H fork pockets or carriage mounted with spring-loaded lock pin. Sturdy steel construction.

**Coil Lifting Rams**—Transport a variety of types of coiled materials and accommodate multiple core sizes.

| Load Capacity                | Pole Length | Pole Dia.          | Carriage Class | Item No. |
|------------------------------|-------------|--------------------|----------------|----------|
| <b>Coil Lifting Rams</b>     |             |                    |                |          |
| <b>Fork Mounted-Inverted</b> |             |                    |                |          |
| 3,000 lb                     | 24 in       | 4 $\frac{1}{2}$ in | —              | 5UET5    |
|                              | 36 in       | 4 $\frac{1}{2}$ in | —              | 5UET7    |
|                              | 48 in       | 4 $\frac{1}{2}$ in | —              | 5UET9    |
|                              | 60 in       | 4 $\frac{1}{2}$ in | —              | 5UEU1    |
| 5,500 lb                     | 24 in       | 5 $\frac{1}{2}$ in | —              | 5UET6    |
|                              | 36 in       | 5 $\frac{1}{2}$ in | —              | 5UET8    |
|                              | 48 in       | 5 $\frac{1}{2}$ in | —              | 5UEU0    |
|                              | 60 in       | 5 $\frac{1}{2}$ in | —              | 5UEU2    |
| <b>Carriage Mounted</b>      |             |                    |                |          |
| 3,000 lb                     | 24 in       | 4 $\frac{1}{2}$ in | 2              | 5UEU3    |
|                              | 36 in       | 4 $\frac{1}{2}$ in | 2              | 5UEU5    |
|                              | 48 in       | 4 $\frac{1}{2}$ in | 2              | 5UEU7    |
|                              | 60 in       | 4 $\frac{1}{2}$ in | 2              | 5UEU9    |
| 5,500 lb                     | 24 in       | 5 $\frac{1}{2}$ in | 2              | 5UEU4    |
|                              | 36 in       | 5 $\frac{1}{2}$ in | 2              | 5UEU6    |
|                              | 48 in       | 5 $\frac{1}{2}$ in | 2              | 5UEU8    |
|                              | 60 in       | 5 $\frac{1}{2}$ in | 2              | 5UEU0    |

**Carpet Lifting Rams**—High-strength, rotatable poles with tapered tips move rolls of carpet or rugs. Replaceable.

| Load Capacity                | Pole Length          | Pole Dia.          | Carriage Class | Item No. |
|------------------------------|----------------------|--------------------|----------------|----------|
| <b>Carpet Lifting Rams</b>   |                      |                    |                |          |
| <b>Fork Mounted-Inverted</b> |                      |                    |                |          |
| 1,800 lb                     | 144 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5PVK0    |
| 2,200 lb                     | 120 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5PVJ9    |
| 2,500 lb                     | 108 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5PVJ8    |
| <b>Fork Mounted</b>          |                      |                    |                |          |
| 1,800 lb                     | 144 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5UEV3    |
| 2,200 lb                     | 120 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5UEV2    |
| 2,500 lb                     | 108 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | —              | 5UEV1    |
| <b>Carriage Mounted</b>      |                      |                    |                |          |
| 1,800 lb                     | 144 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 2              | 5UEV6    |
| —                            | 144 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 3              | 5UEV9    |
| 2,200 lb                     | 120 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 2              | 5UEV5    |
| —                            | 120 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 3              | 5UEV8    |
| 2,500 lb                     | 108 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 2              | 5UEV4    |
| —                            | 108 $\frac{1}{2}$ in | 2 $\frac{3}{4}$ in | 3              | 5UEV7    |



Sign in to **Grainger.com®** to see **YOUR Pricing** and **MORE**