

NSF-Listed Sanitary Stem Casters

Castors satisfy the National Sanitation Foundation's (NSF) rigorous testing requirements for use in environments where sanitary conditions must be maintained. Mount on carts, prep tables, food-service equipment, racks, and similar items that will be exposed to frequent washdowns, oils, or chemicals. All are swivel casters and can rotate 360°.

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	SWIVEL CASTER Item No.	SWIVEL CASTER WITH BRAKE Item No.
Friction-Ring Stem					
Thermoplastic Rubber Tread					
5"	325 lb	6"	1/4" x 2 3/16"	32J812	—
Rubber Tread					
2"	75 lb	2 29/64"	7/16" x 1 3/8"	20TM13	—
3"	100 lb	3 9/16"	1/4" x 1 29/32"	20TM15	—
	100 lb	3 9/16"	7/16" x 1 3/8"	20TM14	—
3 1/2"	150 lb	4 9/16"	7/16" x 1 29/32"	32J833	—
	150 lb	4 9/16"	7/16" x 1 3/8"	32J842	—
	115 lb	4 9/8"	1/4" x 1 29/32"	20TM16	—
4"	150 lb	5"	7/16" x 1 1/4"	487G42	—
	150 lb	5"	1/4" x 1 1/8"	487G40	—
	150 lb	6 1/16"	3/8" x 2 1/2"	487G50	487G58 *
	200 lb	5 13/16"	1" x 2 1/2"	32J941	—
	200 lb	6 1/16"	7/16" x 1 1/8"	32J835	—
Polyurethane Tread					
3"	135 lb	3 9/16"	7/16" x 1 3/8"	20TM19	—
3 1/2"	325 lb	4 9/16"	7/16" x 1 1/8"	487G44	—
4"	350 lb	4 13/16"	7/16" x 1 3/8"	32J848	—
	350 lb	4 13/16"	7/16" x 1 29/32"	32J840	—
	250 lb	5 13/16"	1" x 2 1/2"	32J814	—
	250 lb	5 13/16"	7/16" x 2 3/16"	32J813	—
	300 lb	5 13/16"	2 1/2" x 2 3/16"	—	32J933
5"	300 lb	6 1/16"	7/16" x 1 3/8"	32J849	—
	300 lb	6 1/16"	7/16" x 1 3/8"	32J841	—
	300 lb	6 1/16"	7/16" x 2 3/16"	20TM20	—
	325 lb	6 1/16"	7/16" x 2 1/8"	487G52	—
Polyolefin Tread					
3 1/2"	230 lb	4 9/16"	7/16" x 1 1/8"	487G43	—
	250 lb	4 9/16"	7/16" x 1 3/8"	32J839	—
4"	275 lb	5"	7/16" x 1 3/8"	32J846	—
	275 lb	5"	7/16" x 1 1/8"	487G41	—
5"	300 lb	6 1/16"	7/16" x 1 3/8"	32J838	—
Threaded Stem					
Thermoplastic Rubber Tread					
3"	210 lb	4"	3/8"-16 x 1"	20TM55	—
4"	300 lb	4 13/16"	1/2"-13 x 1 1/2"	32J828	—

* With total lock.



**Friction Ring Stem
w/ Total Lock
487G58**



**Threaded Stem
20TM22**

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	SWIVEL CASTER Item No.	SWIVEL CASTER WITH BRAKE Item No.
Rubber Tread					
2"	75 lb	2 29/64"	3/8"-16 x 1 1/8"	20TM12	—
	75 lb	2 1/4"	1/2"-13 x 1 1/8"	20TM49	—
3"	100 lb	3 3/8"	1/2"-13 x 1 1/2"	20TM50	—
3 1/2"	160 lb	4 3/8"	1/2"-13 x 1 1/2"	32J821	—
	160 lb	4 39/64"	3/8"-16 x 2 1/2"	20TM32	20TM31
	115 lb	4 13/16"	1/2"-13 x 1 1/2"	20TM51	—
	115 lb	4 13/16"	1/2"-13 x 1 1/2"	20TM52	—
4"	170 lb	4 13/16"	1/2"-13 x 1 1/2"	32J822	—
	170 lb	4 13/16"	1/2"-13 x 2 1/2"	32J935	32J927
	170 lb	5"	1/2"-13 x 2 1/2"	20TM33	—
	200 lb	5 13/16"	1/2"-13 x 2 1/2"	32J936	32J928
5"	200 lb	6 1/4"	1/2"-13 x 2 1/2"	20TM35	20TM30
	200 lb	6"	1/2"-13 x 1 1/2"	32J823	—
Polyurethane Tread					
3"	300 lb	4 1/8"	1/2"-13 x 3/4"	487G45	—
	250 lb	4 39/64"	1/2"-13 x 2 1/2"	20TM22	20TM23
3 1/2"	250 lb	4 3/8"	1/2"-13 x 1 1/2"	32J830	—
	350 lb	4 39/64"	1/2"-13 x 1 1/2"	20TM21	—
	275 lb	5"	1/2"-13 x 1 1/2"	20TM24	—
4"	275 lb	5"	1/2"-13 x 2 1/2"	20TM25	20TM26
	350 lb	4 13/16"	1/2"-13 x 3/4"	32J819	—
	350 lb	4 13/16"	1/2"-13 x 2 1/2"	32J981	32J982
	300 lb	6 1/16"	1/2"-13 x 2 1/2"	20TM28	20TM29
	325 lb	6 1/16"	1/2"-13 x 3/4"	487G46	—
5"	350 lb	5 13/16"	1/2"-13 x 2 1/2"	32J983	—
	350 lb	6"	1/2"-13 x 3/4"	32J820	—
	350 lb	6 1/4"	1/2"-13 x 1 1/2"	20TM27	—
Polyolefin Tread					
3"	350 lb	3 3/8"	1/2"-13 x 3/4"	20TM58	—
	350 lb	3 7/8"	1/2"-13 x 2 1/2"	20TM59	—
3 1/2"	250 lb	4 3/8"	1/2"-13 x 3/4"	32J815	—
	250 lb	4 3/8"	1/2"-13 x 1 1/2"	32J824	—
	275 lb	5"	1/2"-13 x 1 1/2"	20TM36	—
4"	350 lb	4 13/16"	1/2"-13 x 1 1/2"	32J825	—
	350 lb	4 13/16"	1/2"-13 x 3/4"	32J816	—
5"	350 lb	6"	1/2"-13 x 1 1/2"	32J826	—

Corrosion- and Debris-Resistant Stem Casters

Antimicrobial casters have wheels that are impregnated with an antimicrobial compound that prevents damaging or odor-causing microbes from growing on them. **Corrosion-resistant** casters will not rust or corrode in environments when exposed to water or cleaning chemicals. **Debris-resistant** casters have a thread guard that stops debris from getting inside the caster and damaging or contaminating it. Suitable for racks, carts, and other equipment that will be used in areas where the casters will be exposed to dirt or frequent washdowns, such as laundry rooms, textile factories, food-service facilities, restaurants, offices, government buildings, and schools. All are swivel casters and can rotate 360°.

Wheel Dia.	Load Rating	Mounting Height	Caster Stem Size	Wheel Bearing Type	SWIVEL CASTER Item No.	SWIVEL CASTER WITH BRAKE Item No.
Antimicrobial Corrosion- & Debris-Resistant Expanding Stem						
Thermoplastic Rubber Tread						
3"	165 lb	4 1/16"	1/2"-13 x 2 1/4"	Precision Ball	455U23	455U39 *
4"	190 lb	5 1/16"	1/2"-13 x 2 1/4"	Precision Ball	455U27	455U33 *
5"	220 lb	6 1/16"	1/2"-13 x 2 1/4"	Precision Ball	455U25	455U40 *
6"	240 lb	7 1/16"	1/2"-13 x 2 1/4"	Precision Ball	455U41	455U34 *
Corrosion- & Debris-Resistant Threaded Stem						
Polyolefin Tread						
3"	110 lb	4 5/16"	3/18"-16 x 3/4"	Delrin	429H21	429H22
	110 lb	4 5/16"	5/16"-18 x 1"	Delrin	429H19	429H20
Debris-Resistant Friction-Ring Stem						
Polyurethane Tread						
5"	300 lb	5 13/16"	27/32" x 2 3/16"	Precision Ball	32J932	—
Debris-Resistant Threaded Stem						
Thermoplastic Rubber Tread						
5"	280 lb	6 1/4"	1/2"-13 x 1"	Precision Ball	29XW85	—

* With total lock.



**Antimicrobial
Expanding Stem
w/ Total Lock
455U33**



**Debris-Resistant
Friction-Ring
32J932**

CAD DRAWINGS Available Online

Grainger's CAD capability lets you download 2D drawings and 3D CAD files in your choice of format.

> CAD available on select products.
Go to Grainger.com

