



2KMA7



## Leveling Jacks

Designed for permanent installation, these screw-style jacks hold platforms and portable equipment in place and keep them stabilized. Typically, for use with work platform applications. Include folding crank handle.

Cap. (lb.)	Overall H (in.)	Min. Height Below Equip Frame (in.)	Max. Extended Height Below Equip Frame (in.)	Screw Travel	Finish	Item No.
5,000 lb	18 in	4 1/2 in	13 1/2 in	9 in	Stainless Steel	2KMA7
5,000 lb	26 in	4 1/2 in	21 1/2 in	17 in	Stainless Steel	2KMA8
5,000 lb	30 in	4 1/2 in	25 1/2 in	21 in	Chrome	2KMA6
5,000 lb	30 in	4 1/2 in	25 1/2 in	21 in	Stainless Steel	2KMA9



1XEX1



29AU76



## Threaded Tube Ends

Material is glass-fiber reinforced polyamide based (PA) technopolymer. Resistant to solvents, oils, grease, and other chemical agents. Standard execution. Brass boss, threaded pass-through hole. Black matte finish.

Tube Wall Size	Brand	Outside Dia.	ROUND Load Capacity	Item No.	Outside Dia.	SQUARE Load Capacity	Item No.
<b>1 in Thread Size</b>							
0.079 in	Elesa	1.75 in	1,232 lb	29AU90	—	—	—
<b>3/8-16 Thread Size</b>							
0.065 in	S & W	1.5 in	1,500 lb	1XEY1	1 1/2 in sq	1,500 lb	1XEX1
	Elesa	—	—	—	1.5 in	1,344 lb	29AU81
<b>1/2-13 Thread Size</b>							
0.065 in	S & W	1.5 in	1,500 lb	1XEY2	1 1/2 in sq	1,500 lb	1XEX2
	S & W	2 in	2,000 lb	1XEY4	2 in sq	2,000 lb	1XEX6
	Elesa	1.5 in	1,120 lb	29AU85	—	—	—
0.12 in	S & W	—	—	—	1 1/2 in sq	1,500 lb	1XEX4
	S & W	—	—	—	2 in sq	2,000 lb	1XEX7
	Elesa	—	—	—	1.5 in	1,344 lb	29AU82
<b>27/49 Thread Size</b>							
0.079 in	Elesa	1.181 in	1,008 lb	29AU77	1.378 in	1,344 lb	29AU75
	Elesa	1.654 in	1,120 lb	29AU79	—	—	—
<b>5/8-11 Thread Size</b>							
0.065 in	S & W	1.5 in	1,500 lb	1XEY3	1 1/2 in sq	1,500 lb	1XEX3
	Elesa	1.5 in	1,120 lb	29AU86	1.5 in	1,344 lb	29AU83
0.079 in	Elesa	1.75 in	1,232 lb	29AU88	—	—	—
0.12 in	S & W	—	—	—	1 1/2 in sq	1,500 lb	1XEX5
	S & W	—	—	—	2 in sq	2,000 lb	1XEX8
<b>3/4-10 Thread Size</b>							
0.065 in	Elesa	1.5 in	1,120 lb	29AU87	1.5 in	1,792 lb	29AU80
0.079 in	Elesa	1.75 in	1,232 lb	29AU89	—	—	—
0.12 in	S & W	—	—	—	2 in sq	2,000 lb	1XEX9
	Elesa	—	—	—	1.5 in	1,792 lb	29AU84
<b>42/89 Thread Size</b>							
0.079 in	Elesa	1.181 in	1,008 lb	29AU76	1.378 in	1,344 lb	29AU74
<b>M12 Thread Size</b>							
0.079 in	Elesa	1.654 in	1,120 lb	29AU78	1.181 in	1,008 lb	29AU72
<b>M14 Thread Size</b>							
0.079 in	Elesa	—	—	—	1.181 in	1,008 lb	29AU73



4NYH2



4TRY5



## Bottless Leveling Mounts

**Level-It™**—Choose from steel, nonskid steel, stainless steel, and Delrin® base. See Grainger.com® for additional leveling mounts.

**PolyMount™**—Polyglass-filled nylon base is corrosion-resistant. Lag holes allow permanent floor mounting. For washdown applications. See Grainger.com® for additional leveling mounts.

Base Dia. Level-It	H	Hex	Load Capacity	Base	Finish	Item No.
<b>1/4-20</b>						
1 in	0.8125 in	1/2 in	200 lb	Delrin(R)	Stainless Steel	4TPW8
		1/2 in	750 lb	Steel w/ Non-Skid Pad	Yellow Zinc	4NYH2
<b>3/8-16</b>						
1 1/4 in	0.875 in	5/8 in	3750 lb	Steel	Black Oxide	20KK61
		5/8 in	3750 lb		Yellow Zinc	26377
		5/8 in	3750 lb		Nickel	26378
1 1/4 in	1 in	5/8 in	300 lb	Delrin(R) w/ Non-Skid Pad	Yellow Zinc	4TPW3
		5/8 in	1800 lb	Steel w/ Non-Skid Pad	Yellow Zinc	4NYH3
		5/8 in	1800 lb		Nickel	4TVF9
<b>1/2-13</b>						
1 1/2 in	1.125 in	3/4 in	700 lb	Delrin(R)	Yellow Zinc	4NYU4
		3/4 in	5000 lb		Yellow Zinc	26379
		3/4 in	5000 lb	Steel	Nickel	26380
1 1/2 in	1.25 in	3/4 in	5000 lb		Black Oxide	20KK62
		3/4 in	700 lb	Delrin(R) w/ Non-Skid Pad	Stainless Steel	4TPX7
		3/4 in	3750 lb	Steel w/ Non-Skid Pad	Yellow Zinc	4NYH4
		3/4 in	3750 lb		Nickel	4TVF1
<b>5/8-11</b>						
2 1/2 in	1.25 in	7/8 in	6000 lb	Steel	Yellow Zinc	2G381
		7/8 in	6000 lb		Nickel	2G382
		7/8 in	6000 lb		Black Oxide	20KK63
2 1/2 in	1.375 in	7/8 in	1200 lb	Delrin(R) w/ Non-Skid Pad	Stainless Steel	4TPX8
		7/8 in	4500 lb	Steel w/ Non-Skid Pad	Yellow Zinc	4NYH5
<b>3/4-10</b>						
3 in	1.5 in	1 1/8 in	7400 lb		Yellow Zinc	2G383
		1 1/8 in	7400 lb	Steel	Nickel	2G384
		1 1/8 in	7400 lb		Black Oxide	20KK64
3 in	1.625 in	1 1/8 in	5550 lb	Steel w/ Non-Skid Pad	Yellow Zinc	4NYH6
		1 1/8 in	5550 lb		Nickel	4TVF3
		1 1/8 in	5550 lb	Stainless Steel w/ Non-Skid Pad	Stainless Steel	4NYJ3
<b>1-8</b>						
4 in	1.875 in	1 3/8 in	20,000 lb	Steel	Yellow Zinc	2G385
<b>MB</b>						
1 in	0.8125 in	1/2 in	1000 lb	Stainless Steel	Stainless Steel	14H426
<b>M16</b>						
2 1/2 in	1.375 in	7/8 in	6000 lb	Stainless Steel	Stainless Steel	14H429
<b>M20</b>						
3 in	1.625 in	1 1/8 in	7400 lb	Steel	Yellow Zinc	14H424
		1 1/8 in	7400 lb	Stainless Steel	Stainless Steel	14H430
<b>M24</b>						
4 in	2 in	1 3/8 in	20,000 lb	Steel	Yellow Zinc	14H425
<b>PolyMount</b>						
<b>3/8-16</b>						
2 in	1.4375 in	5/8 in	4000 lb	Nylon	Clear Zinc	4TRX4
		3/4 in	4000 lb		Stainless Steel	4TR99
		1.5 in	3000 lb	Nylon w/ Non-Skid Pad	Clear Zinc	4TTA5
4 in	1.6875 in	3/4 in	3750 lb		Stainless Steel	4TDT5
<b>5/8-11</b>						
3 in	1.6875 in	7/8 in	5000 lb	Nylon	Clear Zinc	4TRX7
4 in	1.875 in	7/8 in	6000 lb		Clear Zinc	4TR11
	1.9375 in	7/8 in	4500 lb	Nylon w/ Non-Skid Pad	Clear Zinc	4TTC2
<b>3/4-10</b>						
4 in	2 in	1 1/8 in	7500 lb	Nylon	Stainless Steel	4TR27
5 in	3 in	1 1/8 in	10,000 lb		Clear Zinc	4TRY5
<b>1-8</b>						
5 in	3.3125 in	1 3/8 in	7500 lb	Nylon w/ Non-Skid Pad	Stainless Steel	4TTE3