1-800-GRAINGER (472-4643)


SHELVING & STORAGE Machine Guards



Welox Hinged Door

Includes installation hardware

Easy-to-assemble barriers protect workers from dangerous machinery, equipment, and robotic cells. 8-ga. panels are welded to a 2" x 2" wire grid pattern. Order panels separately. Use hook fasteners and drive pins (included) to fasten into a 16-ga. 2½" square steel post. Components come with welded footplates and anchor bolts. System installs 50% faster than most other wire guarding products and is easily modified to accommodate field obstructions.




	De	scription		н	w	ltem No.
Doors						
	en Sliding			6 ft	5 ft	48RN11
	pen Slidir			6 ft	5 ft	48RN12
	Welded-Wire Machine Guard Door			66 in	2 ft 10 in	6TMK9
	Welded-Wire Machine Guard Door			6 ft	3 ft 10 in	6TML0
Machin	e Guard C	Cut-Down Panel	Kit	—	—	6TML6
		ltem				Item
н	W	No.		Description	н	No.
Machin	e Guard P	anels	Posts	· · · · · · · · · · · · · · · · · · ·		
6 ft	10 in	23PC13	Corner		6 ft	6TMK6
6 ft	22 in	23PC14		oor Post	6 ft	48RN13
6 ft	34 in	23PC15	Swing	Door Post	6 ft	6TMK7
6 ft	46 in	23PC16	Adjusta	able Corner Post	6 ft	6TMK8
6 ft	58 in	23PC17				
6 ft	70 in	23PC18				
6 ft	82 in	23PC19				
6 ft	94 in	23PC20				



Steel Folding Dock Gates

34" x 34" 15-ga. U-channels riveted back-to-back construction. Equipped with self-securing center drop-in pin. 12-ga. steel vertical gate rails are $1\frac{1}{2}$ " x $1\frac{1}{2}$ ". Universal mounting on face or in casing. Powder-coated finish. Include brackets, bearing washers, casters, and lock lugs. Padlocks not included.

Opening Width	Folded Height		In Use Height	ltem No.	Opening Width	Folded Height	Folded Width	In Use Height	ltem No.
Single					Double				
3 to 4 ft	6 ½ ft	7 ft	6 ft	54XU44	6 to 8 ft	6 ½ ft	7 ft	6 ft	54XU47
5 to 6 ft	6 ½ ft	7 ft	6 ft	54XU43	8 to 10 ft	11 in	6 ft	6 ft	54XU57
6 to 7 ft	6 ft	7 ft	6 ft	54XU42	0 10 10 11	11 in	7 ft	7 ft	54XU56
	8 ½ ft	11 in	8 ft	54XU38	10 to 12 ft		11 in	6 ft	54XU55
	11 in	7 ft	6½ ft	54XU41	12 to 14 ft	: 7 ½ ft	7 ft	7 ft	54XU54
	11 in	7 ft	7 ft	54XU40	14 to 16 ft		7 ft	6 ft	54XU53
	11 in	7 ft	71⁄2 ft	54XU39		11 in	7 ft	7 ft	54XU51
7 to 8 ft	6 ft	6 ½ ft	6 ft	54XU37	16 to 18 ft		7 ft	6½ ft	54XU52
	11 in	7 ft	61⁄2 ft	54XU36		15 in	7 ft	71⁄2 ft	54XU50
	11 in	7 ½ ft	7 ft	54XU35	18 to 20 ft	. 15 in	7 ft	6½ ft	54XU49
	11 in	8 ft	71⁄2 ft	54XU34		15 in	7 ft	71⁄2 ft	54XU48
	11 in	8 ft	81⁄2 ft	54XU33	Portable	Single			
8 to 9 ft	7 ft	15 in	61⁄2 ft	54XU32	6 to 7 ft	6 ½ ft	6 ½ ft	6 ft	54XU28
	8 ft	15 in	71⁄2 ft	54XU30	Portable				
	11 in	7 ft	7 ft	54XU31	1 to 12 ft	6 ½ ft	6 ft 6 in	6 ft	54XU29
9 to 10 ft	7 ft	15 in	61⁄2 ft	54XU46					
	8 ft	15 in	71/6 ft	54X1145					



Machine Guard System

Up to 12" sweep. Panel system is held in place with pins, brackets, and safety nuts. Can be reconfigured. All-steel, welded-wire post. Lockable hinged doors. Includes safety socket wrench.

Н	w	ltem No.	н	w	ltem No.
Wire Partition P	anels		Posts		
	2 ft	19N873	Line Posts		
	3 ft	19N872	6 ft	2 in	19N876
5 ft	4 ft	19N871	8 ft	2 in	19N874
	5 ft	19N870	Offset Post		
	8 ft	19N869	8 ft	2 in	19N875
	2 ft	19N868	Corner Post		
7 ft	3 ft	19N867	6 ft	2 in	19N877
7 11	4 ft	19N866	Doors		
	5 ft	19N865	5 ft	4 ft	19N880
			7 ft -	3 ft	19N879
			7 11 -	4 ft	19N878


Panel 19H220


Saf-T-Fence Machine Perimeter Guarding


- Economical alternative to permanent walls
- Combines security, strength, and flexibility

An all-steel, modular system of panels, posts, and hinged doors protect machinery, employees, and visitors. Easy to assemble with interchangeable panels and posts. 10-ga. welded wire mesh with $11/4" \times 21/2"$ grid openings welded to $11/2" \times 11/2" \times 14$ -ga. steel angle frames.

ungio munico.						
Overall Height	Overall Width	ltem No.				
Panels						
	10 in	19H236				
	16 in	19H238				
	19 in	19H240				
	22 in	19H220				
58 in	28 in	19H243				
10 00	34 in	19H221				
	46 in	19H222				
	58 in	19H223				
	70 in	19H245				
	94 in	19H224				
	10 in	19H237				
	16 in	19H239				
	19 in	19H241				
82 in	22 in	19H225				
02 111	28 in	19H244				
	34 in	19H226				
	48 in	19H227				
	58 in	19H228				
Posts						
5.3 ft	3 in	19H232				







Sign in to Grainger.com® to see YOUR Pricing and MORE