

CONTINUED

Capacitor-Start/Run NEMA Frame Cradle & Rigid Base-Mount Motors



HP	Nameplate RPM	Frame	Motor Thermal Protection	Voltage	Full Load Amps	Motor Service Factor	Ins. Class	Nom. Efficiency	Shaft Dia.	Shaft Length	Overall Length	Brand	Mr. Model	Item No.
1-Speed (Cont.)														
Open Dripproof with Rigid Base-Mount (Cont.)														
¾	3.450	48	Auto	115/208-230V AC	7.2/4.0-3.6	1.25	B	76.2 %	½ in	1 ½ in	11 ½ in	Dayton	20CL59	20CL59 ‡
	3.450	48	None	115/208-230V AC	7.2/4.0-3.6	1.25	B	76.2 %	½ in	1 ½ in	11 ½ in	Dayton	20CL55	20CL55 ‡
	3.450	56	Auto	115/208-230V AC	7.2/4.0-3.6	1.25	B	76.2 %	¾ in	1 ½ in	11 ½ in	Dayton	20VD15	20VD15 ‡
	3.450	56	None	115/208-230V AC	7.2/4.0-3.6	1.25	B	76.2 %	¾ in	1 ½ in	11 ½ in	Dayton	20VD20	20VD20 ‡
	1.725	56	Auto	115/208-230V AC	6.6/3.5-3.3	1.25	B	81.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR73	31TR73 ‡
	1.725	56	Manual	115/208-230V AC	6.6/3.5-3.3	1.25	B	81.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR74	31TR74 ‡
1	1.725	56H	None	115/208-230V AC	6.6/3.5-3.3	1.25	B	81.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR72	31TR72 ‡
	1.140	56H	None	115/208-230V AC	6.7/3.7-3.4	1.15	B	80.2 %	¾ in	1 ½ in	13 ½ in	Dayton	31T06	31T06 ‡
	3.450	56	Auto	115/208-230V AC	8.8/4.9-4.4	1.25	B	80.4 %	¾ in	1 ½ in	12 ¾ in	Dayton	31TR94	31TR94 ‡
	3.450	56	Manual	115/208-230V AC	8.8/4.9-4.4	1.25	B	80.4 %	¾ in	1 ½ in	12 ¾ in	Dayton	31T04	31T04 ‡
	3.450	56	None	115/208-230V AC	8.8/4.9-4.4	1.25	B	80.4 %	¾ in	1 ½ in	12 ¾ in	Dayton	31T03	31T03 ‡
	1.725	56H	Auto	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR80	31TR80 ‡
1 ½	1.725	56H	Manual	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR87	31TR87 ‡
	1.725	56H	None	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	1 ½ in	12 ¾ in	Dayton	31TR75	31TR75 ‡
	1.725	56HZ	Auto	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	2 ¼ in	13 in	Dayton	31TR77	31TR77 ‡
	1.725	56HZ	Manual	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	2 ¼ in	13 in	Dayton	31TR86	31TR86 ‡
	1.725	56HZ	None	115/208-230V AC	8.4/4.6-4.2	1.15	B	82.6 %	¾ in	2 ¼ in	13 ¼ in	Dayton	31TR81	31TR81 ‡
	3.450	56H	Auto	115/208-230V AC	13.6/7.0-6.8	1.15	B	81.5 %	¾ in	1 ½ in	12 ½ in	Dayton	31TR98	31TR98 ‡
2	3.450	56H	Manual	115/208-230V AC	13.6/7.0-6.8	1.15	B	81.5 %	¾ in	1 ½ in	12 ½ in	Dayton	31TR97	31TR97 ‡
	3.450	56H	None	115/208-230V AC	13.6/7.0-6.8	1.15	B	81.5 %	¾ in	1 ½ in	12 ½ in	Dayton	31TR99	31TR99 ‡
	1.725	56H	Auto	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR83	31TR83 ‡
	1.725	56H	Manual	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR78	31TR78 ‡
	1.725	56H	None	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	1 ½ in	13 ½ in	Dayton	31TR76	31TR76 ‡
	1.725	56HZ	Auto	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	2 ¼ in	13 ¾ in	Dayton	31TR79	31TR79 ‡
3	1.725	56HZ	Manual	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	2 ¼ in	13 ¾ in	Dayton	31TR85	31TR85 ‡
	1.725	56HZ	None	115/208-230V AC	12.6/6.9-6.3	1.15	B	83.8 %	¾ in	2 ¼ in	13 ¾ in	Dayton	31TR82	31TR82 ‡
	3.450	56H	Auto	115/208-230V AC	17.8/9.2-8.9	1.15	B	82.9 %	¾ in	1 ½ in	11 ½ in	Dayton	31T01	31T01 ‡
	3.450	56H	Manual	115/208-230V AC	17.8/9.2-8.9	1.15	B	82.9 %	¾ in	1 ½ in	11 ½ in	Dayton	31T05	31T05 ‡
	3.450	56H	None	115/208-230V AC	17.8/9.2-8.9	1.15	B	82.9 %	¾ in	1 ½ in	12 ½ in	Dayton	31T02	31T02 ‡
	3.450	145T	None	115/208-230V AC	17.5/9.3-8.6	1.15	B	80 %	¾ in	2 ¼ in	13 ¼ in	Dayton	6K631	6K631 ‡
5	1.725	56H	Auto	115/208-230V AC	17.6/9.5-8.8	1.15	B	84.8 %	¾ in	1 ½ in	14 ¾ in	Dayton	31TR71	31TR71 ‡
	1.725	56H	None	115/208-230V AC	17.6/9.5-8.8	1.15	B	84.5 %	¾ in	1 ½ in	13 ¾ in	Dayton	31TR70	31TR70 ‡
	1.725	56HZ	Auto	115/208-230V AC	17.6/9.5-8.8	1.15	B	84.5 %	¾ in	2 ¼ in	14 ¾ in	Dayton	31TR88	31TR88 ‡
	1.725	56HZ	None	115/208-230V AC	17.6/9.5-8.8	1.15	B	84.5 %	¾ in	2 ¼ in	14 ¾ in	Dayton	31TR84	31TR84 ‡
	3.450	145T	None	115/230V AC	25.0/12.5	1.15	B	84.1 %	¾ in	2 ¼ in	13 ¾ in	Dayton	5JE13	5JE13 ‡
	1.745	215	None	115/230V AC	35.6/17.8	1.15	F	80.4 %	1 ½ in	3 in	16 ½ in	Dayton	5K483	5K483 ‡
7 ½	3.530	184T	None	230V AC	19.6	1.15	F	88.1 %	1 ½ in	2 ½ in	18 in	Dayton	6K633	6K633 ‡
	1.745	213T	None	230V AC	22.0	1.15	F	85 %	1 ½ in	3 ½ in	17 ½ in	Dayton	5K676	5K676 ‡
	1.740	184T	None	230V AC	20.0	1.15	F	84.2 %	1 ½ in	2 ¾ in	16 ¼ in	Dayton	6K854	6K854 ‡
10	3.530	213T	None	230V AC	30.3	1.15	F	89.3 %	1 ¾ in	3 ½ in	19 ½ in	Dayton	6K634	6K634 ‡
	1.740	215T	None	230V AC	35.5	1.15	F	85.4 %	1 ¾ in	3 ¾ in	19 ½ in	Dayton	5K677	5K677 ‡
10	1.740	215T	None	230V AC	42.2	1.15	F	88.2 %	1 ¾ in	3 ¾ in	19 ¾ in	Dayton	6K100	6K100 ‡
Totally Enclosed Fan-Cooled with Cradle Base-Mount														
¾	1.140	56H	Auto	115/230V AC	10.4/5.2	1	B	73.7 %	¾ in	1 ½ in	14 ¼ in	Dayton	5PHA8	5PHA8 ‡
	1	1.140	56H	Auto	115/230V AC	12.1/6.1	1	B	75.7 %	¾ in	1 ½ in	14 ¾ in	Dayton	5PHC0
Totally Enclosed Fan-Cooled with Rigid Base-Mount														
½	1.725	56	None	115/230V AC	5.8-5.6/2.9-2.8	1.25	B	72 %	¾ in	1 ½ in	11 ¾ in	Marathon	5KCR46MN0094	1K109
	1.140	56	None	115/208-230V AC	10.6/5.4-5.3	1	B	70 %	¾ in	1 ½ in	13 ¾ in	Dayton	5K672	5K672 ‡
¾	1.725	56	None	115/230V AC	9.0-8.8/4.5-4.4	1.25	B	72 %	¾ in	1 ½ in	12 ¾ in	Marathon	5KCR49PN0101	1K110
	1.140	56	None	115/230V AC	10.6/5.3	1	B	66 %	¾ in	1 ½ in	13 ¾ in	Marathon	5KCR48WN6066	2K599
1	1.140	56H	None	115/208-230V AC	10.6/5.4-5.3	1.15	B	73.6 %	¾ in	1 ½ in	13 ¾ in	Dayton	5UKF6	5UKF6 ‡
	1.725	56	None	115/230V AC	11.8-11.4/5.9-5.7	1.15	B	77.4 %	¾ in	1 ½ in	12 ½ in	Marathon	5KCR49UN0108	1K111
	1.725	56H	Auto	115/208-230V AC	9.9/5.2-5.0	1.15	B	77.7 %	¾ in	1 ½ in	12 ½ in	Dayton	6K562	6K562 ‡
	3.450	56H	Auto	115/208-230V AC	14.6/8.1-7.4	1	B	80.1 %	¾ in	1 ½ in	12 ¾ in	Dayton	6XJ53	6XJ53 ‡
	3.450	56H	Manual	115/208-230V AC	14.6/8.1-7.4	1	B	79.1 %	¾ in	1 ½ in	12 ¾ in	Dayton	6K338	6K338 ‡
	3.450	143T	None	115/208-230V AC	14.6/8.1-7.4	1	B	76.2 %	¾ in	2 ¼ in	13 ¼ in	Dayton	3K300	3K300 ‡
1 ½	1.725	56H	Auto	115/208-230V AC	14.4/8.0-7.2	1.15	B	81.2 %	¾ in	1 ½ in	13 ¾ in	Dayton	5K565	5K565 ‡
	1.725	56H	Manual	115/208-230V AC	14.4/8.0-7.2	1.15	B	81.2 %	¾ in	1 ½ in	13 ¾ in	Dayton	5K641	5K641 ‡
	1.725	56H	None	115/208-230V AC	14.4/8.0-7.2	1.15	B	79.3 %	¾ in	1 ½ in	13 ¾ in	Dayton	1K066	1K066 ‡
	1.725	56HZ	Auto	115/208-230V AC	14.4/8.0-7.2	1.15	B	81.5 %	¾ in	2 ¼ in	14 ¼ in	Dayton	5UKG0	5UKG0 ‡
	1.725	56HZ	Manual	115/208-230V AC	14.4/8.0-7.2	1.15	B	81.2 %	¾ in	2 ¼ in	14 ¼ in	Dayton	6K420	6K420 ‡
	1.725	56HZ	None	115/208-230V AC	14.4/8.0-7.2	1.15	B	81.2 %	¾ in	2 ¼ in	14 ¼ in	Dayton	6K419	6K419 ‡
2	1.725	145T	None	115/208-230V AC	14.4/8.0-7.2	1.15	B	80.9 %	¾ in	2 ¼ in	14 ¼ in	Dayton	6K828	6K828 ‡
	3.450	56H	Auto	115/208-230V AC	19.5/10.8-9.7	1.15	B	80 %	¾ in	1 ½ in	13 ¾ in	Dayton	5UKG3	5UKG3 ‡
	3.450	56H	Manual	115/208-230V AC	19.5/10.8-9.7	1	B	79.8 %	¾ in	1 ½ in	13 ¾ in	Dayton	5K961	5K961 ‡
	3.450	56H	None	115/208-230V AC	19.5/10.8-9.7	1	B	76.8 %	¾ in	1 ½ in	13 ¾ in	Dayton	5UKG4	5UKG4 ‡
	3.450	145T	None	115/208-230V AC	19.5/10.8-9.7	1	B	79.7 %	¾ in	2 ¼ in	14 ¼ in	Dayton	3K344	3K344 ‡
	1.725	56H	Auto	115/208-230V AC	18.9/10.3-9.4	1	F	79.6 %	¾ in	1 ½ in	14 ¾ in	Dayton	5UKG5	5UKG5 ‡
3	1.725	56H	None	115/208-230V AC	18.9/10.3-9.4	1	F	78.1 %	¾ in	1 ½ in	13 ¾ in	Dayton	1K067	1K067 ‡
	1.725	56HZ	Auto	115/230V AC	18.9/9.4	1	F	81.7 %	¾ in	2 ¾ in	14 ½ in	Dayton	5UKG6	5UKG6 ‡
	1.725	56HZ	None	115/208-230V AC	18.8/10.2-9.4	1	B	81.5 %	¾ in	1 ½ in	14 ½ in	Dayton	5UKG7	5UKG7 ‡
	3.540	182T	None	115/230V AC	32.0/16.0	1	F	79.2 %	1 ½ in	2 ¾ in	16 ¾ in	Dayton	6K145	6K145 ‡
	3.450	145T	None	230V AC	15.4	1	F	78.9 %	¾ in	2 ¾ in	15 in	Dayton	5UKG8	5UKG8 ‡
	1.740	184T	None	115/230V AC	30.0/15.0	1	F	81.9 %	1 ½ in	2 ¾ in	17 ¾ in	Dayton	5K967	5K967 ‡
5	3.540	184T	None	230V AC	19.6	1.15	F	82.2 %	1 ½ in	2 ¾ in	17 ¾ in	Dayton	6K146	6K146 ‡
	1.745	213T	None	230V AC	23.0	1	F	83.7 %	1 ¾ in	3 ¾ in	19 ¾ in	Dayton	5K968	5K968 ‡
	1.740	184T	None	230V AC	22.0	1	F	82.7 %	1 ½ in	2 ¾ in	18 ½ in	Dayton	2TJ12	2TJ12 ‡
7 ½	3.530	213												