

Imperial Tape WxL	Tape Thickness	Tape Backing Material*	Tape Adhesive Material	Environment	Tape Color	Temp. Range	Series	Brand	Item No.	Pkg. Qty.
General Purpose Duct Tape										
Heavy Duty										
1 in x 10-yd	17 mil	PECC	Rubber	Indoor/Outdoor	Black	30° to 150°F	—	Gorilla	16V093	1
1½ in x 10-yd	16.75 mil	PECC	Rubber	Indoor/Outdoor	Black	32° to 150°F	—	Gorilla	787ER3	1
1½ in x 39-yd	16 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	349	Nashua	15R434	1
1½ in x 60-yd	13 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	357	Nashua	15R452	1
	13 mil	PECC	Rubber	Indoor/Outdoor	Brown	40° to 200°F	357	Nashua	1P105	1
	13 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	357	Nashua	15R449	1
	13 mil	PECC	Rubber	Indoor/Outdoor	White	40° to 200°F	357	Nashua	15R447	1
2½ in x 60-yd	13 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	357	Nashua	15R453	1
	13 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	357	Nashua	15R446	1
	13 mil	PECC	Rubber	Indoor/Outdoor	Olive Drab	40° to 200°F	357	Nashua	15R450	1
	13 mil	PECC	Rubber	Indoor/Outdoor	White	40° to 200°F	357	Nashua	15R448	1
2½ in x 25-yd	17 mil	PECC	Rubber	Indoor/Outdoor	Black	30° to 150°F	—	Gorilla	5REA3	1
4 in x 60-yd	13 mil	PECC	Rubber	Indoor/Outdoor	Olive Drab	40° to 200°F	357	Nashua	15R451	1
Standard Duty										
¾ in x 60-yd	10.5 mil	CC	Rubber	Indoor/Outdoor	White	Up to 200°F	175	Tapecase	15C775	1
1½ in x 60-yd	11 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	398	Nashua	15R456	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	2280	—	26VC87	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	2280	Nashua	30F047	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	All-Climate	Nashua	3NJ25	1
1½ in x 60-yd	9 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	2280	Nashua	26VC89	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	2280	Nashua	26W990	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Green	40° to 200°F	2280	Nashua	30F052	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Red	40° to 200°F	2280	Nashua	30F053	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	394	Nashua	6JD46	1
	9 mil	PECC	Rubber	Indoor/Outdoor	White	40° to 200°F	2280	Nashua	26W993	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Yellow	40° to 200°F	2280	Nashua	26W994	1
	10 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	396	Nashua	5AD15	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	398	Nashua	15R465	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	398	Nashua	15R462	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Brown	40° to 200°F	398	Nashua	15R463	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Brown	40° to 200°F	398	Nashua	15R464	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	398	Nashua	2W504	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Green	40° to 200°F	398	Nashua	15R461	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Red	40° to 200°F	398	Nashua	15R457	1
2 in x 60-yd	11 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	365	Nashua	6A067	1
	11 mil	PECC	Rubber	Indoor/Outdoor	White	40° to 200°F	398	Nashua	15R455	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Yellow	40° to 200°F	398	Nashua	15R459	1
	12 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	345	Nashua	10C003	1
	12 mil	PECC	Rubber	Indoor/Outdoor	Olive Drab	40° to 200°F	231	Polyken	15R474	1
	12 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	345	Nashua	2W502	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	5640	Ability One	1XE85	1
	10 mil	PECC	Rubber	Indoor Only	Silver	40° to 200°F	6969	3M	15F769	1
2½ in x 60-yd	10.5 mil	CC	Rubber	Indoor/Outdoor	White	Up to 200°F	175	Tapecase	15C777	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	2280	—	26VC95	1
	10 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	396	Nashua	15R454	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	398	Nashua	15R442	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Brown	40° to 200°F	398	Nashua	15R441	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	398	Nashua	15R458	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Green	40° to 200°F	398	Nashua	15R440	1
	11 mil	PECC	Rubber	Indoor/Outdoor	White	40° to 200°F	398	Nashua	15R438	1
2 in x 25-yd	12 mil	PECC	Rubber	Indoor/Outdoor	Brown	40° to 200°F	231	Polyken	15R475	1
	12 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	345	Nashua	1P116	1
	9 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	2280	—	26VC96	1
	11 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	398	Nashua	15R460	1
Light Duty										
1 in x 50-yd	6.5 mil	VCC	Rubber	Indoor Only	Gray	40° to 200°F	3903	3M	15C919	1
	6.5 mil	VCC	Rubber	Indoor Only	Red	40° to 200°F	3903	3M	15C920	1
	6.5 mil	VCC	Rubber	Indoor Only	Yellow	40° to 200°F	3903	3M	15C922	1
1½ in x 50-yd	6.5 mil	VCC	Rubber	Indoor Only	Gray	40° to 200°F	3903	3M	15C931	1
	6.5 mil	VCC	Rubber	Indoor Only	Red	40° to 200°F	3903	3M	15C932	1
1½ in x 60-yd	6 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	306	—	26VC84	1
	6.5 mil	VCC	Rubber	Indoor Only	Black	40° to 200°F	3903	3M	15F770	1
2 in x 50-yd	6.5 mil	VCC	Rubber	Indoor Only	Blue	40° to 200°F	3903	3M	15F771	1
	6.5 mil	VCC	Rubber	Indoor Only	Gray	40° to 200°F	3903	3M	15F772	1
	6.5 mil	VCC	Rubber	Indoor Only	Green	40° to 200°F	3903	3M	15F773	1
	6.5 mil	VCC	Rubber	Indoor Only	Red	40° to 200°F	3903	3M	15F774	1
2 in x 25-yd	6.5 mil	VCC	Rubber	Indoor Only	White	40° to 200°F	3903	3M	15F775	1
	6.5 mil	VCC	Rubber	Indoor Only	Yellow	40° to 200°F	3903	3M	15F776	1
	0.7 mil	PECC	Rubber	Indoor/Outdoor	White	30° to 150°F	—	Gorilla	499L89	1
	6.5 mil	VCC	Rubber	Indoor Only	Black	40° to 200°F	3903	3M	15D152	1
4 in x 50-yd	6.5 mil	VCC	Rubber	Indoor Only	Red	40° to 200°F	3903	3M	15D156	1
	6.5 mil	VCC	Rubber	Indoor Only	White	40° to 200°F	3903	3M	15D157	1
	6.5 mil	VCC	Rubber	Indoor Only	Yellow	40° to 200°F	3903	3M	15D158	1
Transparent Repair Tape										
Standard Duty										
2 in x 9-yd	8.2 mil	EC	Acrylic	Indoor/Outdoor	Transparent	10° to 120°F	—	Gorilla	30WM01	1
Light Duty										
1½ in x 5-yd	7 mil	EC	Rubber	Indoor/Outdoor	Transparent	4° to 140°F	—	Gorilla	45DV43	1
2 in x 18-yd	7 mil	PEF	Acrylic	Indoor/Outdoor	Transparent	-5° to 140°F	—	Gorilla	55FJ92	1
2½ in x 36-yd	5.2 mil	VF	Rubber	Indoor Only	Transparent	-20° to 140°F	TC521	—	494K29	16
Clean Removal Duct Tape										
Standard Duty										
2 in x 60-yd	11.5 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	15F803	1
2 in x 25-yd	11.5 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	15F805	1
2 in x 60-yd	11.5 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	8979	3M	15F807	1
2½ in x 60-yd	12.1 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	39RW36	1
3½ in x 60-yd	11.5 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	45FD26	1
6 in x 60-yd	12.1 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	54EN73	6
12 in x 60-yd	12.1 mil	PECC	Rubber	Indoor/Outdoor	Blue	40° to 200°F	8979	3M	54EN51	2
UL-Printed Duct Tape										
Heavy Duty										
1½ in x 60-yd	14 mil	PECC	Rubber	Indoor/Outdoor	Black	40° to 200°F	557	Nashua	10A995	1
	14 mil	PECC	Rubber	Indoor/Outdoor	Gray	40° to 200°F	557	Nashua	10A996	1
	14 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	557	Nashua	6JD47	1
Flame Retardant Duct Tape										
Standard Duty										
1½ in x 60-yd	11.5 mil	PECC	Rubber	Indoor/Outdoor	Silver	40° to 200°F	235	Polyken	35UX90	24
Light Duty										
3 in x 36-yd	7 mil	GC	Acrylic	Indoor/Outdoor	White	40° to 275°F	296FR	Polyken	15R478	1

* PECC = polyethylene coated cloth. CC = cotton cloth. VCC = vinyl coated cloth. PPCC = polypropylene coated cloth. EC = ethylene copolymer. PEF = polyethylene film. VF = vinyl film. GC = glass cloth.

General Purpose
787ER3



General Purpose
26VC95



Transparent
Repair
30WM01



Clean Removal
15F807



UL-Printed
10A996



Flame Retardant
35UX90



Duct & Repair Tape

Tapes are high-strength, durable, and have an adhesive on one side that conforms and adheres to uneven surfaces when pressure is applied.

General Purpose Duct Tape—For general, temporary repair and patching, as well as labeling, marking, and wire pulling.

Transparent Repair Tape—For discreet patching and repair work such as covering a hole in a window screen, or mending a tear in a tent.

Clean Removal Duct Tape—Tape can be left in place and exposed to outdoor elements for up to six months before removing. For use in applications where temporary but durable taping is needed, such as seasonal weather sealing.

UL-Printed Duct Tape—This tape is used in HVAC applications to seal, seam, and join ductwork and provide evidence that the work is UL-compliant.

Flame Retardant Duct Tape—For use in high-temperature applications such as sealing ductwork, insulating wiring, and environments that require flame-retardant materials.

Nuclear Grade Duct Tape—For sealing and repairing in harsh environments, it resists corrosion that could result from exposure to harsh substances found in nuclear power plants, ship yards, and steel mills. It leaves little or no residue after being applied for six months and is useful for temporary sealing, insulating, or wrapping applications.

Metalized Duct Tape—Metalized coating blends with ductwork, foil-covered sheathing and insulation.

CONTINUED