

CONTINUED

Double-Sided VHB (Very High Bond) Foam Tape

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Tape Tensile Strength	Series	Item No.
Double-Sided VHB Very Conformable Foam Tape						
Black						
¾ in x 15 yd	¼ in	Acrylic Foam	50° to 300°F	90 lb/in	5952	1YBZ5
1 in x 36 yd	¼ in	Acrylic Foam	50° to 300°F	90 lb/in	5952	54EN23
Double-Sided VHB Conformable Foam Tape						
½ in x 5 yd	1.1 mm	—	50 °F to 300 °F	90 lb/in	5952	793Z92
¾ in x 5 yd	1.1 mm	—	50 °F to 300 °F	90 lb/in	5952	793Z94
Gray						
½ in x 5 yd	0.6 mm	Acrylic Foam	50 °F to 450 °F	91 lb/in	GPH-060GF	793ZA2
	½ in	Acrylic Foam	-31° to 194°F	90 lb/in	4936	15C325
	½ in	Acrylic Foam	-31° to 194°F	95 lb/in	4926	15C310
½ in x 36 yd	½ in	Acrylic Foam	60° to 200°F	85 lb/in	4941	15C332
	1.1 mm	Acrylic Foam	50 °F to 450 °F	97 lb/in	GPH-110GF	793ZA6
	½ in	Acrylic Foam	40° to 300°F	85 lb/in	4941	24A690
¾ in x 5 yd	½ in	Acrylic Foam	-31° to 194°F	90 lb/in	4936	15C329
	½ in	Acrylic Foam	-31° to 194°F	95 lb/in	4926	15C314
	1.6 mm	Acrylic Foam	50 °F to 450 °F	104 lb/in	GPH-160GF	793ZD4
1 in x 5 yd	0.6 mm	Acrylic Foam	50 °F to 450 °F	91 lb/in	GPH-060GF	793ZC0
	½ in	Acrylic Foam	-31° to 194°F	90 lb/in	4936	15C327
	½ in	Acrylic Foam	-31° to 194°F	95 lb/in	4926	15C312
2 in x 5 yd	½ in	Acrylic Foam	60° to 200°F	85 lb/in	4941	15C334
	½ in	Acrylic Foam	-31° to 194°F	70 lb/in	4991	15C339
	1.1 mm	Acrylic Foam	50 °F to 450 °F	97 lb/in	GPH-110GF	793ZC3
12 in x 5 yd	1.1 mm	Acrylic Foam	50 °F to 450 °F	104 lb/in	GPH-110GF	793ZC8
	1.6 mm	Acrylic Foam	50 °F to 450 °F	104 lb/in	GPH-160GF	793ZC9
	½ in	Acrylic Foam	60° to 200°F	85 lb/in	4941	15C333
	¾ in	Acrylic Foam	-31° to 194°F	70 lb/in	4991	15C398

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Tape Tensile Strength	Series	Item No.
White						
½ in x 5 yd	1.1 mm	Acrylic Foam	32 °F to 300 °F	68 lb/in	LSE-100WF	793Z86
	2 mm	—	50 °F to 300 °F	91 lb/in	4955	793Z99
¾ in x 5 yd	1.6 mm	Acrylic Foam	32 °F to 300 °F	63 lb/in	LSE-160WF	793Z98
	1.1 mm	Acrylic Foam	32 °F to 300 °F	68 lb/in	LSE-100WF	793Z90
1 in x 5 yd	1.6 mm	Acrylic Foam	32 °F to 300 °F	63 lb/in	LSE-160WF	793Z96
	1.1 mm	Acrylic Foam	32 °F to 300 °F	68 lb/in	LSE-100WF	793Z88
2 in x 5 yd	1.6 mm	Acrylic Foam	32 °F to 300 °F	63 lb/in	LSE-160WF	793Z97
	1.1 mm	Acrylic Foam	32 °F to 300 °F	68 lb/in	LSE-100WF	793Z89
Double-Sided VHB Firm Foam Tape						
Black						
½ in x 5 yd	½ in	Polyester Foam	Up to 200°F	160 lb/in	4929	15C316
¾ in x 5 yd	½ in	Polyester Foam	Up to 200°F	160 lb/in	4929	15C318
1 in x 5 yd	½ in	Polyester Foam	Up to 200°F	160 lb/in	4929	15C317
White						
	½ in	Acrylic Foam	-31° to 230°F	160 lb/in	4930	15C319
	½ in	Acrylic Foam	50° to 200°F	140 lb/in	4950	15C368
½ in x 5 yd	½ in	Acrylic Foam	32° to 200°F	110 lb/in	4951	15C375
	½ in	Acrylic Foam	50° to 160°F	80 lb/in	4952	15C381
	½ in	Acrylic Foam	50° to 300°F	75 lb/in	4959	15C391
	½ in	Acrylic Foam	-31° to 230°F	160 lb/in	4930	15C323
	½ in	Acrylic Foam	50° to 200°F	140 lb/in	4950	15C372
¾ in x 5 yd	½ in	Acrylic Foam	32° to 200°F	110 lb/in	4951	15C379
	½ in	Acrylic Foam	50° to 160°F	80 lb/in	4952	15C385
	½ in	Acrylic Foam	50° to 300°F	75 lb/in	4959	15C395
	½ in	Acrylic Foam	-31° to 230°F	160 lb/in	4930	15C321
	½ in	Acrylic Foam	30° to 200°F	140 lb/in	4950	15C370
1 in x 5 yd	½ in	Acrylic Foam	32° to 200°F	110 lb/in	4951	15C377
	½ in	Acrylic Foam	50° to 160°F	80 lb/in	4952	15C383
	½ in	Acrylic Foam	50° to 300°F	75 lb/in	4959	15C393
	½ in	Acrylic Foam	-31° to 230°F	160 lb/in	4930	15C322
	½ in	Acrylic Foam	50° to 200°F	140 lb/in	4950	15C371
2 in x 5 yd	½ in	Acrylic Foam	32° to 200°F	110 lb/in	4951	15C378
	½ in	Acrylic Foam	50° to 160°F	80 lb/in	4952	15C384
	½ in	Acrylic Foam	50° to 300°F	75 lb/in	4959	15C394



Double-Sided Film Tape

■ Acrylic adhesive

General Purpose Film—Adhesive on both sides and a pull-away liner, they are intended for one-time, permanent bonding of materials together or mounting of light-duty items such as signs, nameplates, or point-of-purchase (POP) displays.

Repositionable—Adhesive on one side and a light adhesive on the liner side, they are designed for lightweight items such as labels, paper signs, and advertisements that need to be moved or replaced frequently. The light adhesive removes cleanly when items are repositioned.

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Environment	Temperature Range	Series	Brand	Item No.	Pkg. Qty.
Double-Sided General Purpose Film Tape								
Transparent								
½ in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K179	1
1 in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K174	1
1 in x 16 ¾ yd	5.5 mil	Polyester-Backed Film Tape	Indoor Only	65° to 75°F	—	Fast Cap	3VZ25	1
2 in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K175	1
2 in x 16 ¾ yd	5.5 mil	Polyester-Backed Film Tape	Indoor Only	65° to 75°F	—	Fast Cap	3WAA1	1
5 ½ in x 60 yd	7.9 mil	Polyester-Backed Film Tape	Indoor/Outdoor	Up to 355°F	DCP800A2PW	IPG	58NV87	8
White								
1 in x 54 ¾ yd	10.2 mil	Vinyl Film	Indoor Only	0° to 158°F	9087	3M	54EN47	18
Double-Sided Repositionable Film Tape								
Transparent								
1 in x 5 yd	3.5 mil	Vinyl Film	Indoor/Outdoor	60° to 125°F	665	3M	45J518	1
1 in x 72 yd	2 mil	Polyester-Backed Film Tape	Indoor Only	65° to 150°F	9415PC	3M	48UV66	1
2 in x 5 yd	3.5 mil	Vinyl Film	Indoor/Outdoor	60° to 125°F	665	3M	45J519	1

Double-Sided Carpet Mounting Tape

- Rubber adhesive
- Indoor only

The pull-away liner facilitates easy unwinding and can be left in place until the carpet is ready to be attached. It is often used for temporary carpeting of large areas.

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Series	Brand	Item No.
Tan						
1 in x 25 yd	11 mil	Cloth	40° to 200°F	105C	Polyken	15R469
1 ½ in x 25 ¼ yd	11 mil	Cloth	40° to 200°F	105C	Polyken	16D173
1 ¾ in x 36 yd	11 mil	Cloth	35° to 150°F	—	Polyken	35UX91
2 ½ in x 25 ¼ yd	11 mil	Cloth	40° to 200°F	105C	Polyken	15R504
2 ½ in x 25 ¼ yd	11 mil	Cloth	40° to 200°F	105C	Polyken	16D174
White						
1 ½ in x 25 ¼ yd	13 mil	Polyester Coated Cloth	50° to 225°F	DF 642	Shurtape	44MY42

POLYKEN® Shurtape®
TRUE TO YOUR WORK

44MY42

