60FC11





Barcode Label Scanners

ZEBRA

Scanners read barcodes on labels, and capture address and tracking information on items, process inbound and outbound shipments, price products, and manage inventory. They are used in warehouses, retail stores, e-commerce businesses, shipping and receiving departments, product picking tasks, and healthcare facilities. Corded Barcode Label Scanners-Plug into USB outlets. Commonly used at counters at retail stores. Cordless Barcode Label Scanners—Portable scanners are powered by batteries. They are suitable for applications where the scanner needs to be used in many different locations. Industrial Cordless Barcode Label Scanners—These portable scanners are more rugged than standard cordless barcode scanners. They can withstand more impact from being dropped or knocked around during use and are suitable for freezer applications. They are powered by batteries.

| Travel Distance | | | | | | Item |
|----------------------------|------------------------|---------|---|------------------------|--------------|--------|
| from Base | Model Number | Weight | Connec. Type | Image Scan Type | Voltage | No. |
| Corded Barcode La | ibel Scanners | | | | | |
| 30 in | DS2208-SR00006ZZWW | 161.6 g | USB, RS232, Keyboard Wedge, TGCS (IBM), 46XX over RS485 | 1D Scanner, 2D Scanner | 4.5 V, 5.5 V | 60EA80 |
| 30 111 | DS2208-SR7U2100SGW | 161.6 g | USB, RS232, Keyboard Wedge, TGCS (IBM), 46XX over RS485 | 1D Scanner, 2D Scanner | 4.5 V, 5.5 V | 60EA85 |
| 30 in | LI2208-SR00006ZZNA | 140 g | USB | 1D Scanner | 5 V | 60EA74 |
| 30 111 | LI2208-SR00007ZZNA | 140 g | USB | 1D Scanner | 5 V | 60EA75 |
| | LS2208-7AZU0100ZNA | 150 g | USB, RS232, Keyboard Wedge, IBM 468x/9x | 1D Scanner | 5 V | 60EA69 |
| _ | LS2208-SR20001NA | 150 g | USB, RS232, Keyboard Wedge, IBM 468x/9x | 1D Scanner | 5 V | 60EA70 |
| | LS2208-SR20007R-NA | 150 g | USB, RS232, Keyboard Wedge, IBM 468x/9x | 1D Scanner | 5 V | 60EA73 |
| Cordless Barcode | Label Scanners | | | | | |
| | DS2278-SR00006ZZWW | 214 g | USB | 1D Scanner, 2D Scanner | 5 V | 60EA86 |
| 30 in | DS2278-SR7UMC00AZW | 214 g | USB | 1D Scanner, 2D Scanner | 5 V | 60EA91 |
| | DS2278-SR00007ZZWW | 214 g | USB | 1D Scanner, 2D Scanner | 5 V | 60EA87 |
| Industrial Cordless | Barcode Label Scanners | | | | | |
| | LI3678-ER2F003VZWW | 424 g | USB | 1D Scanner | 5 V, 12 V | 60EC11 |
| | LI3678-SR0F003VZWW | 386.5 g | USB | 1D Scanner | 5 V, 12 V | 60EC13 |

13C564

Direct Thermal Labels





Create custom labels with barcodes and other useful information. These blank paper labels do not require a ribbon, ink, or toner for printing. Adhesive backing sticks to surfaces such as packages, shipping containers, and warehouse or retail racks. A compatible thermal barcode label printer is used to print addresses, barcodes, company logos, etc., see page 1328. Direct Thermal Rolls—Multiple labels are stored on a roll core. Colored Direct Thermal Label Rolls—These labels can be used for color-coding shipments, shipping locations, and products in a container.

| Label Width | Label Height | Label Color | Core Dia. | Labels per Roll | Rolls per Case | Brand | Item No. | Label Width | Label Height | Label Color | Core Dia. | Labels per Roll | Rolls per Case | Brand | Item No. |
|----------------|-----------------|----------------|--------------|--------------------|----------------------|---------|-------------|----------------|-----------------|----------------|--------------|--------------------|----------------------|-------|-------------|
| Direct 1 | hermal L | abel Roll | S | | | | | 4 in | 3 in | White | 3 in | 1,000 | 2 | Avery | 49VT62 |
| Printer | Compatil | oility Des | k Top La | bel Printe | r | | | 6 in | 4 in | White | 3 in | 1,000 | 1 | Avery | 49VT58 |
| 3/4 in | 2 in | White | 1 in | 500 | 10 | Dymo | 1ZTB9 | Colored | Direct T | 'hermal La | abel Rol | ls | | | |
| 1 in | 21/8 in | White | 1 in | 500 | 1 | Dymo | 2XZN6 | Printer | Compati | bility Des | k Top La | abel Printe | r | | |
| 11/8 in | 31/2 in | White | 1 in | 260 | 1 | Dymo | 2XZN3 | 11/8 in | 3½ in | Clear | 1 in | 130 | 1 | Dymo | 23M344 |
| 11/8 in | 3½ in | White | 1 in | 350 | 10 | Dymo | 1ZTB7 | Printer | Compati | bility Indu | ıstrial L | abel Printe | er | | |
| 125/64 in | 31/2 in | White | 1 in | 260 | 1 | Dymo | 2XZN4 | 3 in | 2 in | Blue | 3 in | 3,000 | 8 | _ | 60DX42 |
| 21/4 in | 4 in | White | 1 in | 250 | 1 | Dymo | 2XZN8 | 3 in | 2 in | Green | 3 in | 3,000 | 8 | _ | 60DX44 |
| 213/32 in | 17/64 in | White | _ | 800 | 1 | Brother | 13C564 | 3 in | 2 in | Orange | 3 in | 3,000 | 8 | _ | 60DX45 |
| 31/2 in | 17/64 in | White | _ | 400 | 1 | Brother | 13C558 | 3 in | 2 in | Red | 3 in | 3,000 | 8 | _ | 60DX43 |
| 3½ in | 113/32 in | White | | 400 | 1 | Brother | 13C563 | 3 in | 2 in | Yellow | 3 in | 3,000 | 8 | | 60DX41 |
| 329/32 in | 213/32 in | White | _ | 300 | 1 | Brother | 13C559 | 3 in | 5 in | Blue | 3 in | 1,200 | 8 | _ | 60DX47 |
| 4 in | 21/8 in | White | 1 in | 220 | 1 | Dymo | 23M345 | 3 in | 5 in | Green | 3 in | 1,200 | 8 | _ | 60DX49 |
| 4 in | 25/16 in | White | 1 in | 250 | 1 | Dymo | 23M347 | 3 in | 5 in | Orange | 3 in | 1,200 | 8 | _ | 60DX50 |
| 4 in | 25/16 in | White | 1 in | 300 | 10 | Dymo | 1ZTB8 | 3 in | 5 in | Red | 3 in | 1,200 | 8 | _ | 60DX48 |
| 6 in | 4 in | White | | 200 | 1 | Brother | 13C569 | 3 in | 5 in | Yellow | 3 in | 1,200 | 8 | | 60DX46 |
| 6 in | 4 in | White | 1 in | 220 | 1 | Dymo | 23M346 | 4 in | 2 in | Blue | 3 in | 3,000 | 4 | _ | 60DX52 |
| Printer | Compatil | oility Indu | istrial L | abel Printe | er | | | 4 in | 2 in | Green | 3 in | 3,000 | 4 | _ | 60DX54 |
| 2 in | 1 in | White | 3 in | 3,000 | 4 | Avery | 49VT59 | 4 in | 2 in | Orange | 3 in | 3,000 | 4 | _ | 60DX55 |
| 3 in | 2 in | White | 3 in | 1,000 | 4 | Avery | 49VT60 | 4 in | 2 in | Red | 3 in | 3,000 | 4 | _ | 60DX53 |
| 4 in | 2 in | White | 3 in | 1,000 | 2 | Avery | 49VT61 | 4 in | 2 in | Yellow | 3 in | 3,000 | 4 | | 60DX51 |



13F532 4LT32

Heat Poly Bag Sealers

Seal parts in plastic bags for shipping, distribution, or storage. Bag sealers use pressure and heat to close poly bags with a watertight, airtight seal. They crimp the top of a bag and apply heat that melts a strip of the bag to close it. Foot Operated—These sealers help with floor sealing jobs. Tabletop Impulse Sealers—Spot crimp sealing for flat and gusseted poly bags or poly tubing. Repair Kits-Include heating element, lower PTFE tape, and upper PTFE fabric.

| Max. Seal Length | Max. Seal Width | Max. Seal Thick. | Overall Height | Overall Length | Heat Sealing Type | Includes Cutter | Item No. | KITS Item No. | | | | |
|--------------------------|-----------------------|------------------------|-------------------|-------------------|-------------------------|--------------------|-------------|---------------------|--|--|--|--|
| Foot-Operated Sealers | | | | | | | | | | | | |
| 17¾ in | 1/8 in | 7 mil | 361/4 in | 20½ in | Impulse | No | 4LT32 | 5ZZ45 | | | | |
| 23% in | 1/8 in | 7 mil | 361/4 in | 26¾ in | Impulse | No | 5ZZ47 | 5ZZ48 | | | | |
| Tabletop Impulse Sealers | | | | | | | | | | | | |
| 6 in | 5/8 in | 7 mil | 4 in | 71/s in | Direct | No | 13F532 | | | | | |
| 7% in | 1/8 in | 6 mil | 81/4 in | 121/4 in | Impulse | No | 4LT36 | 5ZZ56 | | | | |
| 111/8 in | 1/8 in | 6 mil | 8¾ in | 181/s in | Impulse | No | 4LT28 | 5ZZ38 | | | | |
| 111/8 in | 1/8 in | 6 mil | 11 in | 18½ in | Impulse | Yes | 5ZZ35 | 2VAE2 | | | | |
| 111/8 in | 5⁄8 in | 7 mil | 31/8 in | 11% in | Direct | No | 13F534 | | | | | |
| 15¾ in | 1/8 in | 7 mil | 10% in | 21% in | Impulse | No | 5ZZ40 | 5ZZ42 | | | | |
| 20½ in | 1/8 in | 7 mil | 11% in | 26% in | Impulse | No | 2LED7 | 2LEE4 | | | | |
| 235/8 in | 1/8 in | 7 mil | 13 in | 32¾ in | Impulse | No | 2LED8 | 2LEE5 | | | | |

1356