



General Purpose Masking Tape

- Tan color
- Rubber adhesive
- Indoor use only

This tape has a stronger adhesive than painter's tape and may leave adhesive residue when removed. It is used for temporary holding, wrapping, marking, and labeling applications.

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Series	Brand	Item No.	Pkg. Qty.
½ in x 60 yd	5 mil	Crepe Paper	50° to 140°F	PG500	lpg	23M224	72
	5 mil	Crepe Paper	50° to 150°F	TC083	—	497C11	1
	5.1 mil	Crepe Paper	Up to 150°F	101+	3M	19YP47	72
¼ in x 60 yd	5 mil	Crepe Paper	50° to 140°F	PG500	lpg	23M205	48
	5.1 mil	Crepe Paper	Up to 150°F	101+	3M	19YP48	48
¾ in x 60 yd	7 mil	Kraft Paper	30° to 225°F	TC450	—	497C39	1
	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	52JE62	1
	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	29WT52	36
½ in x 60 yd	5 mil	Crepe Paper	50° to 140°F	PG500	lpg	23M206	36
	5.1 mil	Crepe Paper	Up to 150°F	101+	3M	19YP49	36
	6.3 mil	Crepe Paper	50° to 200°F	PG5	lpg	23M218	36
1 in x 60 yd	4.8 mil	Crepe Paper	60° to 150°F	TC106	—	497C19	1
	5 mil	Crepe Paper	50° to 150°F	TC083	—	497C13	1
	6.3 mil	Kraft Paper	Up to 325°F	TC650	—	497C89	1
1 ½ in x 60 yd	7 mil	Kraft Paper	30° to 225°F	TC450	—	497C40	1
	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	52JE63	1
	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	29WT53	24
1 ½ in x 60 yd	6.3 mil	Crepe Paper	50° to 200°F	PG5	lpg	23M219	24
	7 mil	Kraft Paper	30° to 225°F	TC450	—	497C41	1
	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	35HX18	1
1 ½ in x 60 yd	4.4 mil	Crepe Paper	Up to 200°F	201+	3M	29WT54	24
	5 mil	Crepe Paper	50° to 140°F	PG500	lpg	23M207	24
	5 mil	Crepe Paper	50° to 150°F	CP 83	Shurtape	22XN45	1
1 ½ in x 60 yd	5.1 mil	Crepe Paper	Up to 150°F	101+	3M	19YP51	24
	6.3 mil	Crepe Paper	50° to 200°F	PG5	lpg	23M203	24
	5 mil	Crepe Paper	50° to 150°F	TC083	—	497C15	1
2 in x 60 yd	6.3 mil	Kraft Paper	Up to 325°F	TC650	—	497C91	1
	7 mil	Kraft Paper	30° to 225°F	TC450	—	497C42	1

Electroplating Masking Tape

- Lead backing
- Silver color
- Rubber adhesive
- Indoor use only
- Temp. range: -60° to 225°F

Masking tape is electrically and thermally conductive and protects surfaces in electroplating applications. This pliable tape conforms to detailed shapes for masking areas that are not intended for exposure, and removes cleanly after use.



15D106

Imperial Tape WxL	Tape Thickness	Series	Item No.
½ in x 5 yd	6.3 mil	421	15D110
	6.8 mil	420	15D104
¾ in x 5 yd	6.3 mil	421	15D113
	6.8 mil	420	15D107
1 in x 5 yd	6.3 mil	421	15D111
	6.8 mil	420	15D105
2 in x 5 yd	6.3 mil	421	15D112
	6.8 mil	420	15D106

Sealing Foam Tape

- Series 4500
- Black color
- Indoor and outdoor use
- Temp. range: 0° to 250°F

These continuous rolls of tape have a vinyl foam backing that is flexible and conforms to uneven surfaces. The acrylic adhesive adheres to surfaces when pressure is applied and provides cushioning, insulates from weather, dampens sound, and absorbs vibration. It can be used in applications for weather stripping, protecting equipment, and insulating pipes to prevent condensation.



15D042

Imperial Tape WxL	Tape Thickness	Item No.
¾ in x 5 yd	½ in	15D042
	¼ in	15D041
1 in x 5 yd	½ in	15C924
	¼ in	15C923



Drywalling Fiberglass Mesh Tape
6FFA4

High-Temperature Sealing
15C122

Outdoor Line Set
10A411



Sealing Cloth & Film Tape

- Indoor and outdoor use, except No. 6FFA4 is indoor use only

These continuous rolls of tape are high-strength, durable, and have an adhesive on one side that conforms and adheres to uneven surfaces when pressure is applied.

Drywalling Fiberglass Mesh Tape—It has a light adhesive to keep the tape in place while compounds are applied. This tape is used to reinforce sealants such as paint-on mastic in ductwork and joint compounds or mud in drywall applications.

High-Temperature Sealing Glass Cloth Tape—Tape wraps and seals ducts, cables, and pipes in high-heat applications such as thermal spray masking and submerged arc welding.

Outdoor Line Set Film Tape—This tape is UV- and weather-resistant. Line sets are hoses and fittings that connect indoor HVAC equipment to outdoor equipment such as a condenser.

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Tape Adhesive Material	Temperature Range	Series	Brand	Item No.
Drywalling Fiberglass Mesh Tape							
White							
1 ½ in x 100 yd	9 mil	Fiberglass	Acrylic	50° to 200°F	MJ 100	Shurtape	6FFA4
High-Temperature Sealing Glass Cloth Tape							
White							
½ in x 5 yd	5 mil	Glass Cloth	Silicone	-65° to 450°F	3615	3M	15C122
½ in x 60 yd	5.4 mil	Glass Cloth	Silicone	-65° to 450°F	361	3M	15D056
1 in x 5 yd	5 mil	Glass Cloth	Silicone	-65° to 450°F	3615	3M	15C123
2 in x 5 yd	5 mil	Glass Cloth	Silicone	-65° to 450°F	3615	3M	15C124
Outdoor Line Set Film Tape							
Black							
1 ½ in x 60 yd	2.85 mil	Polypropylene Coated Cloth	Acrylic	-35° to 210°F	LS 300	Shurtape	10A411

POLYKEN® Residue-Free Gaffer's Tape

- Series 510
- 11.5 mil thickness
- Indoor and outdoor use
- Temp. range: 40° to 200°F

Gaffer's tape has a heavy, vinyl coated cloth-backing and does not leave an adhesive residue. The rubber adhesive adheres well to a variety of surfaces, including carpet. It is water- and heat-resistant, but less conformable than duct tape. This tape is often used to temporarily secure lighting and cables without causing surface damage. It is also used in assembly, manufacturing, construction, general maintenance and repair.



Black
22VC17

Imperial Tape WxL	Item No.
Black	
1 in x 55 yd	22VC30
1 ½ in x 55 yd	22VC17
1 ½ in x 54 yd	22VC29
2 ¼ in x 54 yd	22VC31
4 in x 55 yd	19YP90
Brown	
1 ½ in x 54 yd	22VC20
2 ¼ in x 54 yd	22VC22
Fluorescent Green	
1 ½ in x 49 yd	15R497
Fluorescent Pink	
1 ½ in x 49 yd	15R494
Gray	
1 ½ in x 54 yd	22VC27
2 ¼ in x 54 yd	22VC28
Green	
1 ½ in x 54 yd	22VC24
2 ¼ in x 54 yd	22VC23
Orange	
1 ½ in x 49 yd	15R495
Red	
1 in x 55 yd	22VC16
1 ½ in x 54 yd	22VC25
White	
1 in x 55 yd	22VC18
1 ½ in x 54 yd	22VC19
2 ¼ in x 54 yd	22VC26
Yellow	
1 ½ in x 49 yd	15R496
1 ½ in x 54 yd	22VC21