



CONTINUED

## Double-Sided VHB (Very High Bond) Foam Tape & Tape Shapes



Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Series	Item No.
<b>Double-Sided VHB Low-Temperature Conformable Foam Tape</b>					
<b>Gray</b>					
1/2 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4943F	15C358
3/4 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4943F	15C362
1 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4957	15C390
1 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4943F	15C360
1 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4957	15C388
2 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4943F	15C361
2 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4957	15C389
<b>Double-Sided VHB Conformable Foam Tape</b>					
<b>Gray</b>					
1/2 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4926	15C310
1/2 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4936	15C325
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP16	15C882
1/2 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP32	15C886
1/2 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP45	15C888
1/2 in x 5 yd	1/16 in	Acrylic Foam	60° to 200°F	4941	15C332
1/2 in x 5 yd	3/32 in	Acrylic Foam	-31° to 194°F	4991	15C397
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP16	15C835
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP25	15C837
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP32	15C839
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP45	15C841
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP62	15C843
1/2 in x 36 yd	1/2 in	Acrylic Foam	40° to 300°F	4941	24A690
3/4 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4926	15C314
3/4 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4936	15C329
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP62	15D048
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP16	15D018
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP25	15D019
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP32	15D020
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP45	15D021
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP62	15D022
3/4 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4926	15C312
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP16	15C936
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP25	15C937
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP32	15C938
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP45	15C939
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP62	15C940
3/4 in x 5 yd	1/2 in	Acrylic Foam	60° to 200°F	4941	15C334
3/4 in x 5 yd	3/32 in	Acrylic Foam	-31° to 194°F	4991	15C399
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP16	15C822
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP25	15C823
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP32	15C824
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP45	15C825
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP62	15C826

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Series	Item No.
2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP25	15C978
2 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP32	15C979
2 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP45	15C980
2 in x 5 yd	1/16 in	Acrylic Foam	50° to 250°F	RP62	15C981
2 in x 5 yd	1/16 in	Acrylic Foam	60° to 200°F	4941	15C335
2 in x 5 yd	3/32 in	Acrylic Foam	-31° to 194°F	4991	15C401
2 in x 5 yd	1/2 in	Acrylic Foam	50° to 250°F	RP25	15C944
2 in x 18 yd	1/16 in	Acrylic Foam	50° to 250°F	RP45	15C946
2 in x 18 yd	1/16 in	Acrylic Foam	50° to 250°F	RP62	15C947
11 in x 5 yd	1/2 in	Acrylic Foam	-31° to 194°F	4936	15C327
12 in x 5 yd	1/16 in	Acrylic Foam	60° to 200°F	4941	15C333
12 in x 5 yd	3/32 in	Acrylic Foam	-31° to 194°F	4991	15C398
<b>Double-Sided VHB Firm Foam Tape</b>					
<b>Black</b>					
1/2 in x 5 yd	1/2 in	Polyester Foam	Up to 200°F	4929	15C316
1/2 in x 5 yd	1/16 in	Acrylic Foam	Up to 200°F	4949	15C364
3/4 in x 5 yd	1/2 in	Polyester Foam	Up to 200°F	4929	15C318
3/4 in x 5 yd	1/16 in	Acrylic Foam	Up to 200°F	4949	15C366
1 in x 5 yd	1/2 in	Polyester Foam	Up to 200°F	4929	15C317
1 in x 5 yd	1/16 in	Acrylic Foam	Up to 200°F	4949	15C365
<b>White</b>					
1/2 in x 5 yd	1/2 in	Acrylic Foam	-31° to 230°F	4930	15C319
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 200°F	4950	15C368
1/2 in x 5 yd	1/2 in	Acrylic Foam	32° to 200°F	4951	15C375
1/2 in x 5 yd	1/16 in	Acrylic Foam	50° to 160°F	4952	15C381
1/2 in x 5 yd	1/16 in	Acrylic Foam	50° to 300°F	4959	15C391
1/2 in x 5 yd	1/2 in	Acrylic Foam	-31° to 230°F	4930	15C323
1/2 in x 5 yd	1/2 in	Acrylic Foam	50° to 200°F	4950	15C372
3/4 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4951	15C379
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 160°F	4952	15C385
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 300°F	4959	15C395
3/4 in x 5 yd	1/2 in	Acrylic Foam	-31° to 230°F	4930	15C321
3/4 in x 5 yd	1/2 in	Acrylic Foam	30° to 200°F	4950	15C370
3/4 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4951	15C377
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 160°F	4952	15C383
3/4 in x 5 yd	1/16 in	Acrylic Foam	50° to 300°F	4959	15C393
3/4 in x 5 yd	1/2 in	Acrylic Foam	-31° to 230°F	4930	15C322
3/4 in x 5 yd	1/2 in	Acrylic Foam	50° to 200°F	4950	15C371
2 in x 5 yd	1/16 in	Acrylic Foam	32° to 200°F	4951	15C378
2 in x 5 yd	1/16 in	Acrylic Foam	50° to 160°F	4952	15C384
2 in x 5 yd	1/16 in	Acrylic Foam	50° to 300°F	4959	15C394

Imperial Tape WxL	Tape Thickness	Product Form	Temperature Range	Series	Item No.
<b>Double-Sided VHB Conformable Foam Tape Shapes</b>					
<b>Gray</b>					
1 in x 1 in	1/16 in	Square	60° to 200°F	4941	15C348
1 in x 2 in	1/16 in	Strip	60° to 200°F	4941	15C342
1 1/2 in x 1 1/2 in	1/16 in	Square	60° to 200°F	4941	15C347
2 in dia	1/16 in	Disc	60° to 200°F	4941	15C349



General Purpose  
45K174



Repositionable  
48UV66

## Double-Sided Film Tape

Acrylic adhesive  
**General Purpose Film**—Adhesive on both sides and a pull-away liner, they are intended for one-time, permanent bonding of materials together or mounting of light-duty items such as signs, nameplates, or point-of-purchase (POP) displays.



**Repositionable**—Adhesive on one side and a light adhesive on the liner side, they are designed for lightweight items such as labels, paper signs, and advertisements that need to be moved or replaced frequently. The light adhesive removes cleanly when items are repositioned.

Imperial Tape WxL	Tape Thickness	Tape Backing Material	Environment	Temperature Range	Series	Brand	Item No.	Pkg. Qty.
<b>Double-Sided General Purpose Film Tape</b>								
<b>Transparent</b>								
1/2 in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K179	1
1 1/2 in x 5 3/4 yd	5 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	54EN04	36
1 in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K174	1
1 in x 16 3/4 yd	5.5 mil	Polyester-Backed Film Tape	Indoor Only	65° to 75°F	—	Fast Cap	3VZ25	5
2 in x 5 yd	8.3 mil	Polyester-Backed Film Tape	Indoor/Outdoor	-10° to 200°F	9088	3M	45K175	1
2 in x 16 3/4 yd	5.5 mil	Polyester-Backed Film Tape	Indoor Only	65° to 75°F	—	Fast Cap	3WAA1	1
5 1/4 in x 60 yd	7.9 mil	Polyester-Backed Film Tape	Indoor/Outdoor	Up to 355°F	DCP800A2PW	IPG	58NV87	8
<b>White</b>								
1 in x 54 3/4 yd	10.2 mil	Vinyl Film	Indoor Only	0° to 158°F	9087	3M	54EN47	18
<b>Double-Sided Repositionable Film Tape</b>								
<b>Transparent</b>								
1 in x 5 yd	3.5 mil	Vinyl Film	Indoor/Outdoor	60° to 125°F	665	3M	45J518	1
1 in x 72 yd	2 mil	Polyester-Backed Film Tape	Indoor Only	65° to 150°F	9415PC	3M	48UV66	1
2 in x 5 yd	3.5 mil	Vinyl Film	Indoor/Outdoor	60° to 125°F	665	3M	45J519	1



44MY42

## Double-Sided Carpet Mounting Tape

Rubber adhesive  
Indoor only  
The pull-away liner facilitates easy unwinding and can be left in place until the carpet is ready to be attached. It is often used for temporary carpeting of large areas.



Imperial Tape WxL	Tape Thickness	Tape Backing Material	Temperature Range	Series	Brand	Item No.
<b>Tan</b>						
1 in x 25 yd	11 mil	Cloth	40° to 200°F	105C	Polyken	15R469
1 7/8 in x 25 1/4 yd	11 mil	Cloth	40° to 200°F	105C	Polyken	16D173
1 7/8 in x 25 1/4 yd	11 mil	Cloth	35° to 150°F	—	Polyken	35UX91
1 7/8 in x 36 yd	11 mil	Cloth	40° to 200°F	105C	Polyken	15R504
2 1/8 in x 25 1/4 yd	11 mil	Cloth	40° to 200°F	105C	Polyken	16D174
<b>White</b>						
1 7/8 in x 25 1/4 yd	13 mil	Polyester Coated Cloth	50° to 225°F	DF 642	Shurtape	44MY42